

Submit 1 Copy To Appropriate District Office  
District I - (575) 393-6161  
1625 N. French Dr., Hobbs, NM 88240  
District II - (575) 748-1283  
811 S. First St., Artesia, NM 88210  
District III - (505) 334-6178  
1000 Rio Brazos Rd., Aztec, NM 87410  
District IV - (505) 476-3460  
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico  
Energy, Minerals and Natural Resources

Form C-103  
Revised July 18, 2013

OIL CONSERVATION DIVISION  
1220 South St. Francis Dr.  
Santa Fe, NM 87505

WELL API NO. 30-025-27615
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LO-6792-0005
7. Lease Name or Unit Agreement Name Susco 3 State
8. Well Number 1
9. OGRID Number 288173
10. Pool name or Wildcat Sawyer San Andres West

SUNDRY NOTICES AND REPORTS ON WELLS  
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator  
Stanolind Operating DBA Stanolind NM LLC

3. Address of Operator  
310 W. Wall, Suite 1000, Midland, Texas 79701

4. Well Location  
Unit Letter D : 660 feet from the North line and 460 feet from the West line  
Section 3 Township 10S Range 37E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)  
3967' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒  
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐  
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐  
DOWNHOLE COMMINGLE ☐  
CLOSED-LOOP SYSTEM ☐  
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐  
COMMENCE DRILLING OPNS. ☐ P AND A ☐  
CASING/CEMENT JOB ☐  
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8 5/8" 24# casing set @ 472', cemented w/ 350 sx Class "C", circulated to surface  
4 1/2" 9.5 and 10.5# casing set @ 5012', cemented w/ 1200 sx Lite and 300 sx Class "C", cement top 1670' (CBL)  
San Andres perforations 4969-5006'.

Stanolind proposes to plug and abandon as follows:

- Set CIBP @ 4900, dump 2 sx Class "C" cement on plug
- TIH and displace with mud laden fluid.
- Spot 20 sx Class "C" cement from 2840' to 2740'. ~~If hole is not standing full~~, WOC and tag.
- Spot 20 sx Class "C" cement from 2260' to 2160'. ~~If hole is not standing full~~, WOC and tag.
- Perforate the 4 1/2" casing @ 522', circulate cement to surface, leaving the hole full of cement. Estimated volume is 140 sx.
- Cut off wellhead and install P&A marker plate (location within LPC area).
- Clean and level location.

A closed-loop system will be used. Notice will be given 24 hours before setting all plugs.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Sgt. M. Pat TITLE Ex. VP- OPERATIONS DATE 5/9/14

Type or print name \_\_\_\_\_ E-mail address: \_\_\_\_\_ PHONE: \_\_\_\_\_

For State Use Only

APPROVED BY: Mark Brown TITLE Dist. Supervisor DATE 5/13/2014

Conditions of Approval (if any):

MAY 13 2014

**PRIOR TO P&A**

**Stanolind Operating LLC DBA Stanolind NM LLC**

WELL NAME:	Susco "3" State #1			FIELD:	Sawyer		
LOCATION:	S3 T10S R37E			API #:	30-025-27615		
COUNTY:	Lea		ST:	NM		SPUD DATE:	07/09/73
KB:	3677'	GL:	3967'	TD:	5013'	PBTD:	5010'

**8 5/8" @ 472' cmt'd w/ 350 sx (circ)**

**TOC 1670' CBL**

**Perfs 4969-5006'**

**4 1/2" @ 5011' Cmt'd w/ 1500 sx**

# AFTER P&A

WELL NAME:	Susco "3" State #1	FIELD:	Sawyer
LOCATION:	S3 T10S R37E	API #:	30-025-27615
COUNTY:	Lea	ST:	NM
KB:	3677'	GL:	3967'
TD:	5013'	PBTD:	5010'
SPUD DATE:	07/09/73		

8 5/8" @ 472' cmt'd w/ 350 sx (circ)

Perf @ 522' and circulate cement to surface, estimated 140 sx

## Formation Tops:

Top anhydrite	2260'
Base of salt	2840'
Yates	3050'
7 Rivers	2972'
Queen	3268'
Grayburg	3774'
Sam Andres	4230'

TOC 1670' CBL

20 sack cement plug @ 2260'

20 sack cement plug @ 2840'

CIBP @ 4900' plus 20' of cement

Perfs 4969-4996'

4 1/2" @ 5012' Cmt'd w/ 1500 sx