

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

OCB Hobbs

FORM APPROVED
OMB No. 1004-0137
Expires: March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE- Other instructions on reverse side.

1. Type of Well <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other		HOBBS OCB	5. Lease Serial No. NM-086
2. Name of Operator Armstrong Energy Corporation		MAY 21 2014	6. If Indian, Allottee or Tribe Name
3a. Address P.O. Box 1973, Roswell, NM 88202-1973	3b. Phone No. (include area code) 575-625-2222	RECEIVED	7. If Unit or CA/Agreement, Name and/or No.
4. Location of Well (Footage, Sec., T., R., M., or Survey Description) Unit N, 990' FSL & 1650' FWL, Sec 25, T19S-R34E			8. Well Name and No. Superior Federal #6
			9. API Well No. 30-025-21745
			10. Field and Pool, or Exploratory Area Pearl Queen
			11. County or Parish, State Lea County, New Mexico

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input checked="" type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other
	<input type="checkbox"/> Change Plans	<input checked="" type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

- Contact BLM 24 hrs prior to beginning any plugging operations. (Lea County Wells: 575-393-3612)
- MI RU, ND WH, NU BOP, POH w/ production tbg.
- RU Wireline and set CIBP @ 4,740'.
- TIH w/ tbg to 4,740', circ hole w/ 9.2 ppg mud. Spot 25 sx cement on top of CIBP. Pull up to 3,170', spot 25 sx plug. PUH, WOC 4 hrs, tag plug.
- POH, RU Wireline and perf 4 shots @ 1,982'. TIH w/ tbg and pump 75 sx Class "C" w/ 2% CaCl plug, displace to 1,862'. PUH, WOC 4 hrs, tag plug.
- POH, RU Wireline and perf 4 shots @ 298'. TIH w/ tbg and pump 75 sx Class "C" plug, circ annular volume to Surface and fill 5.5" csg to Surface for full 298' surface plug.
- Cut off WH and mast anchors 3' below G.L.
- Install ground level Dry Hole marker.
- Notify authorized BLM officer before release rig. Upon approval, RD and move out.
- Clean location, remove caliche, rip road and location, re-seed.

RECLAMATION PROCEDURE
ATTACHED

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

*Ground level Dry Hole Marker Required. CPC Timing Restrictions

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed) Kyle Alpers Title Field Engineer

Signature [Signature] Date 04/18/2014

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by [Signature] Title SEPS Date 5-18-14

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office CFO

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

MWB/ocb 5/22/2014

MAY 22 2014

Armstrong Energy Corporation
P.O. Box 1973
Roswell, NM 88202-1973



Well: Superior Federal #6

P&A Procedures

1. Contact BLM office 24 hours prior to beginning any plugging operations.
(Lea County Wells 575-393-3612)
2. MI RU, ND W.H., NU BOP, POOH with production tubing.
3. Rig up W.L. and set CIBP @ 4,740'.
4. TIH w/tbg to 4,740', circulate hole w/ 9.2ppg mud. Spot 25 sx cement on top of CIBP. Pull up to 3,170', spot 25 sx plug. PUH, WOC 4 hrs, tag plug
5. POOH, rig up wireline and perforate 4 shots @ 1,982'. TIH w/tbg and pump 75 sx Class "C" w2% CaCl plug, displace to 1,862'. PUH, WOC 4 hrs, tag plug
6. POOH, rig up wireline and perforate 4 shots @ 298'. TIH w/tbg and pump 75 sx Class "C" plug, circulate annular volume to surface and fill 5.5" casing to surface for full 298' surface plug.
7. Cut off WH & mast anchors 3' below G.L.
8. Install ground level dry hole marker,
9. Notify authorized BLM officer before release rig, upon approval RDMO
10. Clean location, remove caliche, rip road and location, reseed.



CURRENT
LAST UPDATED
4/15/2014

3,730' GR

Anhydrite - 1,807'

Salt - 1,932'

Base of Salt - 3,120'

Yates - 3,535'

Queen - 4,616'

Penrose - 4,938'

11" hole
8 5/8" 24#/ft @ 248'
125sx - Circulated

7 7/8" hole

TOC - 2,960'

Queen Sand
Perforations - 4/11/1966
4811', 4814', 4899', 4903', 4967', 4971',
4992', 5011', 5015', 1spf ea

5 1/2" 15.5#/ft @ 5,139'
TD 5,150' PBTD 5,139'


<p>Armstrong Energy Corporation Superior Federal #6 Unit N 900' FSL & 1650' FWL Section 25, T19S, R34E Lea County, New Mexico API Number 30-025-21745 Lease Serial No. NM-086 Spud Date: 3/23/1966</p>
<p>Downhole Production Equipment 146 jts 2 3/8" 4:7# tbg</p>
<p>Surface Production Equipment</p>
<p>Notes Originally drilled and operated by D.W. St. Clair</p>

STIMULATION
Frac thru perms, 30,000gal, 30,000# sd

270sx 50-50 Lite Poz



PROPOSED
LAST UPDATED
4/15/2014



Anhydrite - 1,807'

Salt - 1,932'

Base of Salt - 3,120'

Yates - 3,535'

Queen - 4,616'

Penrose - 4,938'

11" hole
8 5/8" 24#/ft @ 248'
125sx - Circulated

PERF @ 298', PUMP 75SX PLUG
CIRC ANNULAR VOL. TO SURFACE
AND FILL 5.5" CSG TO SURFACE

7 7/8" hole

PERF @ 1982', PUMP 75 SX. PLUG

TOC - 2,960'

150'+ PLUG 3170'-3020', 25 SX

CIBP @ 4740' w/35' CEMENT - 25 sx cont

Queen Sand
Perforations - 4/11/1966
4811', 4814', 4899', 4903', 4967', 4971',
4992', 5011', 5015', 1spf ea

Armstrong Energy Corporation
Superior Federal #6
Unit N 900' FSL & 1650' FWL
Section 25, T19S, R34E
Lea County, New Mexico
API Number 30-025-21745
Lease Serial No. MM-086
Spud Date: 3/23/1966

Downhole Production
Equipment

Surface Production
Equipment

Notes
PROPOSED PLUGS
CIBP @ 4,740' w/35' cement
25sx cement @ 3,170' - 150'+
Perforate @ 1,982', squeeze 75
sx plug
298' surface plug

5 1/2" 15.5#/ft @ 5,139'
TD 5,150' PBSD 5,139'

STIMULATION
Frac thru perms, 30,000gal, 30,000# sd
270sx 50-50 Lite Poz

BUREAU OF LAND MANAGEMENT
Carlsbad Field Office
620 East Greene Street
Carlsbad, New Mexico 88220
575-234-5972

Permanent Abandonment of Federal Wells
Conditions of Approval

Failure to comply with the following Conditions of Approval may result in a Notice of Incidents of Noncompliance (INC) in accordance with 43 CFR 3163.1.

1. Plugging operations shall commence within ninety (90) days from the approval date of this Notice of Intent to Abandon.

If you are unable to plug the well by the 90th day provide this office, prior to the 90th day, with the reason for not meeting the deadline and a date when we can expect the well to be plugged. Failure to do so will result in enforcement action.

2. Notification: Contact the appropriate BLM office at least 24 hours prior to the commencing of any plugging operations. For wells in Chaves and Roosevelt County, call 575-627-0272; Eddy County, call 575-361-2822; Lea County, call 575-393-3612.

3. Blowout Preventers: A blowout preventer (BOP), as appropriate, shall be installed before commencing any plugging operation. The minimum BOP requirement is a 2M system for a well not deeper than 9,090 feet; a 3M system for a well not deeper than 13,636 feet; and a 5M system for a well not deeper than 22,727 feet.

4. Mud Requirement: Mud shall be placed between all plugs. Minimum consistency of plugging mud shall be obtained by mixing at the rate of 25 sacks (50 pounds each) of gel per 100 barrels of water. Minimum nine (9) pounds per gallon.

5. Cement Requirement: Sufficient cement shall be used to bring any required plug to the specified depth and length. Any given cement volumes on the proposed plugging procedure are merely estimates and are not final. Unless specific approval is received, no plug except the surface plug shall be less than 25 sacks of cement. In lieu of a cement plug in a cased hole, a bridge plug set within 50 feet to 100 feet above the perforations shall be capped with 25 sacks of cement. If a bailer is used to cap this plug, 35 feet of cement shall be sufficient.

Unless otherwise specified in the approved procedure, the cement plug shall consist of either Neat Class "C", for up to 7,500 feet of depth or Neat Class "H", for deeper than 7,500 feet plugs.

6. Dry Hole Marker: All casing shall be cut-off at the base of the cellar or 3 feet below final restored ground level (whichever is deeper). The well bore shall then be capped with a 4-inch pipe, 10'-feet in length, 4 feet above ground and embedded in cement. The following information shall be permanently inscribed on the dry hole marker: well name and number, name of the operator, lease serial number, surveyed location (quarter-quarter section, section, township and range or other authorized survey designation acceptable to the authorized officer such as metes and bounds).

7. Subsequent Plugging Reporting: Within 30 days after plugging work is completed, file one original and five copies of the Subsequent Report of Abandonment, Form 3160-5 to BLM. The report should give in detail the manner in which the plugging work was carried out, the extent (by depths) of cement plugs placed, and the size and location (by depths) of casing left in the well. Show date well was plugged.

8. Trash: All trash, junk and other waste material shall be contained in trash cages or bins to prevent scattering and will be removed and deposited in an approved sanitary landfill. Burial on site is not permitted.

Following the submission and approval of the Subsequent Report of Abandonment, surface restoration conditions of approval will be developed and furnished to you.

Timing Limitation Stipulation / Condition of Approval for lesser prairie-chicken:

Oil and gas activities including 3-D geophysical exploration, and drilling will not be allowed in lesser prairie-chicken habitat during the period from March 1st through June 15th annually. During that period, other activities that produce noise or involve human activity, such as the maintenance of oil and gas facilities, pipeline, road, and well pad construction, will be allowed except between 3:00 am and 9:00 am. The 3:00 am to 9:00 am restriction will not apply to normal, around-the-clock operations, such as venting, flaring, or pumping, which do not require a human presence during this period. Additionally, no new drilling will be allowed within up to 200 meters of leks known at the time of permitting. Normal vehicle use on existing roads will not be restricted. Exhaust noise from pump jack engines must be muffled or otherwise controlled so as not to exceed 75 db measured at 30 feet from the source of the noise.

Ground-level Abandoned Well Marker to avoid raptor perching: Upon the plugging and subsequent abandonment of the well, the well marker will be installed at ground level on a plate containing the pertinent information for the plugged well. For more installation details, contact the Carlsbad Field Office at 575-234-5972.

Requirements for ground level dry hole markers

Well Identification Markers

Conditions of Approval (COA)

The BLM Carlsbad Field Office (CFO) Conditions of Approval (COA) Requires that ground level dry hole markers be placed on well within the Lesser Prairie Chicken habitat area. The dry hole markers will be to the following specifications. The operator will construct the markers as follows:

1. An 8 inch X 8 inch steel plate 1/8 to 3/16 of an inch thick is to be placed on the old dry hole marker stand pipe 2 inches from ground level, in the Lesser Prairie Chicken habitat area.
2. Steel plate may be welded or bolted approximately 2 inches from ground level on the stand pipes. If plates are bolted to the stand pipe, the person installing the plate will be required to weld a pipe collar on the plate and place a minimum of two set screws/bolt on each collar. Aluminum data plates may be bolted with minimum ¼ inch bolt and locking nuts or self tapping fine threaded screws. A minimum of one in each corner is to be installed on each plate.
3. An 8 inch x 8 inch aluminum plate, which is 12 gauge or .080 sign material (1/8 inch aluminum plate may be used in place of the .080 plate) with the required information for that well stamped or engraved in a minimum 3/8 inch, tall letter or number.
4. The following information will be stamped or engraved on the 8 inch X 8 inch aluminum plate in the following order.
 - a. First row: Operators name
 - b. Second row: Well name and number
 - c. Third row: Legal location to include ¼ ¼, Section, Township, and range. If the legal location cannot be placed on one row it can be split into two rows with the ¼ ¼ (example: 1980 FNL 1980 FWL) being on the top row.
 - d. Fourth row: Lease Number and API number.
 - i. Example marker plate: (attached)

NMOCD Order No. R-12965 also required the operator to notify NMOCD when this type of dry hole marker is used. This can be done on the subsequent report of abandonment which is submitted to the BLM after the well is plugged. State that a ground level dry hole marker was installed as required in the COA's from the BLM.



United States Department of the Interior

BUREAU OF LAND MANAGEMENT

Carlsbad Field Office
620 E. Greene St.
Carlsbad, New Mexico 88220-6292
www.blm.gov/nm



In Reply Refer To: 1310

Interim Reclamation Procedures

Reclamation Objective: Oil and gas development is one of many uses of the public lands and resources. While development may have a short- or long-term effect on the land, successful reclamation can ensure the effect is not permanent. During the life of the development, all disturbed areas not needed for active support of production operations should undergo "interim" reclamation in order to minimize the environmental impacts of development on other resources and uses.

Interim reclamation consists of minimizing the footprint of disturbance by reclaiming all portions of the well site not needed for production operations. The portions of the cleared well site not needed for operational and safety purposes are recontoured to a final or intermediate contour that blends with the surrounding topography as much as possible. Sufficient level area remains for setup of a workover rig and to park equipment. Topsoil is respread over areas not needed for all-weather operations¹. Production facilities should be clustered to maximize the opportunity for interim reclamation. In order to inspect and operate the well or complete workover operations, it may be necessary to drive, park, and operate on restored, interim vegetation within the previously disturbed area. This is generally acceptable provided damage is repaired and reclaimed following use.

To reduce final reclamation costs; maintain healthy, biologically active topsoil; and to minimize habitat, visual, and forage loss during the life of the well, all salvaged topsoil should be spread over the area of interim reclamation, rather than stockpiled.

1. The Application for Permit to Drill or Reenter (APD, Form 3160-3), Surface Use Plan of Operations must include adequate measures for stabilization and reclamation of disturbed lands. Oil and Gas operators must plan for reclamation, both interim and final, up front in the APD process as per Onshore Oil and Gas Order No. 1.
2. For wells and/or access roads not having an approved plan, or an inadequate plan for surface reclamation (either interim or final reclamation), the operator must submit a proposal describing the procedures for reclamation. For interim reclamation, the appropriate time for submittal would be when filing the Well Completion or Recompletion Report and Log (Form 3160-4). Interim reclamation is to be completed within 6 months of well completion.
3. If you have an approved Surface Use Plan of Operation and/or an approved Sundry Notice, you are free to proceed with interim reclamation as per approved APD or Sundry Notice. If you have issues or concerns, contact a BLM specialist to assist you. It would be in your interest to have a BLM specialist look at the location and access road prior to the removal of reclamation equipment to ensure that it meets BLM objectives. Upon conclusion submit a Form 3160-5, Subsequent Report of Reclamation. This will prompt a specialist to inspect the location to verify work was completed as per approved plans.
4. The approved Subsequent Report of Reclamation will be your notice that the native soils, contour and seedbed have been reestablished. If the BLM objectives have not been met the operator will be notified and corrective actions may be required.
5. It is the responsibility of the operator to monitor these locations and/or access roads until such time as the operator feels that the BLM objective has been met.

If there are any questions, please feel free to contact any of the following specialists:

Jim Amos
Supervisory Environmental Protection Specialist
575-234-5909 (Office), 575-361-2648 (Cell)

Linda Denniston
Environmental Protection Specialist
575-234-5974

Jennifer Van Curen
Environmental Protection Specialist
575-234-5905

Mike Burton
Environmental Protection Specialist
575-234-2226

Jeffery Robertson
Natural Resource Specialist

Solomon Hughes
Natural Resource Specialist
575-234-5951

Douglas Hoag
Civil Engineering Technician
575-234-5979