

HOBBS OCD

JUN 19 2014

RECEIVED

OIL CONSERVATION DIVISION

1220 South St. Francis Dr.

Santa Fe, NM 87505

WELL API NO. 30-025-28562
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. NM1364
7. Lease Name or Unit Agreement Name Kathy Folk
8. Well Number 1
9. OGRID Number 24010
10. Pool name or Wildcat Wildcat Grayberg
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4001' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other2. Name of Operator
V-F PETROLEUM INC.3. Address of Operator
P.O. Box 1889, Midland, Texas 79702

4. Well Location

Unit Letter H : 1800 feet from the North line and 330 feet from the East lineSection 32 Township 16-S Range 35-E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

4001' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
 TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
 PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
 DOWNHOLE COMMINGLE ☐
 CLOSED-LOOP SYSTEM ☐
 OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
 COMMENCE DRILLING OPNS. ☐ P AND A ☐
 CASING/CEMENT JOB ☐
 OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

V-F Petroleum Inc. wishes to P&A this well. Current PB depth is 4,790'.

Proposal: Set CIPB @ 4,575' with 25 sx of cement on top. Set 50 sx plug 2,400' - 2,250'. Set 50 sx plug 350' - 500'. Set 10 sx plug 0' - 30'. Install dry hole marker. Hole will be loaded with 10# mud. All plugs will be displaced with 10# mud.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

*Eric Sprinkle*TITLE Engineering TechnicianDATE: 06/17/2014Type or print name Eric SprinkleE-mail address: eric@vfpetroleum.comPHONE: 432-683-3344

For State Use Only

APPROVED BY:

Mary Brown

TITLE

Dist. Supervisor

DATE

6/23/2014

Conditions of Approval (if any):

JUN 23 2014

Well: Kathy Folk #1
 Location: 1800 FNL & 330 FEL
 Sec 32 T-16-S R-35-E
 of Lea County, New Mexico
 API# 30-025-28562

Operator: V-F Petroleum Inc
 Field:
 Elevation: GL= 4001'
 KB-GL= 15'
 KB= 4016'

Tot Depth	Hole Sz	Tops & Perfs	Casing & Cement
150	17 1/2"	Proposed: Plug 0-30 w/ 10 sx Class C CMT	
300			420 sx Class C CMT
425		Proposed: Plug 350-500 w/ 50 sx Class C CMT	13 3/8" 61# CSG
600	12 1/4"		
900			
1200			
1500			
1800			
2100		Anhy 1,902'	
2400		Proposed: Plug 2,400-2,250 w/ 50 sx Class C CMT	
2700			
3000		Yates 3,125'	
3300			
3600			
3900		Queen 4,060'	
4200			
4500		Proposed: CIPB @ 4,575' w/ 25 sx Class C CMT	
4600		Perfs 4,672'-4,708'	1700 sx Lite CMT
4700			200 sx Class C CMT
4844		San Andres 4,815'	9 5/8" 36# & 40# CSG
5100	7 7/8"		CMT Plug 4,905'-4,790' tag
5400			
5700			Open Hole 4,844'-6,250'
6000			
6250			5 1/2" CSG Cut @ 6,250'
6300			CMT Plug 6,314'-6,210' tag
6450		Glorieta 6,330'; Perfs: 6,331'-6,335'	
6600			
6750			
6900			
7050			
7200			
7350			
7500			
7650		Tubb 7,645'	
7800			
7950			
8100			CMT Plug 8,100'-8,308'
8250			
8400		Abo 8,395'	
8600			
8800			
9000			
9200			
9400			
9600			
9800			
10000			
10200			
10200		Wolfcamp 10,190'	CIBP 10,190' + 100' CMT
10350		10,292-10,329 (9-9-92)	
10500			
10650		Perfs: 10,826'-10,880'	CIBP 10,515' + 20' CMT
10800		Perfs: *10,872'-10,880'	
10950		Perfs: **10,872'-10,890'	875 sx 50/50 poz CMT
11015		Perfs: 10,895'-10,924' (V-F Reperf)	5 1/2" 17# CSG

REMARKS: * Resquezed & Reperfed

** Squeezed & Drilled Out