Office <u>District I</u> – (575) 393-6161	State of 110	w Mexico			Form	
	Energy, Minerals and	Natural Resources	s WELL A		Revised July	8, 2013
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283	OIL CONCEDUATION DIVIGION			API NO. 5-41378	`	
811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISION			ate Type of Lea	se	
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr. Santa Fe, NM 87505			TATE 🗵	FEE	
<u>District IV</u> – (505) 476-3460 1220 S. St. Francis Dr., Santa Fe, NM 87505	Santa Fe, N	1101 67303	6. State	Oil & Gas Leas	se No.	
SUNDRY NOTION	CES AND REPORTS ON W			e Name or Unit		lame
(DO NOT USE THIS FORM FOR PROPOS DIFFERENT RESERVOIR. USE "APPLIC	SALS TO DRILL OR TO DEEPEN 'ATION FOR PERMIT" (FORM C-	OR PLUG BACK TO A		erry BSU State	Com	` <u> </u>
PROPOSALS.)		4.5	1	Number	\	
<ol> <li>Type of Well: Oil Well</li> <li>Name of Operator</li> </ol>	Gas Well  Other	AUG 1 3 2014	1H	ID Number		
Yates Petroleum Corporation	·	AUG I	9. OGK 0255			
3. Address of Operator		RECEIVED		l name or Wildo	at	
105 South Fourth Street, Artesia, N	M 88210	RECOV	Wild	cat; Bone Spring	g	
4. Well Location					_	
	feet from the	South line and line and	660	feet from the	East	line
	feet from the			feet from the	East	line
Section 11 Township 21S Range 33E NMPM Lea County  11. Elevation (Show whether DR, RKB, RT, GR, etc.)						
APPLICATION OF THE PERSON OF T	11. Lievation (Show whein	3,786'	, eic.)			
Annual Control				1 Section of the sect		
12. Check A	appropriate Box to Indic	ate Nature of Not	ice, Report o	or Other Data		
NOTICE OF IN	TENTION TO:		· ·	NT DEDOD	T 0 F	
NOTICE OF IN				NT REPOR		ıc 🗆
TEMPORARILY ABANDON	PERFORM REMEDIAL WORK  PLUG AND ABANDON  REMEDIAL WORK  ALTERING CASING  TEMPORARILY ABANDON  CHANGE PLANS  COMMENCE DRILLING OPNS  PAND A					
PULL OR ALTER CASING	MÚLTIPLE COMPL	CASING/CE				
DOWNHOLE COMMINGLE	Maria (1906) 1 (1907) 1 (1907) Tarangan mengangkan kenalagan	the state of the s		grif Silingan san san		
CLOSED-LOOP SYSTEM	_	OTUED.	tt			<b>K</b> ZI
OTHER:  13. Describe proposed or compl	eted operations (Clearly sta	OTHER:	Intermediat		uding estima	ted date
of starting any proposed wo						
proposed completion or reco		•	•		C	
8/3/14 – TD 12-1/4" hole to 6,126'.						
	. HCK-55 LT&C casing set a					
8/4/14 - Set 9-5/8" 36# and 40# J-55, HCK-55 LT&C casing set at 6,126'. Cemented stage 1 with 500 sacks 35:65:6 Poz "C" + 0.2% D013 + 2% D020 + 90#/sx D035 + 5#/sx D042 + 5% D044 + 0.2% D046 + 0.1% D065 + 0.125#/sx D130 + 0.1% D238 (yld 1.92, wt						
	#/sx D042 + 5% D044 + 0.29	% D046 + 0.1% D06	5 + 0.125 #/sx I	D130 + 0.1% D2	238 (yld 1.92	, wt
12.8). Tailed in with 180 sacks 50/50	#/sx D042 + 5% D044 + 0.20 D Poz "C" + 0.3% D013 + 0.3	% D046 + 0.1% D06 5% D020 + 89#/ D03	5 + 0.125#/sx I 35 + 5#/sx D042	D130 + 0.1% D2 2 + 5% D044 +	238 (yld 1.92 0.2% D046 +	, wt - 0.2%
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2	#/sx D042 + 5% D044 + 0.2° D Poz "C" + 0.3% D013 + 0.3° Circulated 467 sacks to the	% D046 + 0.1% D06 5% D020 + 89#/ D03 ne surface. WOC 52	5 + 0.125#/sx I 35 + 5#/sx D042 hours 30 mins	D130 + 0.1% D2 2 + 5% D044 + 6 . Cemented stag	238 (yld 1.92 0.2% D046 - ge 2 with 149	, wt - 0.2% 0 sacks
12.8). Tailed in with 180 sacks 50/50	#/sx D042 + 5% D044 + 0.2 <sup>1</sup> D Poz "C" + 0.3% D013 + 0.3 D. Circulated 467 sacks to the control of the control	% D046 + 0.1% D06 5% D020 + 89#/ D03 ne surface. WOC 52 14 + 0.2% D046 + 0.	5 + 0.125#/sx I 65 + 5#/sx D042 hours 30 mins 5% D065 + 0.1	D130 + 0.1% D2 2 + 5% D044 + 6 Cemented stag 25#/sx D130 + 6	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 (	, wt - 0.2% 0 sacks yld
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2 35:65:6 Poz "C" + 3% D020 + 90# D 1.94, wt 12.8). Tailed in with 100 sac 0.2% D065 + 0.1% D238 (yld 1.38, v	#/sx D042 + 5% D044 + 0.2 <sup>1</sup> D Poz "C" + 0.3% D013 + 0.2 D Circulated 467 sacks to the color of	% D046 + 0.1% D06 5% D020 + 89#/ D03 the surface. WOC 52 14 + 0.2% D046 + 0. 1013 + 1% D020 + 89 1014 Model M	5 + 0.125#/sx I 5 5 + 5#/sx D042 hours 30 mins 5% D065 + 0.1 0# D035 + 5#/sz DC 39 hours 10	D130 + 0.1% D2 2 + 5% D044 + + . Cemented stag 25#/sx D130 + + x D042 + 5% D0 mins.	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 (	, wt - 0.2% 0 sacks yld
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2 35:65:6 Poz "C" + 3% D020 + 90# D 1.94, wt 12.8). Tailed in with 100 sac	#/sx D042 + 5% D044 + 0.2 <sup>1</sup> D Poz "C" + 0.3% D013 + 0.2 D Circulated 467 sacks to the color of	% D046 + 0.1% D06 5% D020 + 89#/ D03 the surface. WOC 52 14 + 0.2% D046 + 0. 1013 + 1% D020 + 89 1014 Model M	5 + 0.125#/sx I 5 5 + 5#/sx D042 hours 30 mins 5% D065 + 0.1 0# D035 + 5#/sz DC 39 hours 10	D130 + 0.1% D2 2 + 5% D044 + + . Cemented stag 25#/sx D130 + + x D042 + 5% D0 mins.	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 (	, wt - 0.2% 0 sacks yld
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2 35:65:6 Poz "C" + 3% D020 + 90# D 1.94, wt 12.8). Tailed in with 100 sac 0.2% D065 + 0.1% D238 (yld 1.38, v	#/sx D042 + 5% D044 + 0.2 <sup>1</sup> D Poz "C" + 0.3% D013 + 0.2 D Circulated 467 sacks to the color of	% D046 + 0.1% D06 5% D020 + 89#/ D03 the surface. WOC 52 14 + 0.2% D046 + 0. 1013 + 1% D020 + 89 1014 Model M	5 + 0.125#/sx I 5 5 + 5#/sx D042 hours 30 mins 5% D065 + 0.1 0# D035 + 5#/sz DC 39 hours 10	D130 + 0.1% D2 2 + 5% D044 + + . Cemented stag 25#/sx D130 + + x D042 + 5% D0 mins.	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 (	, wt - 0.2% 0 sacks yld
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2 35:65:6 Poz "C" + 3% D020 + 90# D 1.94, wt 12.8). Tailed in with 100 sac 0.2% D065 + 0.1% D238 (yld 1.38, v 8/6/14 – Tested casing to 1000 psi for	#/sx D042 + 5% D044 + 0.2' D Poz "C" + 0.3% D013 + 0.2 D. Circulated 467 sacks to the 1035 + 5#/sx D042 + 5% D042 cks 50/50 Poz "C" + 0.1% Down 14.2). Circulated 182 sacks a 30 mins, good test. Reduced	% D046 + 0.1% D06 5% D020 + 89#/ D03 the surface. WOC 52 44 + 0.2% D046 + 0. 1013 + 1% D020 + 89 text to the surface. Wo 1014 and r	5 + 0.125#/sx I 5 5 + 5#/sx D042 hours 30 mins 5% D065 + 0.1 0# D035 + 5#/sz DC 39 hours 10	D130 + 0.1% D2 2 + 5% D044 + + . Cemented stag 25#/sx D130 + + x D042 + 5% D0 mins.	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 (	, wt - 0.2% 0 sacks yld
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2 35:65:6 Poz "C" + 3% D020 + 90# D 1.94, wt 12.8). Tailed in with 100 sac 0.2% D065 + 0.1% D238 (yld 1.38, v	#/sx D042 + 5% D044 + 0.2 <sup>1</sup> D Poz "C" + 0.3% D013 + 0.2 D Circulated 467 sacks to the color of	% D046 + 0.1% D06 5% D020 + 89#/ D03 the surface. WOC 52 44 + 0.2% D046 + 0. 1013 + 1% D020 + 89 text to the surface. Wo 1014 and r	5 + 0.125#/sx I 5 5 + 5#/sx D042 hours 30 mins 5% D065 + 0.1 0# D035 + 5#/sz DC 39 hours 10	D130 + 0.1% D2 2 + 5% D044 + + . Cemented stag 25#/sx D130 + + x D042 + 5% D0 mins.	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 (	, wt - 0.2% 0 sacks yld
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2 35:65:6 Poz "C" + 3% D020 + 90# D 1.94, wt 12.8). Tailed in with 100 sac 0.2% D065 + 0.1% D238 (yld 1.38, v 8/6/14 – Tested casing to 1000 psi for	#/sx D042 + 5% D044 + 0.2' D Poz "C" + 0.3% D013 + 0.2 D. Circulated 467 sacks to the 1035 + 5#/sx D042 + 5% D042 cks 50/50 Poz "C" + 0.1% Down 14.2). Circulated 182 sacks a 30 mins, good test. Reduced	% D046 + 0.1% D06 5% D020 + 89#/ D03 the surface. WOC 52 44 + 0.2% D046 + 0. 1013 + 1% D020 + 89 text to the surface. Wo 1014 and r	5 + 0.125#/sx I 5 5 + 5#/sx D042 hours 30 mins 5% D065 + 0.1 0# D035 + 5#/sz DC 39 hours 10	D130 + 0.1% D2 2 + 5% D044 + + . Cemented stag 25#/sx D130 + + x D042 + 5% D0 mins.	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 (	, wt - 0.2% 0 sacks yld
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2 35:65:6 Poz "C" + 3% D020 + 90# D 1.94, wt 12.8). Tailed in with 100 sac 0.2% D065 + 0.1% D238 (yld 1.38, v 8/6/14 – Tested casing to 1000 psi for Spud Date:  7/18/14	#/sx D042 + 5% D044 + 0.2' D Poz "C" + 0.3% D013 + 0.2 D Circulated 467 sacks to the color of th	% D046 + 0.1% D06 5% D020 + 89#/ D03 ne surface. WOC 52 14 + 0.2% D046 + 0. 013 + 1% D020 + 89 st to the surface. WC ad hole to 8-3/4 and r	5 + 0.125#/sx I 5 + 5#/sx D042 hours 30 mins 5% D065 + 0.1 0# D035 + 5#/s; DC 39 hours 10 esumed drilling	D130 + 0.1% D2 2 + 5% D044 + + . Cemented stag 25#/sx D130 + + x D042 + 5% D0 mins.	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 (	, wt - 0.2% 0 sacks yld
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2 35:65:6 Poz "C" + 3% D020 + 90# D 1.94, wt 12.8). Tailed in with 100 sac 0.2% D065 + 0.1% D238 (yld 1.38, v 8/6/14 – Tested casing to 1000 psi for Spud Date:	#/sx D042 + 5% D044 + 0.2' D Poz "C" + 0.3% D013 + 0.2 D Circulated 467 sacks to the color of th	% D046 + 0.1% D06 5% D020 + 89#/ D03 ne surface. WOC 52 14 + 0.2% D046 + 0. 013 + 1% D020 + 89 st to the surface. WC ad hole to 8-3/4 and r	5 + 0.125#/sx I 5 + 5#/sx D042 hours 30 mins 5% D065 + 0.1 0# D035 + 5#/s; DC 39 hours 10 esumed drilling	D130 + 0.1% D2 2 + 5% D044 + + . Cemented stag 25#/sx D130 + + x D042 + 5% D0 mins.	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 (	, wt - 0.2% 0 sacks yld
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2 35:65:6 Poz "C" + 3% D020 + 90# D 1.94, wt 12.8). Tailed in with 100 sac 0.2% D065 + 0.1% D238 (yld 1.38, v 8/6/14 – Tested casing to 1000 psi for Spud Date:  7/18/14  Thereby certify that the information a	#/sx D042 + 5% D044 + 0.2 D Poz "C" + 0.3% D013 + 0.2 D Circulated 467 sacks to the 1035 + 5#/sx D042 + 5% D042 + 5% D042 + 5% D042 + 5% D042 + 10.2 Down 14.2). Circulated 182 sacks a 30 mins, good test. Reduced Rig Release Rig Release Right Rig Release Right Righ	% D046 + 0.1% D06 5% D020 + 89#/ D03 ne surface. WOC 52 14 + 0.2% D046 + 0. 013 + 1% D020 + 89 as to the surface. WO ad hole to 8-3/4 and r  the best of my know	5 + 0.125#/sx I 5 + 5#/sx D042 hours 30 mins 5% D065 + 0.1 0# D035 + 5#/sz DC 39 hours 10 resumed drilling	D130 + 0.1% D2 2 + 5% D044 + + Cemented stag 25#/sx D130 + + x D042 + 5% D0 mins.	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 (	, wt - 0.2% 0 sacks yld
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2 35:65:6 Poz "C" + 3% D020 + 90# D 1.94, wt 12.8). Tailed in with 100 sac 0.2% D065 + 0.1% D238 (yld 1.38, v 8/6/14 – Tested casing to 1000 psi for Spud Date:    The control of the control	#/sx D042 + 5% D044 + 0.2 D Poz "C" + 0.3% D013 + 0.2 D Circulated 467 sacks to the 1035 + 5#/sx D042 + 5% D042 + 5% D042 + 5% D042 + 5% D042 + 10.2 Down 14.2). Circulated 182 sacks a 30 mins, good test. Reduced Rig Release Rig Release Right Rig Release Right Righ	% D046 + 0.1% D06 5% D020 + 89#/ D03 me surface. WOC 52 14 + 0.2% D046 + 0. 013 + 1% D020 + 89 sets to the surface. WO ded hole to 8-3/4 and r ase Date:	5 + 0.125#/sx I 5 + 5#/sx D042 hours 30 mins 5% D065 + 0.1 0# D035 + 5#/sz DC 39 hours 10 resumed drilling	D130 + 0.1% D2 2 + 5% D044 + + Cemented stag 25#/sx D130 + + x D042 + 5% D0 mins.	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 ( 044 + 0.2% I	, wt - 0.2% 0 sacks yld 0046 +
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2 35:65:6 Poz "C" + 3% D020 + 90# D 1.94, wt 12.8). Tailed in with 100 sac 0.2% D065 + 0.1% D238 (yld 1.38, v 8/6/14 – Tested casing to 1000 psi for Spud Date:  7/18/14  I hereby certify that the information and the same same same same same same same sam	#/sx D042 + 5% D044 + 0.2 D Poz "C" + 0.3% D013 + 0.2 D Poz "C" + 0.3% D013 + 0.2 Circulated 467 sacks to the 1035 + 5#/sx D042 + 5% D042 cks 50/50 Poz "C" + 0.1% Down 14.2). Circulated 182 sacks a 30 mins, good test. Reduced Rig Release to the 104 power is true and complete to 104 power is true and 1	% D046 + 0.1% D06 5% D020 + 89#/ D03 ne surface. WOC 52 14 + 0.2% D046 + 0. 013 + 1% D020 + 89 st to the surface. WO d hole to 8-3/4 and r  ase Date:  Regulatory Reporti	5 + 0.125#/sx I 65 + 5#/sx D042 hours 30 mins 5% D065 + 0.1 0# D035 + 5#/sz DC 39 hours 10 esumed drilling	D130 + 0.1% D2 2 + 5% D044 + + . Cemented stag 25#/sx D130 + + x D042 + 5% D0 mins. DV7	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 ( 044 + 0.2% I	, wt - 0.2% 0 sacks yld 0046 +
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2 35:65:6 Poz "C" + 3% D020 + 90# D 1.94, wt 12.8). Tailed in with 100 sac 0.2% D065 + 0.1% D238 (yld 1.38, v 8/6/14 – Tested casing to 1000 psi for Spud Date:    Thereby certify that the information and the same same same same same same same sam	#/sx D042 + 5% D044 + 0.2 D Poz "C" + 0.3% D013 + 0.2 D Poz "C" + 0.3% D013 + 0.2 Circulated 467 sacks to the 1035 + 5#/sx D042 + 5% D042 cks 50/50 Poz "C" + 0.1% Down 14.2). Circulated 182 sacks a 30 mins, good test. Reduced Rig Release to the 104 power is true and complete to 104 power is true and 1	% D046 + 0.1% D06 5% D020 + 89#/ D03 ne surface. WOC 52 14 + 0.2% D046 + 0. 013 + 1% D020 + 89 st to the surface. WC d hole to 8-3/4 and r  ase Date:  the best of my know  Regulatory Reporti s: laura@yatespetr	5 + 0.125#/sx I 5 + 5#/sx D04: hours 30 mins 5% D065 + 0.1 0# D035 + 5#/s; OC 39 hours 10 esumed drilling	D130 + 0.1% D2 2 + 5% D044 + + . Cemented stag 25#/sx D130 + + x D042 + 5% D0 mins. DV7	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 ( 044 + 0.2% I	, wt - 0.2% 0 sacks yld 0046 +
12.8). Tailed in with 180 sacks 50/50 D065 + 0.1% D238 (yld 1.38, wt 14.2 35:65:6 Poz "C" + 3% D020 + 90# D 1.94, wt 12.8). Tailed in with 100 sac 0.2% D065 + 0.1% D238 (yld 1.38, v 8/6/14 – Tested casing to 1000 psi for Spud Date:  Type or print name	#/sx D042 + 5% D044 + 0.2 D Poz "C" + 0.3% D013 + 0.2 D Poz "C" + 0.3% D013 + 0.2 Circulated 467 sacks to the 1035 + 5#/sx D042 + 5% D042 cks 50/50 Poz "C" + 0.1% Down 14.2). Circulated 182 sacks a 30 mins, good test. Reduced Rig Release to the 104 power is true and complete to 104 power is true and 1	% D046 + 0.1% D06 5% D020 + 89#/ D03 ne surface. WOC 52 14 + 0.2% D046 + 0. 013 + 1% D020 + 89 st to the surface. WO d hole to 8-3/4 and r  ase Date:  Regulatory Reporti	5 + 0.125#/sx I 5 + 5#/sx D04: hours 30 mins 5% D065 + 0.1 0# D035 + 5#/s; OC 39 hours 10 esumed drilling	D130 + 0.1% D2 2 + 5% D044 + + . Cemented stag 25#/sx D130 + + x D042 + 5% D0 mins. DV7	238 (yld 1.92 0.2% D046 + ge 2 with 149 0.1% D238 ( 044 + 0.2% I	, wt - 0.2% 0 sacks yld 0046 +