

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO 30-025-23169
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LO-1080-0006
7. Lease Name or Unit Agreement Name Sawyer 4 State
8. Well Number 1
9. OGRID Number 288173
10. Pool name or Wildcat Sawyer San Andres West

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>
2. Name of Operator Stanolind Operating, DBA Stanolind NM LLC
3. Address of Operator 310 W Wall, Ste 1000, Midland, TX 79701
4. Well Location Unit Letter <u>B</u> : <u>660</u> feet from the <u>North</u> line and <u>1980</u> feet from the <u>West</u> line Section <u>4</u> Township <u>10S</u> Range <u>37E</u> NMPM Lea County
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3967' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

PERFORM E-PERMITTING TEMPOR <u>P&A NR P.M.</u> P&A R <input type="checkbox"/> ON <input type="checkbox"/> PULL OR INT to P&A <input type="checkbox"/> DOWNHC CSNG <input type="checkbox"/> CHG Loc <input type="checkbox"/> TA <input type="checkbox"/> OTHER: <input type="checkbox"/>	SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS <input type="checkbox"/> P AND A <input checked="" type="checkbox"/> CASING/CEMENT JOB <input type="checkbox"/> OTHER: <input type="checkbox"/>
--	--

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

7/14/14 MIRU, Contact OCD, POOH w/ 30 rods, SISD.
7/15/14 Rods became stuck, tried to free, failed, tried to back off, failed, pulled 63,000#, rods parted, then tbg fell from csg slips, SISD.
7/16/14 NDWH, NUBOP, RIH w/overshot, fish from 7/16/14 to 7/21/14.
7/22/14 Make 3 1/4 bit & scraper run, tag up @ 4661', solid, attempt to rotate, no luck, contact Mark Whitaker w/OCD, approved to set CIBP @ 4660', TOOH, RBIH, set 4 1/2 CIBP @ 4660', release, tag, circ hole w/MLF spot 25sx cmt from 4660' to 4283', POOH.
7/23/14 RIH, tag cmt @ 4295', PUH to 2949', load hole, spot 35sx cmt w/2% CaCl, disp to 2420', PUH, WOC 4 hrs, tag @ 2219', tried To work down, no luck, POOH, red beds in tbg, contact Bill w/ Stanolind & Mark Whitaker, Mark wants to spot 35sx cmt on red Beds, spot 35sx cmt and disp, WOC overnight.
7/24/14 RIH, tag cmt @ 1712', POOH, RIH w/pkr to 30', load hole, set pkr, test csg to 650 psi, wait 30 min, only fell off 75 psi, okayed w/OCD, RUWL, perf @ 460', load hole, set pkr @ 30', est inj rate of 50 psi w/full returns up 4 1/2 x 8 5/8, mix & pump 130sx cmt around 4 1/2 x 8 5/8 csg, leaving 4 1/2 full, POOH w/pkr, NDBOP, cut off wellhead, 4' below ground level, install dry hole marker remove anchors, back fill cellar, RDMO.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

Ex. VP OPERATIONS
SIGNATURE Billy M. Pribe TITLE Supervisor DATE 8/21/14
Type or print name Billy M. Pribe E-mail address: bpribe@stanolind.com PHONE: 432-640-0040
For State Use Only
APPROVED BY: Marky Brown TITLE Dist. Supervisor DATE 8/27/2014
Conditions of Approval (if any):

AUG 28 2014

AFTER P&A

Stanolind Operating LLC DBA Stanolind NM LLC

WELL NAME:	State "4" #1		FIELD:	Sawyer	
LOCATION:	S4 T10S R37E		API #:	30-025-23169	
COUNTY:	Lea	ST:	NM	SPUD DATE:	06/02/69
KB:	3976'	GL:	3967'	TD:	5057'
PBTD:					

8 5/8" @ 410' cmt'd w/ 250 sx (circ)

Perf @ 460' and circulate cement to surface w/ 130 sx

Formation Tops:

Top anhydrite	2235'
Base of salt	2945'
San Andres	4206'

Tested casing to 650#, fell to 575# in 30 min.

35 sack cement plug @ 2219', tag @ 1712'

35 sack cement plug @ 2949', tag @ 2219', tubing plugged w/ red beds

TOC 3030' (calc)

CIBP @ 4660' plus 25 sx of cement, tag @ 4295'

Perfs 4958-5008"

4 1/2" @ 5057' Cmt'd w/ 250 sx "C" plus 27 sx latex cement

TD 5057'