

Submit 1 Copy To Appropriate District Office
 District I- (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II- (575) 748-1283
 1301 W. Grand Ave., Artesia, NM 88210
 District III- (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV- (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG IN DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-28501
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other _____		5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
2. Name of Operator Mack Energy Corporation		6. State Oil & Gas Lease No. VB-1784
3. Address of Operator P.O. Box 960 Artesia, NM 88210		7. Lease Name or Unit Agreement Name Marble State
4. Well Location Unit Letter <u>C</u> <u>663</u> feet from the <u>North</u> line and <u>1983</u> feet from the <u>West</u> line Section <u>21</u> Township <u>15S</u> Range <u>32E</u> NMPM County <u>Lea</u>		8. Well Number 1
11. Elevation (Show whether DR, RKB, RT, GR etc.) 4311' GR		9. OGRID Number 013837
RECEIVED		10. Pool Name or Wildcat San Andres

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO: PERFORM REMEDIAL WORK <input type="checkbox"/> PLUG AND ABANDON <input checked="" type="checkbox"/> TEMPORARILY ABANDON <input type="checkbox"/> CHANGE PLANS <input type="checkbox"/> PULL OR ALTER CASING <input type="checkbox"/> MULTIPLE COMPL <input type="checkbox"/> DOWNHOLE COMMINGLE <input type="checkbox"/> CLOSED-LOOP SYSTEM <input type="checkbox"/> OTHER: <input type="checkbox"/>		SUBSEQUENT REPORT OF: REMEDIAL WORK <input type="checkbox"/> ALTERING CASING <input type="checkbox"/> COMMENCE DRILLING OPNS. <input type="checkbox"/> P AND A <input type="checkbox"/> CASING/CEMENT JOB <input type="checkbox"/> OTHER: <input type="checkbox"/>	
---	--	---	--

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or re-completion.

Mack Energy proposes to Plug and Abandon the Marble State #1 as Follows:

- BY W.L. OR 25SXS BY TBG.**
- Set CIBP @ 4550' w/35' cap.
 - Circ. Hole w/10# brine gel @ 4350'.
 - Set 25 sx Class C plug 4010'-4110' Base San Andres. - WOC & TAG
 - Set 25 sx Class C plug 2266'-2366' Base of Salt & Tag.
 - Set 25 sx Class C plug 1434'-1534' Top of Salt & Tag.
 - Circ. Cmt. To Surface @ 505' w/60 sx Class C.
 - Install P & A marker.

Spud Date: Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jerry W. Sherrell TITLE Production Clerk DATE 9-18-2014

Type or print name Jerry W. Sherrell E-mail address: jerrys@mec.com PHONE: 575-748-1288

APPROVED BY: Maley Brown TITLE Dist Supervisor DATE 9/23/2014
 Conditions of Approval (if any): _____


OIL CONSERVATION DIVISION - Hobbs office **Must Be Notified**
 24 hours prior to the beginning of Plugging Operations.

SEP 23 2014

Mack Energy Corporation

Marble State #1 Sec. 21 T15S R32E 30-025-28501

Before



13 3/8 csg @ 455'
cmt w/530sx, circ

8 5/8 csg @ 4070'
cmt w/2000sx, circ

Perfs 4650-4754'

5 1/2 csg @ 5486' cmt
w/825sx, circ.

36sx plug from 5600-5500'

50sx plug @ 7700'

Pulled 7700' 5 1/2
csg. 7/1/1985

CIBP @ 9575' w/35'
cmt cap

CIBP @ 10,350'


CIBP @ 11,906'

w/35' cmt cap

5 1/2 csg @ 12562'
cmt w/

TD @ 12,562'

After



60sx plug from 505-0'

13 3/8 csg @ 455'
cmt w/530sx, circ

25sx plug from 1534-1434'

25sx plug from 2366-2266'

25sx plug from 4110-4010'

8 5/8 csg @ 4070'
cmt w/2000sx, circ

CIBP @ 4550' w/35' cap

Perfs 4650-4754'

5 1/2 csg @ 5486' cmt
w/825sx, circ.

36sx plug from 5600-5500'

50sx plug @ 7700'

Pulled 7700' 5 1/2
csg. 7/1/1985

CIBP @ 9575' w/35'
cmt cap

CIBP @ 10,350'

CIBP @ 11,906'

w/35' cmt cap

5 1/2 csg @ 12562'
cmt w/

TD @ 12,562'