

Submit 1 Copy To Appropriate District
Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-03316
5. Indicate Type of Lease STATE FEE XX
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name South Pearl Queen Unit
8. Well Number 7
9. OGRID Number 25482
10. Pool name or Wildcat Pearl Queen

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well Gas Well Other INJECTION WELL	
2. Name of Operator State of New Mexico formerly Xeric Oil & Gas Corp.	
3. Address of Operator 1625 N. French Drive Hobbs, New Mexico 88240	
4. Well Location Unit Letter F : 2332 feet from the N line and 1650 feet from the W line Section 3 Township 20S Range 35E NMPM County Lea	
11. Elevation (Show whether DR, RKB, RT, GR, etc.)	

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:		SUBSEQUENT REPORT OF:	
PERFORM REMEDIAL WORK ☐	PLUG AND ABANDON XX	REMEDIAL WORK ☐	ALTERING CASING ☐
TEMPORARILY ABANDON ☐	CHANGE PLANS ☐	COMMENCE DRILLING OPNS. ☐	P AND A ☐
PULL OR ALTER CASING ☐	MULTIPLE COMPL ☐	CASING/CEMENT JOB ☐	
DOWNHOLE COMMINGLE ☐			
OTHER: ☐		OTHER: ☐	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

SEE ATTACHMENTS: PROCEDURE & SCHEMATIC

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mary E Brown TITLE Compliance Officer DATE 7/15/2013
Type or print name _____ E-mail address: _____ PHONE: 575-393-6161
For State Use Only

APPROVED BY: _____ TITLE _____ DATE _____
Conditions of Approval (if any):

NOV 04 2014

State of New Mexico formerly XERIC OIL & GAS

LEASE NAME SOUTH PEARL QUEEN UNIT #7 API 30-0 25 - 03316

U.L. F Section 3 -T 20 S-R 35 E FROM 2332 N / 5 L, 1650 E / W L.

SPECIAL NOTE—Mud Laden Fluid will consist of 9.5# brine with 12.5# Salt Gel per BBL (25 sacks of gel/ per 100 BBLS Brine). All cement plugs will be 25 sacks of cement or 100', whichever is greater. **Unless otherwise specified in the approved procedure**, cement plugs shall consist of class "C" for depths to 7500'. Class "H" will be used for plugs deeper than 7500'.

1. MIRU plugging unit. Lay down production equipment.
2. Set CIBP @ 4700 '. Circulate MLF. Spot 25 sxs cmt on CIBP. PRESSURE TEST CSG.
3. Perf/Sqz or ~~Spot~~ 25 sxs cmt @ 3400 '. If perf, WOC & TAG.
4. Perf /Sqz or ~~Spot~~ 25 sxs cmt @ 1850 '. If perf, WOC and TAG.
5. Perf/Sqz or Spot @ 250 ', w/ sufficient volume to circ cmt to surface inside/outside of csg strings.
6. Cutoff wellhead and anchors, install marker.

-----SPECIAL NOTES-----

PLUGGING & ABANDONMENT WORKSHEET

OPERATOR STATE OF NM FORMERLY XERIC OIL & GAS
LEASENAME SOUTH PEARL QUEEN UNIT

SECT 3 TWN 209 RNG 35E
FROM 2332 N/G L 1650 E/W L _____
TD: _____ FORMATION @ TD _____
PBTD: _____ FORMATION @ PBTD _____

	SIZE	SET @	TOC	TOC DETERMINED BY	
SURFACE	8 5/8	102'	SURF	CIRC	
INTMED 1					
INTMED 2					
PROD	4 1/2	5040'	3580	TEMP SURVEY	
	SIZE	TOP	BOT	TOC	DETERMINED BY
LINER 1					
LINER 2					
CUT & PULL @				TOP - BOTTOM	
INTMED 1			PERFS	-	
INTMED 2			OPENHOLE	-	
PROD					

4. REQUIRED PLUGS DISTRICT I

BENTLEY (ANEYD)	
YATES	
QUEEN	
GRAYBORG	
SAN ANDREW	
CAPTAIN REEF	
DELAWARE	
BELL CANYON	
CHERRY CANYON	
BELLEY CANYON	
BONE SPRING	
OLUKIETA	
SUNBERRY	
TUES	
ORCHARD	
AUBO	
WIC	
PERCH	
STRAWN	
ATOKA	
WAGGLOW	
LESS	
DEVOREAN	

[illegible]

PERF: SQZ
@ 250'

PERF: SQZ
@ 1850'

7
F & SQZ
3400'

SET CIBP
@ 4700'

85/8" 32#
@ 102
TOC SURF
CIRC

SPOT 252X5CMT
4750-4854
4959-4965

4 1/2" 11.6#
@ 5040
TOC 3580
TEMP SURVEY

TD 5040