

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION HOBBS OGD
1220 South St. Francis Dr.
Santa Fe, NM 87505
NOV 10 2014

WELL API NO.
30-025-42085

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Hearns 27 State Com

8. Well Number 501H

9. OGRID Number
7377

10. Pool name or Wildcat
Triste Draw; Bone Spring, East

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
EOG Resources, Inc.

3. Address of Operator
P.O. Box 2267 Midland, TX 79702

4. Well Location
Unit Letter M : 210 feet from the South line and 570 feet from the West line
Section 27 Township 24S Range 33E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3479' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☒ P AND A ☐
CASING/CEMENT JOB ☒
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

11/02/14 Spud 17-1/2" hole.

11/03/14 Ran 28 jts 13-3/8", 54.5#, J-55 STC casing set at 1266'.
Cement lead w/ 700 sks Class C, 13.5 ppg, 1.74 yield;
tail w/ 250 sks Class C, 14.8 ppg, 1.33 yield.
Circulated 143 bbls cement to surface. WOC 26 hrs.

11/04/14 Tested casing to 1500 psi for 30 minutes. Test good.
Resumed drilling 12-1/4" hole.

Spud Date: 11/02/14

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

Stan Wagner

TITLE

Regulatory Analyst

DATE

11/06/14

Type or print name

Stan Wagner

E-mail address:

PHONE:

432-686-3689

For State Use Only

APPROVED BY:

Petroleum Engineer

TITLE

Petroleum Engineer

DATE

11/10/14

Conditions of Approval (if any):

NOV 12 2014