

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised July 18, 2013

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-025-40517
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. VO-8090
7. Lease Name or Unit Agreement Name Mango BRM State
8. Well Number 1H
9. OGRID Number 025575
10. Pool name or Wildcat Featherstone; Bone Spring

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other **NOV 04 2014**

2. Name of Operator
Yates Petroleum Corporation **RECEIVED**

3. Address of Operator
105 South Fourth Street, Artesia, NM 88210

4. Well Location
 Unit Letter C : 100 feet from the North line and 2310 feet from the West line
 Unit Letter N : 268 feet from the South line and 1977 feet from the West line
 Section 27 Township 20S Range 35E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3682'GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE
 CLOSED-LOOP SYSTEM
 OTHER:

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB
 OTHER: Completion operations

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

8/4/14 - Tested casing to 3500 psi for 30 mins, held good. Increased pressure to open toe sleeve 15,270' at 7300 psi. Established rate and pumped 1500 gallons 15% HCL NEFE acid and flushed casing with 457 bbls of 3% KCL with CRW-132.
 10/3-7/14 - Perforated Bone Springs 10,914' - 15,170' (468 holes). Acidized Bone Spring 10,914' - 15,270' with 72,500 gallons 15% HCL acid, frac with a total of 4,357,841# of 20/40 Econoprop, 20/40 RCS and 30/50 Econoprop.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Laura Watts TITLE Regulatory Reporting Technician DATE November 4, 2014

Type or print name Laura Watts E-mail address: laura@yatespetroleum.com PHONE: 575-748-4272
For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engineer DATE 11/19/14
 Conditions of Approval (If any):

NOV 18 2014