

Submit 1 Copy To Appropriate District Office

District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

HOBBS OCD
State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

NOV 05 2014 RECEIVED

WELL API NO. 30-025-32173
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name B.F. Harrison "B" ✓
8. Well Number: 14 ✓
9. OGRID Number: 4323
10. Pool name or Wildcat TGE GLOR UPPER PAD SW
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3314' GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other Water Injection

2. Name of Operator
Chevron USA INC. ✓

3. Address of Operator
15 Smith Road Midland, TX 79705

4. Well Location
Unit Letter F : 1800' feet from the North line and 1650' feet from the West line
Section 9 Township 23-S Range 37-E NMPM County Lea

Approved for Plugging of well bore only.
Liability under bond is retained pending receipt of C-103 (Specifically for Subsequent Report of Well Plugging) which may be found at OCD web page under forms!
www.emnrd.state.nm.us/oed

12. Check appropriate box to indicate Nature of Notice, Report or Other Data

SUBSEQUENT REPORT OF:

REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB
 OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.
10-21-2014 - Tagged CIBP @ 4926', 25 sks of cement @ 4926' disp to 4679' pumped 200 sks @ 2955' disp to 980'
10-22-2014 - Tagged Plug @ 1144' pump 25 sks @ 1144' disp to 897' Perf @ 350' pump 100 sks to Surface out 8-5/8" x 5-1/2" Annulus, leaving the 5-1/2 full

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.
SIGNATURE [Signature] TITLE Representative DATE 10/30/2014

Type or print name Robert Holden E-mail address: rholden@keyenergy.com PHONE: 432-523-5155

For State Use Only

APPROVED BY: [Signature] TITLE Compliance Officer DATE 12/23/2014
Conditions of Approval (if any):

E-PERMITTING
P&A NR dm P&A R _____
INT to P&A _____
CSNG _____ CHG Loc _____
TA _____

DEC 23 2014