Submit I Copy To Appropriate District	State of New Mexico		Form C-103
Office District I – (575) 393-6161	Energy, Minerals and Natural Resources OIL CONSERVATION DIVISION 1220 South St. Francis Dr.		Revised August 1, 2011
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283			WELL API NO. 30-025-41986
811 S. First St., Artesia, NM 88210			5. Indicate Type of Lease
<u>District III</u> – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410			STATE FEE
<u>District IV</u> – (505) 476-3460	Santa Fe, NM 87505		6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505			E-7824
SUNDRY NOTICES AND REPORTS ON WELLS			7. Lease Name or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		C. 1 . 1 . 1 . 1 . 1 . 1 . 1	
PROPOSALS.)		HOBBSOCD	Scharb 10 B3NC State 8. Well Number 1H
1. Type of Well: Oil Well	Gas Well Other		0. OCRIDAL I
2. Name of Operator Mewbourne Oil Company	~	JAN 0 5 2015	9. OGRID Number 14744
3. Address of Operator		*	10. Pool name or Wildcat
PO Box 5270, Hobbs, NM 88241			Quail Ridge; Bone Spring 50460
4. Well Location			
Unit Letter N : 185 feet from the South line and 1980 feet from the West line			
Section 10	Township 19S	Range 34E	NMPM Lea County
A State of the Sta	11. Elevation (Show whether DR,	RKB, RT, GR, etc.)	
3857'			
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data			
NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF:			
PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING			
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐ COMMENCE DRILLING OPNS.☐ P AND A ☐ PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐ CASING/CEMENT JOB ☒			
DOWNHOLE COMMINGLE	MOLTIFEE COMFE	CASING/CEMENT	30B 🛮
_	_		
OTHER:	lated energtions (Clearly state all	OTHER:	Give portinent dates, including estimated date
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of			
proposed completion or recompletion.			
12/16/14MI & spud 17 ½" hole. TD'd hole @ 1797'. Ran 1797' of 13 ¾" 48# & 54.5# J55 ST&C csg. Cemented with 1300 sks Class			
C w/additives. Mixed @ 13.5 #/g w/ 1.75 yd. Tail w/200 sks Class C w/1% CaCl2. Mixed @ 14.8#/g w/1.33 yd. Plug down @ 12:30			
A.M. 12/18/14. WOC. Circ 115 sks of cmt to the pit. At 11:00 P.M. 12/18/14, tested BOPE & csg to 1250# for 30 minutes, held OK.			
Drilled out with 12 1/4" bit.			
Spud Date: 12/16/2014	Rig Release	Date:	
Space Date: 12/10/2011	rag rerease	Suite.	
I hereby certify that the information above is true and complete to the best of my knowledge and belief.			
SIGNATURE DATE 12/23/14DATE_12/23/14			
Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905			
For State Use Only			
APPROVED BY: TITLE Petroleum Engineer DATE 0/05/15			
Conditions of Approval (if arry):		Sinver	/10/