

Submit 3 Copies To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
May 27, 2004

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-37276

5. Indicate Type of Lease

STATE ☐ FEE ☒

6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☐

2. Name of Operator

Cimarex Energy Co.

3. Address of Operator

PO Box 140907; Irving, TX 75014-0907

4. Well Location

Unit Letter P : 1020 feet from the South line and 835 feet from the East line

Section 8 Township 15S Range 36E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3920' GR

Pit or Below-grade Tank Application ☐ or Closure ☐

Pit type _____ Depth to Groundwater _____ Distance from nearest fresh water well _____ Distance from nearest surface water _____

Pit Liner Thickness: _____

Below-Grade Tank: Volume _____

bbls; Construction Material _____

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☒ P AND A ☐

CASING/CEMENT JOB ☒

Set surface & intermediate casing

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

09-19-05 Spudded 17-1/2" hole.
09-20-05 Drilled to 605'. Ran 14jts 13-3/8" 48# H-40 STC casing. Cemented with lead of 400sx Premium Plus + 2% CaCl + 4% Bent + 0.25# Flocele and tail of 200sx Premium Plus + 2% CaCl. Circulated 123 sx to reserve pits. WOC 13.75 hours.
09-21-05 Tested casing to 1000psi for 15 minutes.
09-28-05 In 12-1/4" hole, ran 110jts 9-5/8" 40# J-55 LTC casing to 4715'. Cemented with lead of 1400sx Interfill C + 1/4# Flocele, wt 11.9, yield 2.42. Cemented tail with 200sx Premium Plus + 1% CaCl, wt 14.8, yield 1.335. Circulated 32sx to reserve pits. WOC 25.75 hours.
09-30-05 Tested casing to 1000psi for 30 minutes.

I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines ☐, a general permit ☐ or an (attached) alternative OCD-approved plan ☐.

SIGNATURE Natalie Krueger TITLE Regulatory Technician DATE October 11, 2005

Type or print name Natalie Krueger email address: nkrueger@cimarex.com Telephone No. 972-401-3111
For State Use Only

APPROVED BY: [Signature] TITLE _____ DATE OCT 26 2005
Conditions of Approval (if any): _____

PETROLEUM ENGINEER