

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-30052
5. Indicate Type of Lease STATE FEE XX
6. State Oil & Gas Lease No.

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
Barry D Lee dba Barry Lee Investments

3. Address of Operator
HC 65 Box 222, Crossroads, NM 88114

4. Well Location

Unit Letter M : 660 feet from the South line and 660 feet from the West line
Section 23 Township 9S Range 33E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

12. Check Ann...
Approved for Plugging of well bore only.
Liability under bond is retained pending receipt of
C-103 (Specifically for Subsequent Report of Well
Plugging) which may be found at OCD web page
under forms
www.emnrd.state.nm.us/oed

State Nature of Notice, Report or Other Data

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A XX
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

1/19/2015 Picked up workstring and tagged at 4693'. Circulated mud and spotted 25 sx cement from 4693'.

1/20/2015 Tagged cement at 4496'. POOH to 4062' and spotted 25 sx cement across 8 5/8" shoe at 4000'. WOC and tagged at 3831'. POOH and unset 5 1/2" casing from the slips. Performed stretch tests and cut casing at 3107'.

1/21/2015 Laid down 75 joints 5 1/2" casing. RIH with tubing and spotted 40 sx cement at 3185'.

1/23/2015 RIH and tagged cement at 3055'. POOH and spotted 30 sx cement at 2600'. POOH and spotted 30 sx cement at 2145'. POOH and circulated cement to surface from 455'. Cut off wellhead and filled cement to surface with 2 sx cement. Installed marker and cut off anchors.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Supervisor J & B Well Serv. DATE 1/26/15
Type or print name John R. Stearns, Jr. E-mail address: bobby.stearns@emnrd.com PHONE: 505-760-2482
For State Use Only (Bobby)
APPROVED BY: [Signature] TITLE Dist. Supervisor DATE 2/2/2015
Conditions of Approval (if any):

E-PERMITTING
P&A NR P.M. P&A R _____
INT to P&A _____
CSNG _____ CHG Loc _____
TA _____

FEB 03 2015

Barry D. Lee aka Barry Lee Investments

Ainsworth "DB" #1

API 30-025-30052

660 FSL 660 FWH Sec 23 - T9S - R33E UL "M"

Wellbore Schematic after P&A

