

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (505) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-06016 ✓
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator OXY USA Inc. ✓		6. State Oil & Gas Lease No. 14896
3. Address of Operator P.O. Box 50250 Midland, TX 79710		7. Lease Name or Unit Agreement Name Bertie Whitmire ✓
4. Well Location Unit Letter <u>B</u> : <u>990</u> feet from the <u>north</u> line and <u>2310</u> feet from the <u>east</u> line Section <u>8</u> Township <u>20S</u> Range <u>37E</u> NMPM County <u>Lea</u>		8. Well Number <u>6</u> ✓
11. Elevation (Show whether DR, RKB, RT, GR, etc.) <u>3555'</u>		9. OGRID Number 16696
		10. Pool name or Wildcat Monument Abo, SE

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

E-PERMITTING P&A NR <u>P.M.</u> INT TO P&A _____ CSNG _____ TA _____ OTHER: ☐	SUBSEQUENT REPORT OF: REMEDIAL WORK ☐ ALTERING CASING ☐ COMMENCE DRILLING OPNS. ☐ P AND A ☒ CASING/CEMENT JOB ☐ OTHER: ☐
P&A R _____ COMP _____ CHG Loc _____ RBDMS CHART _____	

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

See Attached

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David Stewart TITLE Sr. Regulatory Advisor DATE 2/2/15

Type or print name David Stewart E-mail address: david_stewart@oxy.com PHONE: 432-685-5717

For State Use Only

APPROVED BY: Mary Brown TITLE Dist. Supervisor DATE 2/5/2015
Conditions of Approval (if any)

FEB 06 2015

Attachment C-103
OXY USA Inc.
Bertie Whitmire #6 - 30-025-06016

1/16/2015 MIRU PU

1/19/2015 POOH w/ rods & pump. NU BOP, test. Work on releasing TAC, stuck in 4-1/2" liner.

1/20/2015 Free TAC after several attempts, POOH w/ tbg. RIH w/ gauge ring to 7075', POOH. RIH & set CIBP @ 7074'.

1/21/2015 RIH w/ tbg & tag CIBP @ 7074', circ hole w/ 10# MLF.

1/22/2015 M&P 25sx CL C cmt on CIBP @ 7074' to 6685' CTOC. PUH to 5883', M&P 25sx CL C cmt, PUH, WOC. RIH & tag cmt @ 5512', PUH to 5010', M&P 25sx CL C cmt, PUH, WOC.

1/26/2015 RIH & tag cmt @ 4862', contact Mark Whitaker-NMOCD approved to continue plugging. PUH to 4524', M&P 25sx CL C cmt, PUH, WOC. RIH & tag cmt @ 4375', PUH to 3290', M&P 25sx CL C cmt, PUH, WOC.

1/27/2015 RIH & tag cmt @ 2683', contact Mark Whitaker-NMOCD approved to continue plugging. PUH & set pkr @ 2017'. RIH & perf @ 2460', attempt to EIR, pressured up to 1500#, no rate or loss. Mark Whitaker-NMOCD approved spotting plug. RIH to 2510', M&P 60sx CL C cmt w/ 2% CaCl₂, PUH, WOC. RIH & tag cmt @ 2197', PUH & set pkr @ 845'. RIH & perf @ 1130', EIR @ 1BPM @ 800#, M&P 40sx CL C cmt, PUH, WOC.

1/28/2015 RIH & tag cmt @ 1010', mark Whitaker-NMOCD approved to continue plugging. PUH to 30' & set pkr. Per Mark Whitaker-NMOCD, monitor well, bubbling 9-5/8" to 7". RIH & perf @ 900', EIR, M&P 40sx CL C cmt w/ 2% CaCl₂, pressure to 700#, WOC.

1/29/2015 Per Mark Whitaker-NMOCD, monitor well for 1hr, bubbling 9-5/8" to 7", pressure built up to 30#. RIH & tag cmt @ 753', PUH & perf @ 700', EIR, M&P 40sx CL C cmt w/ 2% CaCl₂, pressure to 500#, WOC. Per Mark Whitaker-NMOCD, monitor well for 10min, bubbling 9-5/8" to 7", pressure built up to 0#. Perf @ 519', EIR, M&P 40sx CL C cmt w/ 2% CaCl₂, pressure to 500#, WOC.

1/30/2015 RIH & tag cmt @ 395', POOH, RIH & set pkr @ 30', RIH & perf @ 100', EIR @ 1.5BPM @ 0#, M&P 40sx CL C cmt, circ cmt to surf. RDBOP, top off csg, RDPU.