Office	Tew Mexico Form C-103
=	nd Natural Resources Revised July 18, 2013 WELL API NO.
1625 N. French Dr., Hobbs, NM 88240 <u>District II</u> – (575) 748-1283	20.025.11480
811 S. First St., Artesia, NM 88210 OIL CONSERV.	A HON DIVISION 5 Indicate Type of Lease
1000 Pio Provos Pd. Artes, NM 97410	St. Francis Dr. STATE FEE S
District IV - (505) 476-3460 Santa Fe,	NM 87505 6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM	
SUNDRY NOTICES AND REPORTS ON (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPI DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM PROPOSALS.)	IN OR PLUG BACK TO A C-101) FOR SUCH  LANGLIE JAL UNIT
	ECTOR TIBELEGE
2. Name of Operator	9. OGRID Number
LEGACY RESERVES OPERATING L  3. Address of Operator	P FFR <b>2 5 2015</b> 240974 10. Pool name or Wildcat
PO BOX 10848, MIDLAND, TX 79702	
4. Well Location	RECEIVED
Section <u>6</u> Township 2	
11. Elevation (Show who	ther DR, RKB, RT, GR, etc.)
3230 DI	
10 101 1	
E-PERMI <del>TTING</del>	te Nature of Notice, Report or Other Data
P&A NR P.M. P&A R	SUBSEQUENT REPORT OF:
PE INT TO P&A COMP	REMEDIAL WORK ALTERING CASING
TEI CSNG CHG Loc	COMMENCE DRILLING OPNS. □ P AND A □
DII	CASING/CEMENT JOB
PO TA RBDMS CHARI	
CLOSED-LOOP SYSTEM IXI	
CLOSED-LOOP SYSTEM  OTHER:	OTHER:
OTHER:  13. Describe proposed or completed operations. (Clearly	state all pertinent details, and give pertinent dates, including estimated date
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1	
OTHER:  13. Describe proposed or completed operations. (Clearly	state all pertinent details, and give pertinent dates, including estimated date
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1	state all pertinent details, and give pertinent dates, including estimated date
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.	state all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. N	state all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Noring on wireline. Stopped @ 3100'. RIH w/m	state all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper.
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Noring on wireline. Stopped @ 3100'. RIH w/n 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Market)	batate all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper.
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Nor ring on wireline. Stopped @ 3100'. RIH w/m 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spot	D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper.  Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH.
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Nor ring on wireline. Stopped @ 3100'. RIH w/m 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spot 02/13/15 Set packer @ 34' and pressured up on esg to 20.	D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper.  Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH.  S00 psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Nor ring on wireline. Stopped @ 3100'. RIH w/m 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spot 02/13/15 Set packer @ 34' and pressured up on esg to 20.	D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper.  Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH.  Soo psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'.
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Nring on wireline. Stopped @ 3100'. RIH w/n 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mar Circulated 120 bbls. of mud laden fluid. Spot 02/13/15 Set packer @ 34' and pressured up on csg to cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surfact 02/16/15 Moved in backhoe and welder. Dug out cellar	D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper.  Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH.  500 psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. e. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker".
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Noring on wireline. Stopped @ 3100'. RIH w/n 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spott 02/13/15 Set packer @ 34' and pressured up on csg to see cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surfact 02/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and more starting and pressured up on csg to see the surfact of the sur	batate all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper. Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH. 500 psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. E. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". ved off.
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Noring on wireline. Stopped @ 3100'. RIH w/m 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spott of cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surface 02/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and model of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped	D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper.  Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH.  500 psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. e. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker".
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Noring on wireline. Stopped @ 3100'. RIH w/n 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spott 02/13/15 Set packer @ 34' and pressured up on csg to see cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surfact 02/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and more starting and pressured up on csg to see the surfact of the sur	batate all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper. Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH. 500 psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. E. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". ved off.
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Noring on wireline. Stopped @ 3100'. RIH w/m 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spott of cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surface 02/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and model of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped of the stopped complete to surface of the stopped	batate all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper. Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH. 500 psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. E. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". ved off.
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. N ring on wireline. Stopped @ 3100'. RIH w/n 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mar Circulated 120 bbls. of mud laden fluid. Spot 02/13/15 Set packer @ 34' and pressured up on csg to cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surface 02/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and moderate in the stopping of	batate all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper. Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH. 500 psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. E. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". ved off.  S. Hauled contents from Closed-Loop System to approved NMOCD
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Noring on wireline. Stopped @ 3100'. RIH w/n 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spot 02/13/15 Set packer @ 34' and pressured up on csg to cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surfact 02/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and model installed Closed-Loop System with steel tank disposal location according to Rule 19.15.17.	batate all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper. Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH. 500 psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. E. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". ved off.
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. N ring on wireline. Stopped @ 3100'. RIH w/n 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mar Circulated 120 bbls. of mud laden fluid. Spot 02/13/15 Set packer @ 34' and pressured up on csg to cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surface 02/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and moderate in the stopping of	batate all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper. Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH. 500 psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. E. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". ved off.  S. Hauled contents from Closed-Loop System to approved NMOCD
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Noring on wireline. Stopped @ 3100'. RIH w/n 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spot 02/13/15 Set packer @ 34' and pressured up on csg to cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surface 02/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and model Installed Closed-Loop System with steel tank disposal location according to Rule 19.15.17.  Spud Date:  Rig R	batate all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge of otched collar to 3100. Could not go deeper. Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH. Soo psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. E. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". ved off.  S. Hauled contents from Closed-Loop System to approved NMOCD selease Date:
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. N ring on wireline. Stopped @ 3100'. RIH w/n 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mar Circulated 120 bbls. of mud laden fluid. Spot 02/13/15 Set packer @ 34' and pressured up on csg to cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surface 02/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and moderate in the stopping of	batate all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge of otched collar to 3100. Could not go deeper. Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH. Soo psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. E. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". ved off.  S. Hauled contents from Closed-Loop System to approved NMOCD selease Date:
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Noring on wireline. Stopped @ 3100'. RIH w/n 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spot 02/13/15 Set packer @ 34' and pressured up on csg to cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surface 02/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and model Installed Closed-Loop System with steel tank disposal location according to Rule 19.15.17.  Spud Date:  Rig R	batate all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge of otched collar to 3100. Could not go deeper. Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH. Soo psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. E. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". ved off.  S. Hauled contents from Closed-Loop System to approved NMOCD selease Date:
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Noring on wireline. Stopped @ 3100'. RIH w/n 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spot 02/13/15 Set packer @ 34' and pressured up on csg to cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surface 02/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and model Installed Closed-Loop System with steel tank disposal location according to Rule 19.15.17.  Spud Date: Rig R	state all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper. (a Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH. 500 psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. e. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". ved off.  s. Hauled contents from Closed-Loop System to approved NMOCD elease Date:
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Noring on wireline. Stopped @ 3100'. RIH w/n 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spot 02/13/15 Set packer @ 34' and pressured up on csg to cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surface 02/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and model Installed Closed-Loop System with steel tank disposal location according to Rule 19.15.17.  Spud Date:  Rig R	state all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper. (a Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH. 500 psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. e. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". ved off.  s. Hauled contents from Closed-Loop System to approved NMOCD elease Date:
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. North ring on wireline. Stopped @ 3100'. RIH w/m 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spott of 2/13/15 Set packer @ 34' and pressured up on csg to see cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surfact of 2/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and moderate and disposal location according to Rule 19.15.17.  Spud Date:  Rig R  TITL	state all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of D wellhead. NU BOP. POH w/ production equipment. RIH w/ gauge otched collar to 3100. Could not go deeper. (a Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. ted 60 sx cement @ 3056-2708. POH. 500 psi. Held. Perf'd csg @ 1250'. Set packer @ 750' and Sqz'd 75 sx plug @ 937'. POH w/ tbg. ND BOP and wellhead. Perf'd csg @ 350'. e. Rigged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". ved off.  s. Hauled contents from Closed-Loop System to approved NMOCD elease Date:
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. North ring on wireline. Stopped @ 3100'. RIH w/m 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spott of cement and displaced to 950'. WOC. Tagged Sqz'd 115 sx cement and circulated to surfact of 2/16/15 Moved in backhoe and welder. Dug out cellar Removed deadmen. Cleaned location and moderate and disposal location according to Rule 19.15.17.  Spud Date:  Rig R  Title  SIGNATURE	batate all pertinent details, and give pertinent dates, including estimated dates 4 NMAC. For Multiple Completions: Attach wellbore diagram of the Word of Multiple Completions: Attach wellbore diagram of the Word of Seeper.  Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. Tagged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". Tagged down and moved off.  Welded on "Above Ground Dry Hole Marker". Tagged down and moved off.  Welded on "Above Ground Dry Hole Marker". Tagged down and moved off.  Wellhead. Welded on "Above Ground Dry Hole Marker". Tagged down and moved off.  Wellease Date:  DATE 02/23/2015
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 MIRU plugging equipment. Dug out cellar. Noring on wireline. Stopped @ 3100'. RIH w/m 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spott of mud l	batate all pertinent details, and give pertinent dates, including estimated date 4 NMAC. For Multiple Completions: Attach wellbore diagram of the MMAC. For Multiple Completions: Attach wellbore diagram of the MMAC. For Multiple Completions: Attach wellbore diagram of the MMAC. For Multiple Completions: Attach wellbore diagram of the MMAC. For Multiple Completions: Attach wellbore diagram of the MMAC. For Multiple Completions: Attach wellbore diagram of the Mmach and the Mma
OTHER:  13. Describe proposed or completed operations. (Clearly of starting any proposed work). SEE RULE 19.15.7.1 proposed completion or recompletion.  02/11/15 M1RU plugging equipment. Dug out cellar. Noring on wireline. Stopped @ 3100'. RIH w/m 02/12/15 Spotted 40 sx cement @ 3405-3030. (per Mark Circulated 120 bbls. of mud laden fluid. Spott of mud l	batate all pertinent details, and give pertinent dates, including estimated dates 4 NMAC. For Multiple Completions: Attach wellbore diagram of the Word of Multiple Completions: Attach wellbore diagram of the Word of Seeper.  Whitaker w/ OCD). Pull out of cement WOC. Tagged plug @ 3056'. Tagged down and moved off.  Cut off wellhead. Welded on "Above Ground Dry Hole Marker". Tagged down and moved off.  Welded on "Above Ground Dry Hole Marker". Tagged down and moved off.  Welded on "Above Ground Dry Hole Marker". Tagged down and moved off.  Wellhead. Welded on "Above Ground Dry Hole Marker". Tagged down and moved off.  Wellease Date:  DATE 02/23/2015