

HOBBS'OOD

MAR 05 2015

RECEIVED

Basin

*H₂S, water flows, loss of circulation, abnormal pressures, etc.

Devon Energy, North Thistle 34 State Com 1H

2. Casing Program

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
	From	To							
17.5"	0	1,400'	13.375"	48	H-40	STC	1.23	2.76	8.05
12.25"	0	5,250'	9.625"	40	HCK-55	BTC	1.549	1.45	4.41
8.75"	0	10,685'	7"	29	HCP-110	BTC	1.69	2.06	2.93
8.75"	10,685'	15,670'	5.5"	17	HCP-110	BTC	1.58	1.95	2.97
BLM Minimum Safety Factor							1.125	1.00	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h

Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Devon Energy, North Thistle 34 State Com 1H

3. Cementing Program

Casing	# Sks	Wt. lb/ gal	H ₂ O gal/sk	Yld ft ³ / sack	500# Comp. Strength (hours)	Slurry Description
13-3/8" Surface	680	12.9	9.81	1.85	14	Lead: (65:35) Class C Cement: Poz (Fly Ash): 6% BWOC Bentonite + 5% BWOW Sodium Chloride + 0.125 lbs/sack Poly-E-Flake
	550	14.8	6.32	1.33	6	Tail: Class C Cement + 0.125 lbs/sack Poly-E-Flake
9-5/8" Inter.	1100	12.9	9.81	1.85	14	Lead: (65:35) Class C Cement: Poz (Fly Ash): 6% BWOC Bentonite + 5% BWOW Sodium Chloride + 0.125 lbs/sack Poly-E-Flake
	430	14.8	6.32	1.33	6	Tail: Class C Cement + 0.125 lbs/sack Poly-E-Flake
7 x 5-1/2" Combo Prod.	350	10.4	16.9	3.17	16	Lead: Tuned Light ® + 0.125 lb/sk Pol-E-Flake
	1320	14.5	5.31	1.2	25	Tail: (50:50) Class H Cement: Poz (Fly Ash) + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.2% BWOC HR-601 + 2% bwoc Bentonite
7 x 5-1/2" Combo Prod. Two Stage Option	520	12.5	10.86	1.96	30	1 st Stage Lead: (65:35) Class H Cement: Poz (Fly Ash) + 6% BWOC Bentonite + 0.25% BWOC HR-601 + 0.125 lbs/sack Poly-E-Flake
	1320	14.5	5.31	1.2	25	1 st Stage Lead: (50:50) Class H Cement: Poz (Fly Ash) + 0.5% bwoc HALAD-344 + 0.4% bwoc CFR-3 + 0.2% BWOC HR-601 + 2% bwoc Bentonite
	DV Tool = 5300ft					
	20	10.4	16.9	3.17	16	2 nd Stage Lead: Tuned Light ® + 0.125 lb/sk Pol-E-Flake
	30	14.8	6.32	1.33	6	2 nd Stage Tail: Class C Cement + 0.125 lbs/sack Poly-E-Flake

DV tool depth(s) will be adjusted based on hole conditions and cement volumes will be adjusted proportionally. DV tool will be set a minimum of 50 feet below previous casing and a minimum of 200 feet above current shoe. Lab reports with the 500 psi compressive strength time for the cement will be onsite for review.

Pilot Hole depth 11400ft

KOP 10685ft

Plug top	Plug Bottom	% Excess	No Sacks	Wt. lb/gal	Yld ft ³ /sack	Water gal/sk	Slurry Description and Cement Type
10485	11400	10	355	15.6	1.19	5.42	Class H + 0.5% BWOC HR-601 + 0.2% Halad-9

Casing String	TOC	% Excess
13-3/8" Surface	0'	100%
9-5/8" Intermediate	0'	75%
7 x 5-1/2" Production Casing	4750'	25%
7 x 5-1/2" Production Casing – Two Stage Option	1 st Stage = 5300' / 2 nd Stage = 4750'	25%

Devon Energy, North Thistle 34 State Com 1H

4. Pressure Control Equipment

N	A variance is requested for the use of a diverter on the surface casing.
---	--

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
12-1/4"	13-5/8"	3M	Annular	x	50% of working pressure
			Blind Ram		3M
			Pipe Ram		
			Double Ram	x	
			Other*		
8-3/4"	13-5/8"	3M	Annular	x	50% testing pressure
			Blind Ram		3M
			Pipe Ram		
			Double Ram	x	
			Other*		
			Annular	x	
			Blind Ram		
			Pipe Ram		
			Double Ram	x	
			Other*		

*Specify if additional ram is utilized.

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold.

Y	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
Y	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold.

Devon Energy, North Thistle 34 State Com 1H

	Y	Are anchors required by manufacturer?
Y	A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested. Devon proposes using a multi-bowl wellhead assembly (FMC Uni-head). This assembly will only be tested when installed on the surface casing. Minimum working pressure of the blowout preventer (BOP) and related equipment (BOPE) required for drilling below the surface casing shoe shall be 3000 (3M) psi. • Wellhead will be installed by FMC's representatives. • If the welding is performed by a third party, the FMC's representative will monitor the temperature to verify that it does not exceed the maximum temperature of the seal. • FMC representative will install the test plug for the initial BOP test. • FMC will install a solid steel body pack-off to completely isolate the lower head after cementing intermediate casing. After installation of the pack-off, the pack-off and the lower flange will be tested to 3M, as shown on the attached schematic. Everything above the pack-off will not have been altered whatsoever from the initial nipple up. Therefore the BOP components will not be retested at that time. • If the cement does not circulate and one inch operations would have been possible with a standard wellhead, the well head will be cut and top out operations will be conducted. • Devon will pressure test all seals above and below the mandrel (but still above the casing) to full working pressure rating. • Devon will test the casing to 0.22 psi/ft or 1500 psi, whichever is greater, as per Onshore Order #2. After running the 13-3/8" surface casing, a 13-5/8" BOP/BOPE system with a minimum rating of 3M will be installed on the FMC Uni-head wellhead system and will undergo a 250 psi low pressure test followed by a 3,000 psi high pressure test. The 3,000 psi high and 250 psi low test will cover testing requirements a maximum of 30 days, as per Onshore Order #2. If the well is not complete within 30 days of this BOP test, another full BOP test will be conducted, as per Onshore Order #2. After running the 9-5/8" intermediate casing with a mandrel hanger, the 13-5/8" BOP/BOPE system with a minimum rating of 3M will already be installed on the FMC Uni-head. The pipe rams will be operated and checked each 24 hour period and each time the drill pipe is out of the hole. These tests will be logged in the daily driller's log. A 2" kill line and 3" choke line will be incorporated into the drilling spool below the ram BOP. In addition to the rams and annular preventer, additional BOP accessories include a kelly cock, floor safety valve, choke lines, and choke manifold rated at 3,000 psi WP. Devon requests a variance to use a flexible line with flanged ends between the BOP and the choke manifold (choke line). The line will be kept as straight as possible with minimal turns	

Devon Energy, North Thistle 34 State Com 1H

--	--

5. Mud Program

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0	1,400'	FW Gel	8.6-8.8	28-34	N/C
1,400'	5,250'	Saturated Brine	10.0-10.2	28-34	N/C
5,250'	15,670'	Cut Brine	8.5-9.3	28-34	N/C

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing.	
x	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No Logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain
	Coring? If yes, explain

Additional logs planned	Interval
Resistivity	Int. shoe to KOP
Density	Int. shoe to KOP
X CBL	Production casing
X Mud log	Intermediate shoe to TD
PEX	

Devon Energy, North Thistle 34 State Com 1H

7. Drilling Conditions

Condition	Specify what type and where?
BH Pressure at deepest TVD	3005 psi
Abnormal Temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers.

Hydrogen Sulfide (H₂S) monitors will be installed prior to drilling out the surface shoe. If H₂S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.

N H₂S is present

N H₂S Plan attached

8. Other facets of operation

Is this a walking operation? No.

Will be pre-setting casing? No.

Attachments

☒ Directional Plan

☐ Other, describe

DEVON ENERGY

Project: Lea County, NM (NAD-83)
Site: North Thistle 34 State Com
Well: 1H
Wellbore: OH
Design: Plan #1



Azimuths to Grid North
True North: -0.41°
Magnetic North: 6.91°

Magnetic Field
Strength: 48272.9snT
Dip Angle: 60.20°
Date: 2/9/2015
Model: BGGM2014

PROJECT DETAILS: Lea County, NM (NAD-83)
Geodetic System: US State Plane 1983
Datum: North American Datum 1983
Ellipsoid: GRS 1980
Zone: New Mexico Eastern Zone

devon

DESIGN TARGET DETAILS



Name	TVD	+N/-S	+E/-W	Northing	Easting	Latitude	Longitude
SHL (NT34SC 1H)	0.00	0.00	0.00	488923.10	777934.50	32° 20' 30.461 N	103° 34' 2.071 W
PBHL (NT34SC 1H)	11258.00	4658.70	-35.00	493581.80	777899.50	32° 21' 16.561 N	103° 34' 2.091 W

SECTION DETAILS

Sec	MD	Inc	Azi	TVD	+N/-S	+E/-W	Dleg	TFace	VSect	Annotation
1	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
2	10685.04	0.00	0.00	10685.04	0.00	0.00	0.00	0.00	0.00	KOP 10° DLS
3	11585.04	90.00	359.57	11258.00	572.94	-4.30	10.00	359.57	572.96	LP
4	15670.92	90.00	359.57	11258.00	4658.70	-35.00	0.00	0.00	4658.83	TD

FORMATION TOP DETAILS

TVDPath	MDPath	Formation	DipAngle	DipDir
1101.00	1101.00	Rustler	0.00	
1691.00	1691.00	Top Salt	0.00	
5265.00	5265.00	Delaware	0.00	
5991.00	5991.00	Cherry Canyon	0.00	
7271.00	7271.00	Brushy Canyon	0.00	
8933.00	8933.00	Bone Spring	0.00	
10833.00	10834.70	2nd BS	0.00	



LEAM DRILLING SYSTEMS LLC
2010 East Davis, Conroe, Texas 77301
Phone: 936/756-7577, Fax 936/756-7595

Plan: Plan #1 (1H/OH)
North Thistle 34 State Com
Created By: Brady Deaver Date: 11:00, February 09 2015
Date: _____
Approved: _____ Date: _____



LEAM

Drilling Systems, Inc.

DEVON ENERGY

Lea County, NM (NAD-83)
North Thistle 34 State Com
1H

OH

Plan: Plan #1

Standard Planning Report

09 February, 2015


devon



LEAM Drilling Systems LLC
Planning Report

devon

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well 1H
Company:	DEVON ENERGY	TVD Reference:	3567' GL + 25' RKB @ 3592.00usft
Project:	Lea County, NM (NAD-83)	MD Reference:	3567' GL + 25' RKB @ 3592.00usft
Site:	North Thistle 34 State Com	North Reference:	Grid
Well:	1H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #1		

Project	Lea County, NM (NAD-83)		
Map System:	US State Plane 1983	System Datum:	Mean Sea Level
Geo Datum:	North American Datum 1983		
Map Zone:	New Mexico Eastern Zone		

Site	North Thistle 34 State Com				
Site Position:	Northing:	488,923.10 usft	Latitude:	32° 20' 30.461 N	
From:	Map	Easting:	777,934.50 usft	Longitude:	103° 34' 2.071 W
Position Uncertainty:	0.00 usft	Slot Radius:	13-3/16 "	Grid Convergence:	0.41 °

Well	1H					
Well Position	+N/-S	0.00 usft	Northing:	488,923.10 usft	Latitude:	32° 20' 30.461 N
	+E/-W	0.00 usft	Easting:	777,934.50 usft	Longitude:	103° 34' 2.071 W
Position Uncertainty	0.00 usft	Wellhead Elevation:	3,592.00 usft	Ground Level:	3,567.00 usft	

Wellbore	OH				
Magnetics	Model Name	Sample Date	Declination	Dip Angle	Field Strength
	BGGM2014	2/9/2015	(°)	(°)	(nT)
			7.31	60.20	48,273

Design	Plan #1			
Audit Notes:				
Version:	Phase:	PLAN	Tie On Depth:	0.00
Vertical Section:	Depth From (TVD)	+N/-S	+E/-W	Direction
	(usft)	(usft)	(usft)	(°)
	0.00	0.00	0.00	359.57

Plan Sections										
Measured	Inclination	Azimuth	Vertical	+N/-S	+E/-W	Dogleg	Build	Turn	TFO	Target
Depth	(°)	(°)	Depth	(usft)	(usft)	Rate	Rate	Rate	(°)	
(usft)			(usft)			(°/100usft)	(°/100usft)	(°/100usft)		
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	
10,685.04	0.00	0.00	10,685.04	0.00	0.00	0.00	0.00	0.00	0.00	
11,585.04	90.00	359.57	11,258.00	572.94	-4.30	10.00	10.00	0.00	359.57	
15,670.92	90.00	359.57	11,258.00	4,658.70	-35.00	0.00	0.00	0.00	0.00	PBHL (NT34SC 1H)



LEAM Drilling Systems LLC
Planning Report

devon

Database: EDM 5000.1 Single User Db
Company: DEVON ENERGY
Project: Lea County, NM (NAD-83)
Site: North Thistle 34 State Com
Well: 1H
Wellbore: OH
Design: Plan #1

Local Co-ordinate Reference: Well 1H
TVD Reference: 3567' GL + 25' RKB @ 3592.00usft
MD Reference: 3567' GL + 25' RKB @ 3592.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00	0.00
SHL (NT34SC 1H)									
100.00	0.00	0.00	100.00	0.00	0.00	0.00	0.00	0.00	0.00
200.00	0.00	0.00	200.00	0.00	0.00	0.00	0.00	0.00	0.00
300.00	0.00	0.00	300.00	0.00	0.00	0.00	0.00	0.00	0.00
400.00	0.00	0.00	400.00	0.00	0.00	0.00	0.00	0.00	0.00
500.00	0.00	0.00	500.00	0.00	0.00	0.00	0.00	0.00	0.00
600.00	0.00	0.00	600.00	0.00	0.00	0.00	0.00	0.00	0.00
700.00	0.00	0.00	700.00	0.00	0.00	0.00	0.00	0.00	0.00
800.00	0.00	0.00	800.00	0.00	0.00	0.00	0.00	0.00	0.00
900.00	0.00	0.00	900.00	0.00	0.00	0.00	0.00	0.00	0.00
1,000.00	0.00	0.00	1,000.00	0.00	0.00	0.00	0.00	0.00	0.00
1,100.00	0.00	0.00	1,100.00	0.00	0.00	0.00	0.00	0.00	0.00
1,101.00	0.00	0.00	1,101.00	0.00	0.00	0.00	0.00	0.00	0.00
Rustler									
1,200.00	0.00	0.00	1,200.00	0.00	0.00	0.00	0.00	0.00	0.00
1,300.00	0.00	0.00	1,300.00	0.00	0.00	0.00	0.00	0.00	0.00
1,400.00	0.00	0.00	1,400.00	0.00	0.00	0.00	0.00	0.00	0.00
1,500.00	0.00	0.00	1,500.00	0.00	0.00	0.00	0.00	0.00	0.00
1,600.00	0.00	0.00	1,600.00	0.00	0.00	0.00	0.00	0.00	0.00
1,691.00	0.00	0.00	1,691.00	0.00	0.00	0.00	0.00	0.00	0.00
Top Salt									
1,700.00	0.00	0.00	1,700.00	0.00	0.00	0.00	0.00	0.00	0.00
1,800.00	0.00	0.00	1,800.00	0.00	0.00	0.00	0.00	0.00	0.00
1,900.00	0.00	0.00	1,900.00	0.00	0.00	0.00	0.00	0.00	0.00
2,000.00	0.00	0.00	2,000.00	0.00	0.00	0.00	0.00	0.00	0.00
2,100.00	0.00	0.00	2,100.00	0.00	0.00	0.00	0.00	0.00	0.00
2,200.00	0.00	0.00	2,200.00	0.00	0.00	0.00	0.00	0.00	0.00
2,300.00	0.00	0.00	2,300.00	0.00	0.00	0.00	0.00	0.00	0.00
2,400.00	0.00	0.00	2,400.00	0.00	0.00	0.00	0.00	0.00	0.00
2,500.00	0.00	0.00	2,500.00	0.00	0.00	0.00	0.00	0.00	0.00
2,600.00	0.00	0.00	2,600.00	0.00	0.00	0.00	0.00	0.00	0.00
2,700.00	0.00	0.00	2,700.00	0.00	0.00	0.00	0.00	0.00	0.00
2,800.00	0.00	0.00	2,800.00	0.00	0.00	0.00	0.00	0.00	0.00
2,900.00	0.00	0.00	2,900.00	0.00	0.00	0.00	0.00	0.00	0.00
3,000.00	0.00	0.00	3,000.00	0.00	0.00	0.00	0.00	0.00	0.00
3,100.00	0.00	0.00	3,100.00	0.00	0.00	0.00	0.00	0.00	0.00
3,200.00	0.00	0.00	3,200.00	0.00	0.00	0.00	0.00	0.00	0.00
3,300.00	0.00	0.00	3,300.00	0.00	0.00	0.00	0.00	0.00	0.00
3,400.00	0.00	0.00	3,400.00	0.00	0.00	0.00	0.00	0.00	0.00
3,500.00	0.00	0.00	3,500.00	0.00	0.00	0.00	0.00	0.00	0.00
3,600.00	0.00	0.00	3,600.00	0.00	0.00	0.00	0.00	0.00	0.00
3,700.00	0.00	0.00	3,700.00	0.00	0.00	0.00	0.00	0.00	0.00
3,800.00	0.00	0.00	3,800.00	0.00	0.00	0.00	0.00	0.00	0.00
3,900.00	0.00	0.00	3,900.00	0.00	0.00	0.00	0.00	0.00	0.00
4,000.00	0.00	0.00	4,000.00	0.00	0.00	0.00	0.00	0.00	0.00
4,100.00	0.00	0.00	4,100.00	0.00	0.00	0.00	0.00	0.00	0.00
4,200.00	0.00	0.00	4,200.00	0.00	0.00	0.00	0.00	0.00	0.00
4,300.00	0.00	0.00	4,300.00	0.00	0.00	0.00	0.00	0.00	0.00
4,400.00	0.00	0.00	4,400.00	0.00	0.00	0.00	0.00	0.00	0.00
4,500.00	0.00	0.00	4,500.00	0.00	0.00	0.00	0.00	0.00	0.00
4,600.00	0.00	0.00	4,600.00	0.00	0.00	0.00	0.00	0.00	0.00
4,700.00	0.00	0.00	4,700.00	0.00	0.00	0.00	0.00	0.00	0.00



LEAM Drilling Systems LLC
Planning Report

devon

Database:	EDM 5000.1 Single User Db	Local Co-ordinate Reference:	Well 1H
Company:	DEVON ENERGY	TVD Reference:	3567' GL + 25' RKB @ 3592.00usft
Project:	Lea County, NM (NAD-83)	MD Reference:	3567' GL + 25' RKB @ 3592.00usft
Site:	North Thistle 34 State Com	North Reference:	Grid
Well:	1H	Survey Calculation Method:	Minimum Curvature
Wellbore:	OH		
Design:	Plan #1		

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
4,800.00	0.00	0.00	4,800.00	0.00	0.00	0.00	0.00	0.00	0.00
4,900.00	0.00	0.00	4,900.00	0.00	0.00	0.00	0.00	0.00	0.00
5,000.00	0.00	0.00	5,000.00	0.00	0.00	0.00	0.00	0.00	0.00
5,100.00	0.00	0.00	5,100.00	0.00	0.00	0.00	0.00	0.00	0.00
5,200.00	0.00	0.00	5,200.00	0.00	0.00	0.00	0.00	0.00	0.00
5,265.00	0.00	0.00	5,265.00	0.00	0.00	0.00	0.00	0.00	0.00
Delaware									
5,300.00	0.00	0.00	5,300.00	0.00	0.00	0.00	0.00	0.00	0.00
5,400.00	0.00	0.00	5,400.00	0.00	0.00	0.00	0.00	0.00	0.00
5,500.00	0.00	0.00	5,500.00	0.00	0.00	0.00	0.00	0.00	0.00
5,600.00	0.00	0.00	5,600.00	0.00	0.00	0.00	0.00	0.00	0.00
5,700.00	0.00	0.00	5,700.00	0.00	0.00	0.00	0.00	0.00	0.00
5,800.00	0.00	0.00	5,800.00	0.00	0.00	0.00	0.00	0.00	0.00
5,900.00	0.00	0.00	5,900.00	0.00	0.00	0.00	0.00	0.00	0.00
5,991.00	0.00	0.00	5,991.00	0.00	0.00	0.00	0.00	0.00	0.00
Cherry Canyon									
6,000.00	0.00	0.00	6,000.00	0.00	0.00	0.00	0.00	0.00	0.00
6,100.00	0.00	0.00	6,100.00	0.00	0.00	0.00	0.00	0.00	0.00
6,200.00	0.00	0.00	6,200.00	0.00	0.00	0.00	0.00	0.00	0.00
6,300.00	0.00	0.00	6,300.00	0.00	0.00	0.00	0.00	0.00	0.00
6,400.00	0.00	0.00	6,400.00	0.00	0.00	0.00	0.00	0.00	0.00
6,500.00	0.00	0.00	6,500.00	0.00	0.00	0.00	0.00	0.00	0.00
6,600.00	0.00	0.00	6,600.00	0.00	0.00	0.00	0.00	0.00	0.00
6,700.00	0.00	0.00	6,700.00	0.00	0.00	0.00	0.00	0.00	0.00
6,800.00	0.00	0.00	6,800.00	0.00	0.00	0.00	0.00	0.00	0.00
6,900.00	0.00	0.00	6,900.00	0.00	0.00	0.00	0.00	0.00	0.00
7,000.00	0.00	0.00	7,000.00	0.00	0.00	0.00	0.00	0.00	0.00
7,100.00	0.00	0.00	7,100.00	0.00	0.00	0.00	0.00	0.00	0.00
7,200.00	0.00	0.00	7,200.00	0.00	0.00	0.00	0.00	0.00	0.00
7,271.00	0.00	0.00	7,271.00	0.00	0.00	0.00	0.00	0.00	0.00
Brushy Canyon									
7,300.00	0.00	0.00	7,300.00	0.00	0.00	0.00	0.00	0.00	0.00
7,400.00	0.00	0.00	7,400.00	0.00	0.00	0.00	0.00	0.00	0.00
7,500.00	0.00	0.00	7,500.00	0.00	0.00	0.00	0.00	0.00	0.00
7,600.00	0.00	0.00	7,600.00	0.00	0.00	0.00	0.00	0.00	0.00
7,700.00	0.00	0.00	7,700.00	0.00	0.00	0.00	0.00	0.00	0.00
7,800.00	0.00	0.00	7,800.00	0.00	0.00	0.00	0.00	0.00	0.00
7,900.00	0.00	0.00	7,900.00	0.00	0.00	0.00	0.00	0.00	0.00
8,000.00	0.00	0.00	8,000.00	0.00	0.00	0.00	0.00	0.00	0.00
8,100.00	0.00	0.00	8,100.00	0.00	0.00	0.00	0.00	0.00	0.00
8,200.00	0.00	0.00	8,200.00	0.00	0.00	0.00	0.00	0.00	0.00
8,300.00	0.00	0.00	8,300.00	0.00	0.00	0.00	0.00	0.00	0.00
8,400.00	0.00	0.00	8,400.00	0.00	0.00	0.00	0.00	0.00	0.00
8,500.00	0.00	0.00	8,500.00	0.00	0.00	0.00	0.00	0.00	0.00
8,600.00	0.00	0.00	8,600.00	0.00	0.00	0.00	0.00	0.00	0.00
8,700.00	0.00	0.00	8,700.00	0.00	0.00	0.00	0.00	0.00	0.00
8,800.00	0.00	0.00	8,800.00	0.00	0.00	0.00	0.00	0.00	0.00
8,900.00	0.00	0.00	8,900.00	0.00	0.00	0.00	0.00	0.00	0.00
8,933.00	0.00	0.00	8,933.00	0.00	0.00	0.00	0.00	0.00	0.00
Bone Spring									
9,000.00	0.00	0.00	9,000.00	0.00	0.00	0.00	0.00	0.00	0.00
9,100.00	0.00	0.00	9,100.00	0.00	0.00	0.00	0.00	0.00	0.00
9,200.00	0.00	0.00	9,200.00	0.00	0.00	0.00	0.00	0.00	0.00
9,300.00	0.00	0.00	9,300.00	0.00	0.00	0.00	0.00	0.00	0.00



LEAM Drilling Systems LLC
Planning Report



Database: EDM 5000.1 Single User Db
Company: DEVON ENERGY
Project: Lea County, NM (NAD-83)
Site: North Thistle 34 State Com
Well: 1H
Wellbore: OH
Design: Plan #1

Local Co-ordinate Reference:
TVD Reference: 3567' GL + 25' RKB @ 3592.00usft
MD Reference: 3567' GL + 25' RKB @ 3592.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Planned Survey

Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
9,400.00	0.00	0.00	9,400.00	0.00	0.00	0.00	0.00	0.00	0.00
9,500.00	0.00	0.00	9,500.00	0.00	0.00	0.00	0.00	0.00	0.00
9,600.00	0.00	0.00	9,600.00	0.00	0.00	0.00	0.00	0.00	0.00
9,700.00	0.00	0.00	9,700.00	0.00	0.00	0.00	0.00	0.00	0.00
9,800.00	0.00	0.00	9,800.00	0.00	0.00	0.00	0.00	0.00	0.00
9,900.00	0.00	0.00	9,900.00	0.00	0.00	0.00	0.00	0.00	0.00
10,000.00	0.00	0.00	10,000.00	0.00	0.00	0.00	0.00	0.00	0.00
10,100.00	0.00	0.00	10,100.00	0.00	0.00	0.00	0.00	0.00	0.00
10,200.00	0.00	0.00	10,200.00	0.00	0.00	0.00	0.00	0.00	0.00
10,300.00	0.00	0.00	10,300.00	0.00	0.00	0.00	0.00	0.00	0.00
10,400.00	0.00	0.00	10,400.00	0.00	0.00	0.00	0.00	0.00	0.00
10,500.00	0.00	0.00	10,500.00	0.00	0.00	0.00	0.00	0.00	0.00
10,600.00	0.00	0.00	10,600.00	0.00	0.00	0.00	0.00	0.00	0.00
10,685.04	0.00	0.00	10,685.04	0.00	0.00	0.00	0.00	0.00	0.00
KOP 10° DLS									
10,700.00	1.50	359.57	10,700.00	0.20	0.00	0.20	10.00	10.00	0.00
10,750.00	6.50	359.57	10,749.86	3.68	-0.03	3.68	10.00	10.00	0.00
10,800.00	11.50	359.57	10,799.23	11.49	-0.09	11.49	10.00	10.00	0.00
10,834.70	14.97	359.57	10,833.00	19.43	-0.15	19.43	10.00	10.00	0.00
2nd BS									
10,850.00	16.50	359.57	10,847.73	23.58	-0.18	23.58	10.00	10.00	0.00
10,900.00	21.50	359.57	10,894.99	39.85	-0.30	39.85	10.00	10.00	0.00
10,950.00	26.50	359.57	10,940.66	60.18	-0.45	60.18	10.00	10.00	0.00
11,000.00	31.50	359.57	10,984.38	84.41	-0.63	84.41	10.00	10.00	0.00
11,050.00	36.50	359.57	11,025.82	112.35	-0.84	112.36	10.00	10.00	0.00
11,100.00	41.50	359.57	11,064.66	143.81	-1.08	143.81	10.00	10.00	0.00
11,150.00	46.50	359.57	11,100.62	178.52	-1.34	178.53	10.00	10.00	0.00
11,200.00	51.50	359.57	11,133.42	216.24	-1.62	216.25	10.00	10.00	0.00
11,250.00	56.50	359.57	11,162.80	256.68	-1.93	256.69	10.00	10.00	0.00
11,300.00	61.50	359.57	11,188.55	299.52	-2.25	299.53	10.00	10.00	0.00
11,350.00	66.50	359.57	11,210.46	344.44	-2.59	344.45	10.00	10.00	0.00
11,400.00	71.50	359.57	11,228.38	391.10	-2.94	391.12	10.00	10.00	0.00
11,450.00	76.50	359.57	11,242.16	439.15	-3.30	439.16	10.00	10.00	0.00
11,500.00	81.50	359.57	11,251.70	488.21	-3.67	488.23	10.00	10.00	0.00
11,550.00	86.50	359.57	11,256.93	537.92	-4.04	537.94	10.00	10.00	0.00
11,585.04	90.00	359.57	11,258.00	572.94	-4.30	572.96	10.00	10.00	0.00
LP									
11,600.00	90.00	359.57	11,258.00	587.90	-4.42	587.92	0.00	0.00	0.00
11,700.00	90.00	359.57	11,258.00	687.90	-5.17	687.92	0.00	0.00	0.00
11,800.00	90.00	359.57	11,258.00	787.89	-5.92	787.92	0.00	0.00	0.00
11,900.00	90.00	359.57	11,258.00	887.89	-6.67	887.92	0.00	0.00	0.00
12,000.00	90.00	359.57	11,258.00	987.89	-7.42	987.92	0.00	0.00	0.00
12,100.00	90.00	359.57	11,258.00	1,087.88	-8.17	1,087.92	0.00	0.00	0.00
12,200.00	90.00	359.57	11,258.00	1,187.88	-8.92	1,187.92	0.00	0.00	0.00
12,300.00	90.00	359.57	11,258.00	1,287.88	-9.68	1,287.92	0.00	0.00	0.00
12,400.00	90.00	359.57	11,258.00	1,387.88	-10.43	1,387.92	0.00	0.00	0.00
12,500.00	90.00	359.57	11,258.00	1,487.87	-11.18	1,487.92	0.00	0.00	0.00
12,600.00	90.00	359.57	11,258.00	1,587.87	-11.93	1,587.92	0.00	0.00	0.00
12,700.00	90.00	359.57	11,258.00	1,687.87	-12.68	1,687.92	0.00	0.00	0.00
12,800.00	90.00	359.57	11,258.00	1,787.87	-13.43	1,787.92	0.00	0.00	0.00
12,900.00	90.00	359.57	11,258.00	1,887.86	-14.18	1,887.92	0.00	0.00	0.00
13,000.00	90.00	359.57	11,258.00	1,987.86	-14.93	1,987.92	0.00	0.00	0.00
13,100.00	90.00	359.57	11,258.00	2,087.86	-15.69	2,087.92	0.00	0.00	0.00



LEAM Drilling Systems LLC

Planning Report



Database: EDM 5000.1 Single User Db
 Company: DEVON ENERGY
 Project: Lea County, NM (NAD-83)
 Site: North Thistle 34 State Com
 Well: 1H
 Wellbore: OH
 Design: Plan #1

Local Co-ordinate Reference: Well 1H
 TVD Reference: 3567' GL + 25' RKB @ 3592.00usft
 MD Reference: 3567' GL + 25' RKB @ 3592.00usft
 North Reference: Grid
 Survey Calculation Method: Minimum Curvature

Planned Survey									
Measured Depth (usft)	Inclination (°)	Azimuth (°)	Vertical Depth (usft)	+N/-S (usft)	+E/-W (usft)	Vertical Section (usft)	Dogleg Rate (°/100usft)	Build Rate (°/100usft)	Turn Rate (°/100usft)
13,200.00	90.00	359.57	11,258.00	2,187.85	-16.44	2,187.92	0.00	0.00	0.00
13,300.00	90.00	359.57	11,258.00	2,287.85	-17.19	2,287.92	0.00	0.00	0.00
13,400.00	90.00	359.57	11,258.00	2,387.85	-17.94	2,387.92	0.00	0.00	0.00
13,500.00	90.00	359.57	11,258.00	2,487.85	-18.69	2,487.92	0.00	0.00	0.00
13,600.00	90.00	359.57	11,258.00	2,587.84	-19.44	2,587.92	0.00	0.00	0.00
13,700.00	90.00	359.57	11,258.00	2,687.84	-20.19	2,687.92	0.00	0.00	0.00
13,800.00	90.00	359.57	11,258.00	2,787.84	-20.94	2,787.92	0.00	0.00	0.00
13,900.00	90.00	359.57	11,258.00	2,887.83	-21.70	2,887.92	0.00	0.00	0.00
14,000.00	90.00	359.57	11,258.00	2,987.83	-22.45	2,987.92	0.00	0.00	0.00
14,100.00	90.00	359.57	11,258.00	3,087.83	-23.20	3,087.92	0.00	0.00	0.00
14,200.00	90.00	359.57	11,258.00	3,187.83	-23.95	3,187.92	0.00	0.00	0.00
14,300.00	90.00	359.57	11,258.00	3,287.82	-24.70	3,287.92	0.00	0.00	0.00
14,400.00	90.00	359.57	11,258.00	3,387.82	-25.45	3,387.92	0.00	0.00	0.00
14,500.00	90.00	359.57	11,258.00	3,487.82	-26.20	3,487.92	0.00	0.00	0.00
14,600.00	90.00	359.57	11,258.00	3,587.81	-26.95	3,587.92	0.00	0.00	0.00
14,700.00	90.00	359.57	11,258.00	3,687.81	-27.71	3,687.92	0.00	0.00	0.00
14,800.00	90.00	359.57	11,258.00	3,787.81	-28.46	3,787.92	0.00	0.00	0.00
14,900.00	90.00	359.57	11,258.00	3,887.81	-29.21	3,887.92	0.00	0.00	0.00
15,000.00	90.00	359.57	11,258.00	3,987.80	-29.96	3,987.92	0.00	0.00	0.00
15,100.00	90.00	359.57	11,258.00	4,087.80	-30.71	4,087.92	0.00	0.00	0.00
15,200.00	90.00	359.57	11,258.00	4,187.80	-31.46	4,187.92	0.00	0.00	0.00
15,300.00	90.00	359.57	11,258.00	4,287.79	-32.21	4,287.92	0.00	0.00	0.00
15,400.00	90.00	359.57	11,258.00	4,387.79	-32.96	4,387.92	0.00	0.00	0.00
15,500.00	90.00	359.57	11,258.00	4,487.79	-33.72	4,487.92	0.00	0.00	0.00
15,600.00	90.00	359.57	11,258.00	4,587.79	-34.47	4,587.92	0.00	0.00	0.00
15,670.92	90.00	359.57	11,258.00	4,658.70	-35.00	4,658.83	0.00	0.00	0.00
TD - PBHL (NT34SC 1H)									

Design Targets									
Target Name	Dip Angle (°)	Dip Dir. (°)	TVD (usft)	+N/-S (usft)	+E/-W (usft)	Northing (usft)	Easting (usft)	Latitude	Longitude
hit/miss target									
Shape									
SHL (NT34SC 1H)	0.00	0.00	0.00	0.00	0.00	488,923.10	777,934.50	32° 20' 30.461 N	103° 34' 2.071 W
- plan hits target center									
- Point									
PBHL (NT34SC 1H)	0.00	0.01	11,258.00	4,658.70	-35.00	493,581.80	777,899.50	32° 21' 16.561 N	103° 34' 2.091 W
- plan hits target center									
- Point									



LEAM Drilling Systems LLC

Planning Report




Database: EDM 5000.1 Single User Db
Company: DEVON ENERGY
Project: Lea County, NM (NAD-83)
Site: North Thistle 34 State Com
Well: 1H
Wellbore: OH
Design: Plan #1

Local Co-ordinate Reference: Well 1H
TVD Reference: 3567' GL + 25' RKB @ 3592.00usft
MD Reference: 3567' GL + 25' RKB @ 3592.00usft
North Reference: Grid
Survey Calculation Method: Minimum Curvature

Formations						
Measured Depth (usft)	Vertical Depth (usft)	Name	Lithology	Dip (°)	Dip Direction (°)	
1,101.00	1,101.00	Rustler		0.00		
1,691.00	1,691.00	Top Salt		0.00		
5,265.00	5,265.00	Delaware		0.00		
5,991.00	5,991.00	Cherry Canyon		0.00		
7,271.00	7,271.00	Brushy Canyon		0.00		
8,933.00	8,933.00	Bone Spring		0.00		
10,834.70	10,833.00	2nd BS		0.00		

Plan Annotations				
Measured Depth (usft)	Vertical Depth (usft)	Local Coordinates		Comment
		+N/-S (usft)	+E/-W (usft)	
10,685.04	10,685.04	0.00	0.00	KOP 10° DLS
11,585.04	11,258.00	572.94	-4.30	LP
15,670.92	11,258.00	4,658.70	-35.00	TD

DM100161771-2A



CONTINGENCY MODE

DEVON ENERGY

ARTESIA

S.E.N.M

13 3/8 X 9 5/8

QUOTE LAYOUT
F18648
REF: DM100161737
DM100151315

PRIVATE AND CONFIDENTIAL		REVISIONS		DESCRIPTION				DM100151315		
THIS DOCUMENT AND ALL THE INFORMATION CONTAINED HEREIN ARE THE CONFIDENTIAL AND EXCLUSIVE PROPERTY OF FMC TECHNOLOGIES AND MAY NOT BE REPRODUCED, USED, DISCLOSED, OR MADE PUBLIC IN ANY MANNER PRIOR TO EXPRESS WRITTEN AUTHORIZATION BY FMC TECHNOLOGIES. THIS DOCUMENT IS ACCEPTED BY RECIPIENT PURSUANT TO AGREEMENT TO THE FOREGOING, AND MUST BE RETURNED UPON DEMAND.		A	05-08-13		DRAWN BY					
		B	1-22-14		K. VU		05-08-13			
		C	5-13-14		DRAFTING REVIEW		Z. MARQUEZ		05-08-13	
MANUFACTURER AGREES THAT ARTICLES MADE IN ACCORDANCE WITH THIS DOCUMENT SHALL BE CONSIDERED FMC TECHNOLOGIES' DESIGN AND THAT IDENTICAL ARTICLES OR PARTS THEREOF SHALL NOT BE MANUFACTURED FOR THE USE OR SALE BY MANUFACTURER OR ANY OTHER PERSON WITHOUT THE PRIOR EXPRESS WRITTEN AUTHORIZATION BY FMC TECHNOLOGIES.					SURFACE WELLHEAD LAYOUT UNIHEAD, UH-1, SOW, DEVON ENERGY, ODESSA		DESIGN REVIEW			
							K. TAHA		05-08-13	DRAWING NUMBER DM100161771-2B
							APPROVED BY		R. HAMILTON	

FMC Technologies