

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-05684
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. E6706
7. Lease Name or Unit Agreement Name Fast Eumont Unit
8. Well Number 60
9. OGRID Number 192463
10. Pool name or Wildcat Eumont Yates TR Qn

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☐ Other Injection

2. Name of Operator
OXY USA WTP Limited Partnership

3. Address of Operator
P.O. Box 50250 Midland, TX 79710

4. Well Location
Unit Letter D : 660 feet from the South line and 1980 feet from the East line
Section 22 Township 19S Range 37E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3631'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

E-PERMITTING
P&A NR P.M.
INT TO P&A
CSNG
TA
P&A R
COMP
CHG Loc
RBDMS CHART

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

3/6/2015 MIRU PU, NDWH NU BOP

3/9/2015 RIH w/ tbg & tag CIBP @ 3777', circ hole w/ 10# MLF, pressure test csg to 500#, good test. Contact Mark Whitaker-NMOCD, approved waiving WOC-Tag on plugs. M&P 30sx CL C cmt @ 3777-3479', calc. PUH to 3061', M&P 40sx CL C cmt to 2666', calc. POOH. RIH & set pkr @ 1199'. RIH & perf @ 1530', attempt to EIR, pressure up to 1500#, no rate. Contact Mark Whitaker-NMOC approved spotting plugs. RIH to 1587', M&P 25sx CL C cmt, PUH, WOC.

3/10/2015 RIH & tag cmt @ 1355', PUH & set pkr @ 62', RIH & perf @ 425', EIR @ 1BPM @ 500#, M&P 60sx CL C cmt w/ 2% CaCl2, SI @ 150#, WOC. RIH & tag cmt @ 175', contact Mark Whitaker-NMOCD, PUH & perf @ 80', EIR @ 2BPM @ 100# w/ full returns. POOH w/ pkr, ND BOP, NUWH, M&P 30sx CL C cmt, circ to surface. RDPU

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David Stewart TITLE Sr. Regulatory Advisor DATE 3/11/15

Type or print name David Stewart E-mail address: david_stewart@oxy.com PHONE: 432-685-5717

For State Use Only

APPROVED BY: Malcolm Brown TITLE Dist. Supervisor DATE 3/16/2015

Conditions of Approval (if any):

..MAR 17 2015