		UNITED STATE	NTERIOR				OMB N	I APPROVED NO. 1004-013 :: July 31, 2010	5	
							5. Lease Serial No. NMNM94186			
Do not use this form for proposals to drillor to re-antenan abandoned well. Use form 3160-3(4) for such proposals.							6. If Indian, Allottee or Tribe Name			
SUBMIT IN TRIPLICATE - Other instructions on reverse side.							7. If Unit or CA/Agreement, Name and/or N			
							<ul> <li>8. Well Name and No. THISTLE UNIT 51H</li> <li>9. API Well No. 30-025-41896</li> <li>10. Field and Pool, or Exploratory TRIPLE X; BONE SPRING</li> </ul>			
3a. Address       3b. Phone No. (include area code)         333 WEST SHERIDAN AVENUE       Ph: 405-552-3622         OKLAHOMA CITY, OK 73102       Ph: 405-552-3622					10. T					
4. Location of Well	(Footage, Sec., T	C., R., M., or Survey Description	ı)	WAR 17	2013	11.	County or Parish,	and State		
Sec 28 T23S R	333E NWNW 20	DOFNL 430FWL		RECE	VED	L	EA COUNTY	COUNTY, I	M	
12.	CHECK APPI	ROPRIATE BOX(ES) TO	O INDICATE	NATURE OF I	NOTICI	E, REPOR	RT, OR OTHE	R DATA		
TYPE OF SUB	MISSION	•		TYPE O	F ACTIC	N				
□ Notice of Inter	ent	🗖 Acidize	🗖 Dee	pen	🗖 Pro	duction (S	tart/Resume)	U Water	Shut-O	
_		Alter Casing	🗖 Frac	Fracture Treat		lamation		Well Integrity		
🛛 Subsequent Re	•	Casing Repair	New Construction			Recomplete		Other Drilling Operation		
Final Abandonment Not	nment Notice	Change Plans	$\Box$ Plug and Abandon $\Box$ T		_	emporarity Abandon		Dinnig	operatio	
		Convert to Injection	🗖 Plug	Back	🗖 Wa	ter Dispos	al			
determined that the	e site is ready for fi	• •	,	- 1,		,	· · · · · · · · · · · · · · · · · · ·			
set @ 1437?. S cu ft/sk. Disp w/ lines @ 250/350	Set DVT @ 313 // 219 bbls FW. 500 psi, OK. PT	30. TD 17-1/2? hole @ 14 .7?. Lead w/ 660 sx ClC, Circ 258 sx cmt to surf. F csg to 1211 psi, OK. hole @ 5157? BIH w/ 12	yld 1.72 cu ft PT all BOPE @	/sk. Tail w/ 345 s ⊉ 250/3000 psi,	sx CIC, y OK. PT	rld 1.34 mud				
set @ 1437?. S cu ft/sk. Disp w/ lines @ 250/350 (9/23/14-9/27/1 1st lead w/ 450 ft/sk. Tail w/ 430 CIC, yld 1.34 cu OK. PT all rema	Set DVT @ 313 // 219 bbls FW. 500 psi, OK. PT 14) TD 12-1/4? 1 9 sx Econocem 10 sx CIC, yld 1. u ft/sk. Circ 7 bl aining valves, u umps @ 250/35	.7?. Lead w/ 660 sx CIC, Circ 258 sx cmt to surf. F csg to 1211 psi, OK. hole @ 5157?. RIH w/ 12 HLC, yld 1.87 cu ft/sk. 2n 33 cu ft/sk. Disp w/ 387.7 bls cmt to surf. PT annula upper and lower pipe rams 500 psi, OK. Held all tests	yld 1.72 cu ft PT all BOPE ( 7 jts 9-5/8? 4 d lead w/ 155 7 bbls FW fror rr, inside kill a s, blind rams for 10 min. P	/sk. Tail w/ 345 s 250/3000 psi, 0# HCK-55 BTC 0 sx Econocem n frac tanks. Puu nd HCR @ 250/ @ 250/5000 psi T csg to 1500 psi	sx CIC, y OK. PT Csg, se HLC, yi mp 210 3500 ps , OK. PT si, OK.	/ld 1.34 mud t @ 5157' d 1.87 cu sx i, surface	?.			
set @ 1437?. S cu ft/sk. Disp w. lines @ 250/350 (9/23/14-9/27/1 1st lead w/ 450 ft/sk. Tail w/ 430 CIC, yld 1.34 cu OK. PT all rema lines back to pu	Set DVT @ 313 // 219 bbls FW. 500 psi, OK. PT 14) TD 12-1/4? I 9 sx Econocem 10 sx CIC, yld 1. u ft/sk. Circ 7 bl aining valves, u umps @ 250/35	.7?. Lead w/ 660 sx CIC, Circ 258 sx cmt to surf. F csg to 1211 psi, OK. hole @ 5157?. RIH w/ 12 HLC, yld 1.87 cu ft/sk. 2n 33 cu ft/sk. Disp w/ 387.7 bls cmt to surf. PT annula ipper and lower pipe rams 00 psi, OK. Held all tests true and correct. Electronic Submission #2 For DEVON ENERG Committed to AFMSS f	yld 1.72 cu ft PT all BOPE ( 7 jts 9-5/8? 4 d lead w/ 155 bbls FW fror ur, inside kill a s, blind rams for 10 min. P	/sk. Tail w/ 345 s 250/3000 psi, 0# HCK-55 BTC 0 sx Econocem n frac tanks. Pui nd HCR @ 250/ @ 250/5000 psi, T csg to 1500 p 1 by the BLM Wel DN COMPAN, se by LINDA JIMEN	sx CIC, y OK. PT c csg, se HLC, yi mp 210 '3500 ps , OK. PT si, OK. Il Inform nt to the IEZ on 0	/ld 1.34 mud t @ 5157' d 1.87 cu sx i, surface ation Syst Hobbs T 3/12/2015	°. em opted for	OR RFI		
set @ 1437?. S cu ft/sk. Disp w. lines @ 250/35( (9/23/14-9/27/1 1st lead w/ 450 ft/sk. Tail w/ 43( CIC, yld 1.34 cu OK. PT all rema lines back to pu	Set DVT @ 313 // 219 bbls FW. 500 psi, OK. PT 14) TD 12-1/4? I 9 sx Econocem 10 sx CIC, yld 1. u ft/sk. Circ 7 bl aining valves, u umps @ 250/35	.7?. Lead w/ 660 sx CIC, Circ 258 sx cmt to surf. F csg to 1211 psi, OK. hole @ 5157?. RIH w/ 12 HLC, yld 1.87 cu ft/sk. 2n 33 cu ft/sk. Disp w/ 387.7 bls cmt to surf. PT annula ipper and lower pipe rams 00 psi, OK. Held all tests true and correct. Electronic Submission #2 For DEVON ENERG Committed to AFMSS f	yld 1.72 cu ft PT all BOPE ( 7 jts 9-5/8? 4 d lead w/ 155 bbls FW fror ur, inside kill a s, blind rams for 10 min. P	/sk. Tail w/ 345 s 250/3000 psi, 0# HCK-55 BTC 0 sx Econocem n frac tanks. Pui nd HCR @ 250/ @ 250/5000 psi, T csg to 1500 p 1 by the BLM Wel DN COMPAN, se by LINDA JIMEN	sx CIC, y OK. PT c csg, se HLC, yi mp 210 '3500 ps , OK. PT si, OK. Il Inform nt to the IEZ on 0	t @ 5157 d 1.87 cu sx i, surface	°. em opted for	OR REI	COR	
set @ 1437?. S cu ft/sk. Disp w. lines @ 250/350 (9/23/14-9/27/1 1st lead w/ 450 ft/sk. Tail w/ 430 CIC, yld 1.34 cu OK. PT all rema lines back to pu	Set DVT @ 313 // 219 bbls FW. 500 psi, OK. PT 14) TD 12-1/4? I 9 sx Econocem 10 sx CIC, yld 1. u ft/sk. Circ 7 bl aining valves, u umps @ 250/35	.7?. Lead w/ 660 sx CIC, Circ 258 sx cmt to surf. F csg to 1211 psi, OK. hole @ 5157?. RIH w/ 12 HLC, yld 1.87 cu ft/sk. 2n 33 cu ft/sk. Disp w/ 387.7 bls cmt to surf. PT annula ipper and lower pipe rams 00 psi, OK. Held all tests true and correct. Electronic Submission #2 For DEVON ENERG Committed to AFMSS f 10RAVEC	yld 1.72 cu ft PT all BOPE ( 7 jts 9-5/8? 4 d lead w/ 155 bbls FW fror ur, inside kill a s, blind rams for 10 min. P	/sk. Tail w/ 345 s 250/3000 psi, 0# HCK-55 BTC 0 sx Econocem n frac tanks. Pui nd HCR @ 250/ @ 250/5000 psi, T csg to 1500 p 1 by the BLM Wel DN COMPAN, se by LINDA JIMEN	sx CIC, y OK. PT Csg, se HLC, yi mp 210 (3500 ps , OK. PT si, OK. II Inform It to the IEZ on 0 ATORY	/ld 1.34 mud t @ 5157' d 1.87 cu sx i, surface ation Syst Hobbs T 3/12/2015	°. em opted for	2.00%5		
set @ 1437?. S cu ft/sk. Disp w. lines @ 250/350 (9/23/14-9/27/1 1st lead w/ 450 ft/sk. Tail w/ 430 CIC, yld 1.34 cu OK. PT all rema lines back to pu 14. I hereby certify th Name(Printed/Type	Set DVT @ 313 // 219 bbls FW. 500 psi, OK. PT (4) TD 12-1/4? 0 sx Econocem 10 sx CIC, yld 1. 10 ft/sk. Circ 7 bl 11 aining valves, u 12 umps @ 250/35 12 mat the foregoing is 12 mat the foregoing is 13 mat the foregoing is 14 mat the foregoing is	.7?. Lead w/ 660 sx CIC, Circ 258 sx cmt to surf. F csg to 1211 psi, OK. hole @ 5157?. RIH w/ 12 HLC, yld 1.87 cu ft/sk. 2n 33 cu ft/sk. Disp w/ 387.7 bls cmt to surf. PT annula ipper and lower pipe rams 00 psi, OK. Held all tests true and correct. Electronic Submission #2 For DEVON ENERG Committed to AFMSS f 10RAVEC	yld 1.72 cu ft PT all BOPE ( d lead w/ 155 bbls FW fror ur, inside kill a s, blind rams for 10 min. P 272403 verifie Y PRODUCTI or processing	/sk. Tail w/ 345 s 250/3000 psi, 0# HCK-55 BTC 0 sx Econocem n frac tanks. Pui nd HCR @ 250/ @ 250/5000 psi, T csg to 1500 psi T csg to 1500 psi D cOMPAN, se by LINDA JIMEN Title REGUL Date 10/21/2	sx CIC, y OK. PT csg, se HLC, yi mp 210 (3500 ps , OK. PT si, OK. II Informant si, OK.	rld 1.34 mud t @ 5157' d 1.87 cu sx i, surface tion Syst 3/12/2015[ ANALYS	em OPTEDF	OR RE(		
set @ 1437?. S cu ft/sk. Disp w, lines @ 250/350 (9/23/14-9/27/1 1st lead w/ 450 ft/sk. Tail w/ 430 CIC, yld 1.34 cu OK. PT all rema lines back to pu 14. I hereby certify th Name(Printed/Type	Set DVT @ 313 // 219 bbls FW. 500 psi, OK. PT (4) TD 12-1/4? 0 sx Econocem 10 sx CIC, yld 1. 10 ft/sk. Circ 7 bl 11 aining valves, u 12 umps @ 250/35 12 mat the foregoing is 12 mat the foregoing is 13 mat the foregoing is 14 mat the foregoing is	.7?. Lead w/ 660 sx CIC, Circ 258 sx cmt to surf. F csg to 1211 psi, OK. hole @ 5157?. RIH w/ 12 HLC, yld 1.87 cu ft/sk. 2n 33 cu ft/sk. Disp w/ 387.7 bls cmt to surf. PT annula upper and lower pipe rams 500 psi, OK. Held all tests true and correct. Electronic Submission #2 For DEVON ENERG Committed to AFMSS f 10RAVEC	yld 1.72 cu ft PT all BOPE ( d lead w/ 155 bbls FW fror ur, inside kill a s, blind rams for 10 min. P 272403 verifie Y PRODUCTI or processing	/sk. Tail w/ 345 s 250/3000 psi, 0# HCK-55 BTC 0 sx Econocem n frac tanks. Pui nd HCR @ 250/ @ 250/5000 psi, T csg to 1500 psi T csg to 1500 psi D cOMPAN, se by LINDA JIMEN Title REGUL Date 10/21/2	sx CIC, y OK. PT csg, se HLC, yi mp 210 (3500 ps , OK. PT si, OK. II Informant si, OK.	t @ 5157' d 1.87 cu sx i, surface	em OPTEDF	- <u>2015</u>		
Set @ 1437?. S cu ft/sk. Disp w, lines @ 250/350 (9/23/14-9/27/1 1 st lead w/ 450 ft/sk. Tail w/ 430 CIC, yld 1.34 cL OK. PT all rema lines back to pu 14. I hereby certify th Name(Printed/Type Signature	Set DVT @ 313 // 219 bbls FW. 500 psi, OK. PT (4) TD 12-1/4? ) sx Econocem 10 sx ClC, yld 1. u ft/sk. Circ 7 bl aining valves, u umps @ 250/35 mat the foregoing is ped) MEGAN M (Electronic S	.7?. Lead w/ 660 sx CIC, Circ 258 sx cmt to surf. F csg to 1211 psi, OK. hole @ 5157?. RIH w/ 12 HLC, yld 1.87 cu ft/sk. 2n 33 cu ft/sk. Disp w/ 387.7 bls cmt to surf. PT annula ipper and lower pipe rams 00 psi, OK. Held all tests true and correct. Electronic Submission #2 For DEVON ENERG Committed to AFMSS f IORAVEC	yld 1.72 cu ft PT all BOPE ( 7 jts 9-5/8? 4 d lead w/ 155 bbls FW fror ur, inside kill a s, blind rams for 10 min. P 272403 verifie Y PRODUCTI or processing	/sk. Tail w/ 345 s 250/3000 psi, 0# HCK-55 BTC 0 sx Econocem n frac tanks. Pui nd HCR @ 250/ @ 250/5000 psi, T csg to 1500 psi T csg to 1500 psi D cOMPAN, se by LINDA JIMEN Title REGUL Date 10/21/2	sx CIC, y OK. PT csg, se HLC, yi mp 210 (3500 ps , OK. PT si, OK. II Informant si, OK.	t @ 5157 d 1.34 mud t @ 5157 d 1.87 cu sx i, surface ation Syste Hobbs T ANALYS E USE BURE	em OPTEDF MAR 1 EAU OF LAND	2015 2015 MANA Däte/		
Set @ 1437?. S cu ft/sk. Disp w, lines @ 250/350 (9/23/14-9/27/1 1st lead w/ 450 ft/sk. Tail w/ 430 CIC, yld 1.34 cL OK. PT all rema lines back to pu 14. I hereby certify th Name(Printed/Type Signature	Set DVT @ 313 // 219 bbls FW. i00 psi, OK. PT 14) TD 12-1/4? 1 ) sx Econocem 10 sx CIC, yld 1. u ft/sk. Circ 7 bl aining valves, u umps @ 250/35 hat the foregoing is bed) MEGAN M (Electronic S , if any, are attached t holds legal or equ	.7?. Lead w/ 660 sx CIC, Circ 258 sx cmt to surf. F csg to 1211 psi, OK. hole @ 5157?. RIH w/ 12 HLC, yld 1.87 cu ft/sk. 2n 33 cu ft/sk. Disp w/ 387.7 bls cmt to surf. PT annula upper and lower pipe rams 500 psi, OK. Held all tests true and correct. Electronic Submission #2 For DEVON ENERG Committed to AFMSS f 10RAVEC	yld 1.72 cu ft PT all BOPE ( 7 jts 9-5/8? 4 d lead w/ 155 bbls FW fror ur, inside kill a s, blind rams for 10 min. P 272403 verifie Y PRODUCTI or processing DR FEDERA	/sk. Tail w/ 345 s 250/3000 psi, 0# HCK-55 BTC 0 sx Econocem n frac tanks. Pu nd HCR @ 250/ @ 250/5000 psi, T csg to 1500 p 250/5000 psi, T csg to 1500 p by the BLM Well DN COMPAN, se by LINDA JIMEN Title REGUL Date 10/21/2 L OR STATE	sx CIC, y OK. PT csg, se HLC, yi mp 210 (3500 ps , OK. PT si, OK. II Informant si, OK.	t @ 5157 d 1.34 mud t @ 5157 d 1.87 cu sx i, surface ation Syste Hobbs T ANALYS E USE BURE	em OPTEDF	2015 2015 MANA Däte/		

gh/

## Additional data for EC transaction #272403 that would not fit on the form

## 32. Additional remarks, continued

(10/7/14-10/12/14) TD 8-3/4? hole @ 15636?. RIH w/ 114 jts 5-1/2? 17# HCP-110 BTC csg, followed by 247 jts 7? 29# HCP-110 BTC csg, set @ 15628?. Lead w/ 650 sx Tuned Light cmt, yld 3.21 cu ft/sk. Tail w/ 1100 sx Versacem cmt, yld 1.20 cu ft/sk. Disp w/ 509 bbls FW. No cmt to surf. RR @ 06:00.

:

. . ..