

Submit 1 Copy To Appropriate District Office
District I – (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II – (575) 748-1283
811 S. First St., Artesia, NM 88210
District III – (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV – (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

HOBBSOCD

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

APR 09 2015

WELL API NO. 30-025-36369
5. Indicate Type of Lease STATE FEE X
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name CAUDILL 7
8. Well Number 1
9. OGRID Number 4323
10. Pool name or Wildcat LOVINGTON UPPER PENN NE

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well X Gas Well Other

2. Name of Operator
CHEVRON MIDCONTINENT, L. P.

3. Address of Operator
1500 SMITH RD. MIDLAND, TX. 79705

4. Well Location DATUM Y- LAT 32.93299 X-LONG -103.28267
Unit Letter P : 1310 feet from the SOUTH line and 500 feet from the EAST line
Section 7 Township 16-S Range 37-E NMPM County LEA

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3,844' DR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

E-PERMITTING <SWD INJECTION>
CONVERSION RBDMS
RETURN TO TA
CSNG CHG LOC
INT TO PA P&A NR P&A R

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A X
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 13 3/8" 48# @ 440' TOC SURF, 8 5/8" 32# @ 4,417' TOC @ SURF, 5 1/2" 17# @ 11,675' TOC @ 10,109'. TD 11,675', PB 10,565' CIBP W/ 35' CMT. ON TOP. PERFS 11,446'-11,461' W/ CIBP @ 11,400' W/ 2 SX ON TOP, 10,680'-10,686' W/ CIBP @ 10,600' W/ 35' CMT. ON TOP. RAN CBL 10,550'-3,000' NO CMT BEHIND CASING.

ON MARCH 23, 2015 MOVE IN RIG & CMT EQUIPMENT, MARK WHITAKER OK SETTING BOTTOM PLUG 25 SX & TEST CASING.

03 / 24 / 15 RIH & TAGGED UP @ 10,585', MIX & PUMP 25 SX CLASS "H" CEMENT FROM 10,585'-10,335', WOC, TAG CMT. @ 10,414'. TEST 5 1/2" CSG. @ 750# HELD 15 MIN. TEST W/ NO LOSS.

03 / 25 / 15 PERFORATED 5 1/2" CSG. @ 9,720', UNABLE EST. INJ. RATE, OK BY MARK WHITAKER, SPOT 50 SX CLASS "H" FROM 9,797'-9,350' WITNESSED BY MARK WHITAKER. TAG CMT. @ 9,410'.

03 / 26 / 15 PERFORATED 5 1/2" CSG. @ 6,480' EST. INJ. RATE, MIX & SQZ 60 SX CL."C" FROM 6,480'-6,110', WOC TAG CMT. @ 6,110'

03 / 27 / 15 PERFORATED 5 1/2" CSG, @ 4,467', EST. CIRCULATION, MIX & SQZ 90 SX CLASS "C" FROM 4,467'-4,016', WOC TAG CMT. @ 4,016'. PERFORATED 5 1/2" CSG. @ 3,300', EST. CIRCULATION TO SURFACE, PAUL W/ OCD OK TO CIR. CEMENT, MIX & CIRCULATE 854 SX CLASS "C" FROM 3,300'-SURFACE. CUT ALL CASING & ANCHORS & REMOVED 3' BELOW GRADE. WELD ON DRY HOLE MARKER. CLEAN LOCATION.

CEMENT PLUGS CLASS "H" & CLASS "C" & BRINE GEL W/ CLOSED LOOP SYSTEM USED.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Monty L. McCarver TITLE Agent for Chevron U.S.A. DATE 03 / 31 / 15
Type or print name Monty L. McCarver E-mail address: monty.mccarver@nabors.com PHONE: 281-775-3432
For State Use Only APPROVED BY: Mary Brown TITLE Dist. Supervisor DATE 4/9/2015
Conditions of Approval (if any):

APR 14 2015