Form 3160-5 (August 2007)

UNITED STATES DEPARTMENT OF THE INTERIOR **BUREAU OF LAND MANAGEMENT**

NMOCD

FORM APPROVED

OMB No. 1004-0137 Expires: July 31, 2010

Hobbs Lease Serial No. NMNM-124658

SUNDRY N	6. If Indian, Allottee or	Tribe Name			
Do not use this abandoned well. U	form proposals to drill o Jse Form 3160-3 (APD) fo	or to re-enter an or such proposals _a			
	7. If Unit of CA/Agree	ment. Name and/or No.			
SUBMIT IN TRIPLICATE - Other instructions on page 2. 1. Type of Well			ì	internet, reality and reality	
Oil Well Gas W	ell Other	APR 2 3 20	8. Well Name and No. Casper Federal #1		
2. Name of Operator Mack Energy Corporation		DECEIVE	9. API Well No. 30-005-21140		
		ne No. (include area code)	10. Field and Pool or E	10. Field and Pool or Exploratory Area	
		748-1288	San Andres		
4. Location of Well (Footage, Sec., T,R,M, or Survey Description)			11. Country or Parish,	State	
346 FNL & 1647 FWL, Sec. 21 T14S R30E			Chaves, NM		
12. CHEC	K THE APPROPRIATE BOX(ES) T	O INDICATE NATURE OF	NOTICE, REPORT OR OTHE	R DATA	
TYPE OF SUBMISSION		TYPE O	F ACTION		
Notice of Intent	Acidize Alter Casing	Deepen Fracture Treat	Production (Start/Resume) Reclamation	Water Shut-Off Well Integrity	
Subsequent Report	Casing Repair	New Construction	Recomplete	Other	
	Change Plans	Plug and Abandon	Temporarily Abandon		
Final Abandonment Notice 13. Describe Proposed or Completed C	Convert to Injection	Plug Back	Water Disposal		
testing has been completed. Final A determined that the site is ready fo 11/11/2013 MIRU LCH Rig 81. F 11/15/2013 Finish drilling thru sec 11/18/2013 RU E&P wire line. RI surface. Set a CIBP at 4150' w/35 1/SPF 5 settings, 5 holes, 0.42" ho 11/19/2013 Acidized w/750 gals I cap. Ran a CBL log from 3340' to 12/12/2013 Rig up E&P and shot 312/13/2013 Acidized w/43 Bbls of 12/16/2013 Made 1st swab run had move. Evaluate for frac.	Picked up swivel, 4 3/4 bit, beg cond plug. RIH to 4929'. Didr IH with PDC log and logged fit cement cap. Loaded casing a le. 5% acid. Swabbed well, all w 2000'. Bond looks good. Per 3rd set of perfs. 3113-3262' 2/ 15% HCL acid. Flowback an	gin drilling. In't find 3rd plug at 3453 from 4200' to 2000'. RIF and test to 4100# for 30 frater. POH with pkr. Rif forate 2nd set at 3272.5 SPF 0.42" 33 settings 6 and begin swabbing no oi	'- 3799'. Circulate hole of with casing inspection mins. Held good. Perform WE&P wireline. Set CII '-3281' 1/SPF 4 settings of holes.	clean. POH. log and ran it from 4200' to rate 1st set at 3379'-3391' BP at 3340' w/35' cement 4 holes.	
14. I hereby certify that the foregoing is	true and correct Name (Printed/Tuned)				
Jerry W. Sherrell	and contest. Maine it timeartypear	Title Production (Clerk		
Signature Peny W. Shendl		Date 4/13/15	Date 4/13/15		
ACCEPTED	FOR RECORD	FEDERAL OR STATE	OFFICE USE		
Approved by /S/ DAVID	R. GLASS	Title	ln.	ate	
Conditions of approval, if any, are attache that the applicant holds legal or equitable entitle the applicant to conduct operations	title to those rights in the subject lease we thereon ASS	ant or certify thich would Office	Roswell Field		
Title 18 U.S.C. Section 1004 and Title 43 fictitious or fraudulent statements or representations.	U.S.C. Section 1212, make it a crime for Semations as to any matter within its jur	or my person knowingly and wil	Ifully to make in the artment	or agency of the United States any false,	