

Submit 1 Copy To Appropriate District
Office

District I - (575) 393-6161

1625 N. French Dr., Hobbs, NM 88240

District II - (575) 748-1283

811 S. First St., Artesia, NM 88210

District III - (505) 334-6178

1000 Rio Brazos Rd., Aztec, NM 87410

District IV - (505) 476-3460

1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico

Energy, Minerals and Natural Resources

Form C-103

Revised July 18, 2013

WELL API NO.

30-025-42491

5. Indicate Type of Lease

STATE ☒ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name

Nautilus 16 State Com

8. Well Number 201H

9. OGRID Number

7377

10. Pool name or Wildcat

Red Hills; Upper BS Shale

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A
DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH
PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator

EOG Resources, Inc.

3. Address of Operator

P.O. Box 2267 Midland, TX 79702

4. Well Location

Unit Letter A 230 feet from the North line and 850 feet from the East line

Section 16 Township 26S Range 34E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)

3316' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐

DOWNHOLE COMMINGLE ☐

CLOSED-LOOP SYSTEM ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS ☒ P AND A ☐

CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

4/17/15 Spud 12-1/4" hole.

Ran 21 jts 9-5/8", 40#, J55 LTC casing set at 881'.

Cement lead w/ 250 sx Class C, 13.5 ppg, 1.75 CFS yield;

tail w/ 150 sx Class C, 14.8 ppg, 1.34 CFS yield.

Circulated 89 sx cement to surface. WOC 9.5 hrs

Tested casing to 1500 psi for 30 minutes. Test good.


Resumed drilling 8-3/4" hole.

Spud Date: 4/17/2015

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE



TITLE

Regulatory Analyst

DATE

04/16/2015

Type or print name

Stan Wagner


E-mail address:

PHONE:

432-686-3689

For State Use Only

APPROVED BY:



TITLE

Petroleum Engineer

DATE

05/14/15

Conditions of Approval (if any):

MAY 14 2015

NAB