Submit 1 Copy To Appropriate District Office	State of New Mexico	Form C-103
District I - (575) 393-6161	Energy, Minerals and Natural Reso	urces Revised July 18, 2013
1625 N. French Dr., Hobbs, NM 88240 District II – (575) 748-1283		WELL API NO. 30-025-27825
811 S. First St., Artesia, NM 88210	OIL CONSERVATION DIVISI	5. Indicate Type of Lease
District III – (505) 334-6178 1000 Rio Brazos Rd., Aztec, NM 87410	1220 South St. Francis Dr.	STATE FEE X
District IV - (505) 476-3460	Santa Fe, NM 87505	6. State Oil & Gas Lease No.
1220 S. St. Francis Dr., Santa Fe, NM 87505		
TOM V SOMUS	TICES AND REPORTS ON WELLS	7. Lease Name or Unit Agreement Name
DIFFERENT RESERVOIR. USE "APPL	ICATION FOR PERMIT" (FORM C-101) FOR SLICH	Jameson
PROPOSALS.)  1. Type of Well: Oil Well	DSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DESALS TO DRILL OR TO DEEPEN OR PLUG BACK TO DEEPEN OR TO DEEPEN OR PLUG BACK TO DEEPEN DEEP	OCD / 8. Well Number 1
2. Name of Operator	Oas well Other	
State of New Mexico forme	rly Canyon E&P Company APR 23	2015
3. Address of Operator		10. Pool name or Wildcat
	bbs, NM 88240 <b>RECEIVE</b>	Jalmat
4. Well Location		
		e and 2310 feet from the West line
Section 15		SE NMPM County Lea
	11. Elevation (Show whether DR, RKB, RT	, GR, etc.)
12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data		
NOTICE OF II	NTENTION TO:   E-	PERMITTING <swdinjection></swdinjection>
PERFORM REMEDIAL WORK	1	ONVERSION RBDMS
TEMPORARILY ABANDON	CHANGE PLANS 🔲 🧯 🕟	ETURN TO TA
PULL OR ALTER CASING   MULTIPLE COMPL   CSNG   CHG LOC		
DOWNHOLE COMMINGLE	IN	T TO PAR P&A NR P&A R
CLOSED-LOOP SYSTEM  OTHER:	I □ OTHER	
13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date		
of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of		
proposed completion or recompletion.		
1. MIRU plugging equipment. POOH with production equipment.		
	Circulate hole with mud laden fluid. Pressu	re test casing to 500 psi
3. Spot 25 sx cement of		to took odding to ood poi.
4. POOH to 2900'. Spot 25 sx cement. (Base of salt)		
•	Squeeze with 30 sx cement. WOC and tag	(Shoe and top of salt plug)
<ol> <li>Perforate at 300'. Pump sufficient cement to circulate cement to surface inside/outside of 4 1/2" casing.</li> <li>Cut off wellhead 4' below ground level and install P&amp;A marker. Verify cement to surface on all strings.</li> </ol>		
Cut off anchors.		
out on anonoro.		
Spud Date:	Rig Release Date:	
hereby certify that the information above is true and complete to the best of my knowledge and belief.		
$\mathbf{A}$		
SIGNATURE Washin	TITLE Compliance	Officer DATE
Type or print name Mark Whital	Cer E-mail address:	PHONE:
For State Use Only		
APPROVED BY: Maley 4 23/2015		
Conditions of Approval (if any):		

## Canyon E&P Company Jameson No. 1 30-025-27825

8 5/8" @ 1445' w/ 500 sx. Circ cmt

4 1/2" @ 3649' w/ 300 sx.

Open hole 3649-3666'

TD 3666'