

HOBBS OGD
MAY 26 2015
OCD Hobbs

Form 3160-5
(March 2012)

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

RECEIVED

FORM APPROVED
OMB No. 1004-0137
Expires: October 31, 2014

SUNDRY NOTICES AND REPORTS ON WELLS
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

5. Lease Serial No.
NMNM92199

6. If Indian, Allottee or Tribe Name

SUBMIT IN TRIPLICATE - Other instructions on page 2.

7. If Unit of CA/Agreement, Name and/or No.

1. Type of Well
 Oil Well Gas Well Other

8. Well Name and No.
Broadcaster 29 Federal 3H

2. Name of Operator
Endurance Resources LLC

9. API Well No.
30-025-41909

3a. Address
203 West Wall Street Suite 1000 Midland TX 79701

3b. Phone No. (include area code)
432-242-4680

10. Field and Pool or Exploratory Area
Antelope Ridge Bone Spring West

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)
330 FNL & 1980 FEL UL B Sec. 29 T23S R34E

11. County or Parish, State
Lea County, New Mexico

12. CHECK THE APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input type="checkbox"/> Other _____
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input checked="" type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation: Clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recomplete horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports must be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 must be filed once testing has been completed. Final Abandonment Notices must be filed only after all requirements, including reclamation, have been completed and the operator has determined that the site is ready for final inspection.)

Water is being produced from the Bone Spring formation and is producing approximately 294.52 BWPD. This produced water is being transferred via flowline to the Federal 19 No. 1 SWD (SWD-1067) API No. 30-025-24676 located in NE/4 Sec. 19-T23S-R34E, Lea County, New Mexico.

See attached Administrative Order SWD-1067. **Water Analysis.**

ACCEPTED FOR RECORD

MAY 19 2015
[Signature]
BUREAU OF LAND MANAGEMENT
CARLSBAD FIELD OFFICE

14. I hereby certify that the foregoing is true and correct. Name (Printed/Typed)

M. A. Sirgo, III

Title Engineer

Signature *[Signature]*

Date 03/12/2015

THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

MAY 27 2015

[Handwritten mark]



NEW MEXICO ENERGY, MINERALS and NATURAL RESOURCES DEPARTMENT

BILL RICHARDSON

Governor

Joanna Prukop

Cabinet Secretary

Mark E. Fesmire, P.E.

Director

Oil Conservation Division

ADMINISTRATIVE ORDER SWD-1067

APPLICATION OF RAY WESTALL FOR PRODUCED WATER DISPOSAL, LEA COUNTY, NEW MEXICO

ADMINISTRATIVE ORDER OF THE OIL CONSERVATION DIVISION

Under the provisions of Rule 701(B), RAY WESTALL made application to the New Mexico Oil Conservation Division for permission to utilize for produced water disposal its Federal 19 Well No. 1 (API No. 30-025-24676) located 660 feet from the North line and 660 feet from the East line of Section 19, Township 23 South, Range 34 East, NMPM, Lea County, New Mexico.

THE DIVISION DIRECTOR FINDS THAT:

- (1) The application has been duly filed under the provisions of Rule 701(B) of the Division Rules and Regulations;
- (2) Satisfactory information has been provided that all offset operators and surface owners have been duly notified;
- (3) The applicant has presented satisfactory evidence that all requirements prescribed in Rule 701 will be met; and
- (4) No objections have been received within the waiting period prescribed by said rule.

IT IS THEREFORE ORDERED THAT:

The applicant is hereby authorized to utilize its Federal 19 Well No. 1 (API No. 30-025-24676) located 660 feet from the North line and 660 feet from the East line of Section 19, Township 23 South, Range 34 East, NMPM, Lea County, New Mexico, in such manner as to permit the injection of produced water for disposal purposes into the Cherry Canyon member of the Delaware Mountain Group through perforations from 6670 feet to 6883 feet and through plastic-lined tubing set with a packer located within 100 feet of the top of the injection interval.

IT IS FURTHER ORDERED THAT:

The operator shall take all steps necessary to ensure that the injected water enters only the proposed injection interval and is not permitted to escape to other formations or onto the surface.

As preparation for injection, the operator shall plug back the well with cement and cast iron bridge plug to within 200 feet of the bottom permitted injection interval.

The casing-tubing annulus shall be loaded with an inert fluid and equipped with a pressure gauge or an approved leak detection device in order to determine leakage in the casing, tubing, or packer.

After installing injection tubing, the casing shall be pressure tested from the surface to the packer setting depth to assure casing integrity.

The wellhead injection pressure on the well shall be limited to **no more than 1334 psi**. In addition, the injection well or system shall be equipped with a pressure limiting device in workable condition which shall, at all times, limit surface injection pressure to the maximum allowable pressure for this well.

The Director of the Division may authorize an increase in injection pressure upon a proper showing by the operator of said well that such higher pressure will not result in migration of the injected fluid from the injection formation. Such proper showing shall consist of a valid step-rate test run in accordance with and acceptable to this office.

The operator shall notify the supervisor of the Hobbs district office of the Division of the date and time of the installation of disposal equipment and of any mechanical integrity test so that the same may be inspected and witnessed.

The operator shall immediately notify the supervisor of the Hobbs district office of the Division of the failure of the tubing, casing, or packer in said well and shall take such steps as may be timely and necessary to correct such failure or leakage.


PROVIDED FURTHER THAT, jurisdiction is retained by the Division for the entry of such further orders as may be necessary for the prevention of waste and/or protection of correlative rights or upon failure of the operator to conduct operations (1) to protect fresh water or (2) consistent with the requirements in this order, whereupon the Division may, after notice and hearing, terminate the injection authority granted herein.

The operator shall provide written notice of the date of commencement of injection to the Hobbs district office of the Division.

The operator shall submit monthly reports of the disposal operations on Division Form C-115, in accordance with Rule Nos. 706 and 1120 of the Division Rules and Regulations.

The injection authority granted herein shall terminate one year after the effective date of this order if the operator has not commenced injection operations into the subject well, provided however, the Division, upon written request by the operator, may grant an extension thereof for good cause shown.

Approved at Santa Fe, New Mexico, on February 6, 2007.



MARK E. FESMIRE, P.E.
Director

MEF/wvjj

cc: Oil Conservation Division – Hobbs
Bureau of Land Management – Carlsbad



Permian Basin Area Laboratory
2101 S Market Street
Bldg. B

Report Date: 3/20/2015

Complete Water Analysis Report SSP v.8

Customer:	ENDURANCE RESOURCES LLC	Sample Point Name	Broadcaster 29 Federal 3
District:	New Mexico	Sample ID:	201501009582
Sales Rep:	Wayne C Peterson	Sample Date:	2/25/2015
Lease:	DELEWARE BASIN	Log Out Date:	3/20/2015
Site Type:	Well Sites	Analyst:	Samuel Newman
Sample Point Description:	HEATER TREATER OUTLET		

ENDURANCE RESOURCES LLC, DELEWARE BASIN, Broadcaster 29 Federal 3

Field Data		Analysis of Sample					
		Anions:		Cations:			
		mg/L	meq/L	mg/L	meq/L		
Initial Temperature (°F):	250	Chloride (Cl ⁻):	34480.0	972.6	Sodium (Na ⁺):	20490.2	891.7
Final Temperature (°F):	80	Sulfate (SO ₄ ²⁻):	2887.8	60.1	Potassium (K ⁺):	437.1	11.2
Initial Pressure (psi):	100	Borate (H ₃ BO ₃):	406.8	6.6	Magnesium (Mg ²⁺):	237.3	19.5
Final Pressure (psi):	15	Fluoride (F ⁻):	ND		Calcium (Ca ²⁺):	1758.6	87.8
		Bromide (Br ⁻):	ND		Strontium (Sr ²⁺):	61.5	1.4
pH:		Nitrite (NO ₂ ⁻):	ND		Barium (Ba ²⁺):	0.0	0.0
pH at time of sampling:	7.0	Nitrate (NO ₃ ⁻):	ND		Iron (Fe ²⁺):	0.0	0.0
		Phosphate (PO ₄ ³⁻):	ND		Manganese (Mn ²⁺):	0.5	0.0
		Silica (SiO ₂):	ND		Lead (Pb ²⁺):	ND	
					Zinc (Zn ²⁺):	0.0	0.0
					Aluminum (Al ³⁺):	ND	
					Chromium (Cr ³⁺):	ND	
					Cobalt (Co ²⁺):	ND	
					Copper (Cu ²⁺):	ND	
					Molybdenum (Mo ²⁺):	ND	
					Nickel (Ni ²⁺):	ND	
					Tin (Sn ²⁺):	ND	
					Titanium (Ti ³⁺):	ND	
					Vanadium (V ²⁺):	ND	
					Zirconium (Zr ²⁺):	ND	
					Total Hardness:	5444	N/A
Alkalinity by Titration:	mg/L meq/L	Organic Acids:		mg/L meq/L			
Bicarbonate (HCO ₃ ⁻):	488.0 8.0	Formic Acid:	ND				
Carbonate (CO ₃ ²⁻):	ND	Acetic Acid:	ND				
Hydroxide (OH ⁻):	ND	Propionic Acid:	ND				
aqueous CO ₂ (ppm):	400.0	Butyric Acid:	ND				
aqueous H ₂ S (ppm):	51.0	Valeric Acid:	ND				
aqueous O ₂ (ppb):	ND						
Calculated TDS (mg/L):	61248	Anion/Cation Ratio:	1.04				ND = Not Determined
Density/Specific Gravity (g/cm ³):	1.0388						
Measured Density/Specific Gravity	1.0449						
Conductivity (mmhos):	ND						
Resistivity:	ND						
MCF/D:	No Data						
BOPD:	No Data						
BWPD:	No Data						

Conditions		Barite (BaSO ₄)		Calcite (CaCO ₃)		Gypsum (CaSO ₄ ·2H ₂ O)		Anhydrite (CaSO ₄)	
Temp	Press.	Index	Amt (ptb)	Index	Amt (ptb)	Index	Amt (ptb)	Index	Amt (ptb)
80°F	15 psi	0.000	0.000	0.87	74.908	-0.09	0.000	-0.31	0.000
99°F	24 psi	0.000	0.000	0.90	77.303	-0.08	0.000	-0.22	0.000
118°F	34 psi	0.000	0.000	0.97	81.128	-0.07	0.000	-0.13	0.000
137°F	43 psi	0.000	0.000	1.04	85.283	-0.06	0.000	-0.03	0.000
156°F	53 psi	0.000	0.000	1.13	89.439	-0.04	0.000	0.08	154.033
174°F	62 psi	0.000	0.000	1.22	93.482	-0.02	0.000	0.20	345.206
193°F	72 psi	0.000	0.000	1.31	97.370	0.00	0.000	0.32	517.579
212°F	81 psi	0.000	0.000	1.42	101.318	0.02	45.824	0.44	670.132
231°F	91 psi	0.000	0.000	1.53	105.115	0.04	97.957	0.57	802.853
250°F	100 psi	0.000	0.000	1.64	108.675	0.06	147.072	0.69	916.484

Conditions		Celestite (SrSO ₄)		Halite (NaCl)		Iron Sulfide (FeS)		Iron Carbonate (FeCO ₃)	
Temp	Press.	Index	Amt (ptb)	Index	Amt (ptb)	Index	Amt (ptb)	Index	Amt (ptb)
80°F	15 psi	0.14	12.516	-2.00	0.000	0	0.000		0.000
99°F	24 psi	0.15	12.920	-2.02	0.000	0	0.000		0.000
118°F	34 psi	0.16	13.666	-2.03	0.000	0	0.000		0.000
137°F	43 psi	0.18	14.794	-2.04	0.000	0	0.000		0.000
156°F	53 psi	0.20	16.294	-2.04	0.000	0	0.000		0.000
174°F	62 psi	0.23	18.123	-2.05	0.000	0	0.000		0.000
193°F	72 psi	0.26	20.204	-2.05	0.000	0	0.000		0.000
212°F	81 psi	0.30	22.445	-2.04	0.000	0	0.000		0.000
231°F	91 psi	0.35	24.751	-2.04	0.000	0	0.000		0.000
250°F	100 psi	0.40	27.029	-2.03	0.000	0	0.000		0.000

Note 1: When assessing the severity of the scale problem, both the saturation index (SI) and amount of scale must be considered
 Note 2: Precipitation of each scale is considered separately. Total scale will be less than the sum of the amounts of the eight (8) scales.
 Note 3: Saturation Index predictions on this sheet use pH and alkalinity; %CO₂ is not included in the calculations.



ScaleSoft®
ScaleSoft®
SSP2010

Comments: _____

