

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-39220
1. Type of Well: Oil Well ☒ Gas Well ☐ Other -		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator ConocoPhillips Company		6. State Oil & Gas Lease No.
3. Address of Operator P.O. Box 51810 Midland, TX 79710		7. Lease Name or Unit Agreement Name State A-3
4. Well Location Unit Letter P : 660 feet from the South line and 385 feet from the East line Section 3 Township 20-S Range 37-E NMPM County Lea		8. Well Number 8
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3602' GR		9. OGRID Number 217817
		10. Pool name or Wildcat Weir: Blinebry, Monument: Tubb

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

REM
COM
CAS
OTHL

E-PERMITTING <SWD INJECTION>
CONVERSION RBDMS
RETURN TO TA
CSNG CHG LOC
INT TO P&A P&A NR P&A R

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

--MIRU. ND WH, NU BOP. POOH & LD Production equipment

--RIH Tbg - Tag BP @ 7,100'. Circ hole w/ MLF. Spot 50sx cmt to 6,750'.

--Set CIBP @ 5,733' - Cap w/ 45sx cmt @ 5,300'

--Spot 40sx cmt @ 4,150' - 3,800'. WOC-Tag

--Spot 60sx cmt @ 3,600' - 3,000'

--Spot 30sx cmt @ 2,750' - 2,500'. WOC-Tag

--Spot 25sx cmt @ 1,550' - 1,400'. WOC-Tag

--Spot 30sx cmt @ 250' to surface

--POOH. Fill wellbore. Verify cmt @ surface in all annuli

SPOT 25 SXs CMT @
6400'. WOC ? TAG.

A closed-loop system will be used for all fluids from this wellbore and disposed of required by OCD Rule 19.15.17

Spud Date:

11/6/08

Rig Release Date:

11/17/08

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE

TITLE

P&A Tech - Basic Energy Services

DATE

6/8/15

Type or print name

Greg Bryant

E-mail address:

PHONE:

432-563-3355

For State Use Only

APPROVED BY:

Mary Brown

TITLE

Dist. Supervisor

DATE

6/12/2015


Conditions of Approval (if any)

JUN 12 2015

WELLBORE SKETCH
ConocoPhillips Company -- Lower 48 - Mid-Continent BU / Permian

Date: May 11, 2015

RKB @ 3618'
 DF @ 3617'
 GL @ 3602'



12-1/4" Hole

8-5/8" 24# J-55 @ 1454'
 Cmt'd w/ 680 sx, circ 140 sxs
 TOC @ Surface

Top of Salt @ 1499'

Base of Salt @ 2586'

5833-5987'

6026-6195'

6480-6736'

CIBP @ 7100'
 7131-7537'

7 7/8" Hole
 5-1/2" 17# L-80 @ 7613'
 Cmt'd w/ 1250 sx, circ 172 sxs
 TOC @ Surface

PBTD: 7100'
 TD: 7623'

Subarea : Hobbs East
 Lease & Well No. : State A3 No. 08
 Legal Description : 660 FSL & 385 FEL, Sec 3, T20S, R37E
 County : Lea State : New Mexico
 Field : Weir
 Date Spudded : 11/6/2008 Rig Released: 11/17/2008
 API Number : 30-025-39220
 Status: Producing

State O&G Lse
 OGRID No. 217817
 Property Code 31798

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate Down
	11/24/2008	Perf 7131-7135, 7139-7145, 7276-7280, 7318-7321, 7356-7361, 7380-7385, 7394-7399, 7432-7436, 7498-7501, 7511-7518, 7530-7537					
	11/25/2008	Perf 6480-6486, 6581-6588, 6591-6595, 6622-6627, 6630-6633, 6639-6650, 6661-6679, 6698-6707, 6718-6736 w/ 2 SPF					
6480-6736	12/1/2008	15% HCL	4000				
6480-6736	12/1/2008	YF125ST	66,064	117,915	3999	2559	
	12/1/2008	Perf 6026-6029, 6049-6056, 6072-6075, 6089-6092, 6102-6109, 6189-6195					
	12/2/2008	Perf 5833-5843, 5854-5867, 5880-5890, 5902-5904, 5913-5919, 5934-5939, 5950-5960, 5969-5973, 5981-5987, w/ 2 SPF					
5833-6195	12/2/2008	15% HCL	5000				
5833-6195	12/2/2008	YF125ST	99,255	180,578	4410	2954	
5833-6195	10/8/2009	15% HCL	4000				
	10/13/2009	Set CIBP @ 7100'					
5833-6736	10/6/2011	15% HCL	1000				

Formation Tops:

Anhy	1411'
Top Salt	1499'
Base Salt	2586'
Yates	2744'
7 Rivers	3000'
Queen	3561'
Grayburg	3832'
San Andres	4124'
Glorieta	5321'
Blinberry	5763'
Tubb	6456'
Drinkard	6786'
Abo SD	7112'

WELLBORE SKETCH
ConocoPhillips Company -- Lower 48 - Mid-Continent BU / Permian

Date: May 11, 2015

RKB @ 3618'
 DF @ 3617'
 GL @ 3602'

Subarea : Hobbs East
 Lease & Well No. : State A3 No. 08
 Legal Description : 660 FSL & 385 FEL, Sec 3, T20S, R37E
 County : Lea State : New Mexico
 Field : Weir
 Date Spudded : 11/6/2008 Rig Released: 11/17/2008
 API Number : 30-025-39220
 Status : Producing

State O&G Lse
 OGRID No. 217817
 Property Code 31798

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate	Max Down
	11/24/2008	Perf 7131-7135, 7139-7145, 7276-7280, 7318-7321, 7356-7361, 7380-7385, 7394-7399, 7432-7436, 7498-7501, 7511-7518, 7530-7537						
	11/25/2008	Perf 6480-6486, 6581-6588, 6591-6595, 6622-6627, 6630-6633, 6639-6650, 6661-6679, 6698-6707, 6718-6736 w/ 2 SPF						
6480-6736	12/1/2008	15% HCL	4000					
6480-6736	12/1/2008	YF125ST	66,064	117,915	3999	2559		
	12/1/2008	Perf 6026-6029, 6049-6056, 6072-6075, 6089-6092, 6102-6109, 6189-6195						
	12/2/2008	Perf 5833-5843, 5854-5867, 5880-5890, 5902-5904, 5913-5919, 5934-5939, 5950-5960, 5969-5973, 5981-5987, w/ 2 SPF						
5833-6195	12/2/2008	15% HCL	5000					
5833-6195	12/2/2008	YF125ST	99,255	180,578	4410	2954		
5833-6195	10/8/2009	15% HCL	4000					
	10/13/2009	Set CIBP @ 7100'						
5833-6736	10/6/2011	15% HCL	1000					

12-1/4" Hole
 Spot 30sx cmt @ 250'-3'

8-5/8" 24# J-55 @ 1454'
 Cmt'd w/ 680 sx, circ 140 sxs
 TOC @ Surface
 Spot 25sx cmt @ 1550'-1400' - Tag
 Top of Salt @ 1499'

Base of Salt @ 2586'
 Spot 30sx cmt @ 2750'-2500' - Tag

Spot 60sx cmt @ 3600'-3000'

Spot 40sx cmt @ 4150'-3800' - Tag

Spot 45sx cmt @ 5733'-5300'
 Set CIBP @ 5733'
 5833-5987'

6026-6195'

6480-6736'

Spot 50sx cmt @ 7100'-6750'

CIBP @ 7100'
 7131-7537'

7 7/8" Hole
 5-1/2" 17# L-80 @ 7613'
 Cmt'd w/ 1250 sx, circ 172 sxs
 TOC @ Surface

PBTD: 7100'
 TD: 7623'

Formation Tops:

Anhy	1411'
Top Salt	1499'
Base Salt	2586'
Yates	2744'
7 Rivers	3000'
Queen	3561'
Grayburg	3832'
San Andres	4124'
Glorieta	5321'
Blaine	5763'
Tubb	6456'
Drinkard	6786'
Abo SD	7112'

SPOT 25 SXS @ 6400' - WOC ? TAG