

Submit 3 Copies To Appropriate District Office
 District I
 1625 N. French Dr., Hobbs, NM 87240
 District II
 1301 W. Grand Ave., Artesia, NM 88210
 District III
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 June 19, 2008

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-025-42540 /
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name: South Hobbs (GSA) Unit /
8. Well Number 249 /
9. OGRID Number 157984
10. Pool name or Wildcat Hobbs; Grayburg-San Andres

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:
 Oil Well Gas Well Other

2. Name of Operator
 Occidental Permian Ltd. **HOBBS OGD**

3. Address of Operator
 P.O. Box 4294, Houston, TX 77210-4294 **JUL 02 2015**

4. Well Location
 Unit Letter A : 286 feet from the North line and 930 feet from the East line
 Section 10 Township 19-S Range 38-E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
 3600.2' GR **RECEIVED**

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data-

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK
- TEMPORARILY ABANDON
- DRILL OR ALTER CASING
- DOWNHOLE COMMINGLE
- OTHER:

- PLUG AND ABANDON
- CHANGE PLANS
- MULTIPLE COMPL

SUBSEQUENT REPORT OF:

- REMEDIAL WORK
- COMMENCE DRILLING OPNS.
- CASING/CEMENT JOB
- ALTERING CASING
- P AND A
- OTHER: Spud & Run Surface Casing

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

See Attached

Spud Date: 6/23/15

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Mark Stephens TITLE Regulatory Compliance Analyst DATE 7/1/15
 Type or print name Mark Stephens E-mail address: Mark_Stephens@oxy.com PHONE (713) 366-5158

For State Use Only
 APPROVED BY [Signature] TITLE Petroleum Engineer DATE 07/14/15
 Conditions of Approval (if any):

JUL 14 2015 MB *[Signature]*

South Hobbs G/SA Unit No. 249
API No. 30-025-42540
Lea Co., NM

6/22/15 - MI x RU H&P 340

6/23/15 - Spud 12-1/4" hole at 6:00 a.m. (NMOCD notified)

6/23/15 -

6/25/15: Drill 12-1/4" surface hole to 1723'. Rig up casing crew and run 43 jts. 9-5/8", 36#, J-55, LT&C casing with 14 centralizers and set at 1723'. RU Halliburton x cement with 580 sx. Cl. C, 13.5 ppg (lead) x 200 sx. Cl. C, 14.8 ppg (tail). Circulate 161 sx. to surface. Cut off casing x weld on wellhead. Test wellhead to 1400 psi. NU BOP stack x test BOP's and related equipment to 250 psi low and 3000 psi high (annular to 2100 psi). Test casing to 2464 psi x 30 min. TIH x tag cement at 1658'. Drill out float x shoe to 1723'. Commence directional drilling of 8-3/4" production hole.