

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-28423
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. 31118
7. Lease Name or Unit Agreement Name Leamex
8. Well Number 36
9. OGRID Number 217817
10. Pool name or Wildcat Maljamar - GB/SA

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
ConocoPhillips Company

3. Address of Operator
P.O. Box 51810 Midland, TX 79710

4. Well Location
Unit Letter **G** : **1980** feet from the **North** line and **1980** feet from the **East** line
Section **16** Township **17-S** Range **33-E** NMPM County **Lea**

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
4184' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☒
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

E-PERMITTING <SWD INJECTION>
CONVERSION ☐ RBDMS ☐
RETURN TO ☐ TA ☐
CSNG ☐ CHG LOC ☐
INT TO P&A NR ☒ P&A R ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

--MIRU. ND WH, NU BOP. POOH w/ Prod Equip
--Set CIBP @ 4,146'. Circ hole w/ MLF. Cap BP w/ 35sx cmt to 3,696'
--Spot 25sx cmt @ 2,955' to 2,700'. WOC-Tag
--Spot 55sx cmt @ 1,495' to 825'. WOC-Tag
--Spot 30sx cmt @ 402' to surface
--POOH. Fill wellbore. Verify cmt @ surface in all annuli

PRESSURE TEST
← CSG.

The Oil Conservation Division
MUST BE NOTIFIED 24 Hours
Prior to the beginning of operations

A closed-loop system will be used for all fluids from this wellbore and disposed of required by OCD Rule 19.15.17

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Greg Bryant TITLE P&A Tech - Basic Energy Services DATE 7/14/15

Type or print name Greg Bryant E-mail address: PHONE: 432-563-3355

For State Use Only

APPROVED BY: Mary Brown TITLE Dist Supervisor DATE 7/16/2015
Conditions of Approval (if any)

WELLBORE SKETCH
ConocoPhillips Company - Lower 48 - Mid-Continent BU / Permian Operations

Date: June 22, 2015

RKB @ 4196'
 DF @ 4194'
 GL @ 4184'


Subarea: Buckeye
 Lease & Well No.: Leamex 36
 Legal Description: 1980 FNL & 1980 FEL, Sec. 16, T-17-S, R-33-E,

County: Lea State: New Mexico
 Field: Maljamar (Grayburg/San Andres)
 Date Spudded: 11/28/1983 Rig Released: 12/4/1983
 API Number: 30-025-28423
 Status: Producing

State Lease No. B-2148
 OGRID No. 017643

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate	Down
	3/6/1984	Perf 4246-4250, 4261-4266, 4271-4274, 4306-4308, 4311-4313, 4316-4320, 4342-4344, 4347-4353, 4361-4364, 4377-4382, 4392-4394, 4400-4406, 4438-4444, 4451-4453, 4460-4462, 4464-4477, 4481-4486, 4491-4493, 4547-4550, 4554-4558, 4564-4566, 4626-4628, 4634-4642, 4646-4648, 4672-4675 w/ 2 JSPF						
4246-4675	3/8/1984	15% NEFE	11,500					
4246-4675	3/12/1984	RO	31,000	34,500				
	6/18/1997	Tag Fill @ 4658'; CO to 4708'						
4246-4675	6/23/1997	15% HCL	6200					
4246-4675	3/3/2003	15% HCL	500					
4246-4675	9/16/2014	15% HCL	1500					



12 1/4" Hole

8 5/8" 24# K-55 @ 352'
 Cmt'd w/ 400 sx, circ 100 sxs
 TOC @ Surface

Top of Salt @ 876'

Base of Salt @ 2905'

4246-4274'

4306-4394'

4400-4566'

4626-4675'

7-7/8" Hole
 4 1/2" 11.6# N-80 @ 4800'
 Cmt'd w/ 1250 sx; Circ 187 sxs
 TOC @ Surface

PBD: 4757'
 TD: 4800'

Formation Tops:

Santa Rosa Base
 Rustler 1445'
 Salado
 Yates 2751'
 Queen 3746'
 Pemrose
 Grayburg 4199'
 San Andres 4500'
 Glorieta
 Abo
 Wolfcamp

WELLBORE SKETCH
ConocoPhillips Company - Lower 48 - Mid-Continent BU / Permian Operations

Date: June 22, 2015


RKB @ 4196'
 DF @ 4194'
 GL @ 4184'

Subarea : Buckeye
 Lease & Well No. : Leamex 36
 Legal Description : 1980 FNL & 1980 FEL, Sec. 16, T-17-S, R-33-E,
 County : Lea State : New Mexico
 Field : Maljamar (Grayburg/San Andres)
 Date Spudded : 11/28/1983 Rig Released: 12/4/1983
 API Number : 30-025-28423
 Status: Producing

State Lease No. B-2148
 OGRID No. 017643

Stimulation History:

Interval	Date	Type	Gals	Lbs. Sand	Max Press	ISIP	Max Rate	Max Down
	3/6/1984	Perf 4246-4250, 4261-4266, 4271-4274, 4306-4308, 4311-4313, 4316-4320, 4342-4344, 4347-4353, 4361-4364, 4377-4382, 4392-4394, 4400-4406, 4438-4444, 4451-4453, 4460-4462, 4464-4477, 4481-4486, 4491-4493, 4547-4550, 4554-4558, 4564-4566, 4626-4628, 4634-4642, 4646-4648, 4672-4675 w/ 2 JSPF						
4246-4675	3/8/1984	15% NEFE	11,500					
4246-4675	3/12/1984	RO	31,000	34,500				
	6/18/1997	Tag Fill @ 4658'; CO to 4708'						
4246-4675	6/23/1997	15% HCL	6200					
4246-4675	3/3/2003	15% HCL	500					
4246-4675	9/16/2014	15% HCL	1500					



12 1/4" Hole

Spot 30sx cmt @ 402'-3'

8 5/8" 24# K-55 @ 352'
 Cmt'd w/ 400 sx, circ 100 sxs
 TOC @ Surface

Top of Salt @ 876'

Spot 55sx cmt @ 1495'-825' - Tag

Spot 25sx cmt @ 2955'-2700' - Tag
 Base of Salt @ 2905'

Spot 35sx cmt @ 4146'-3696'
 Set CIBP @ 4146'
 4246-4274'

4306-4394'

4400-4566'

4626-4675'

7-7/8" Hole
 4 1/2" 11.6# N-80 @ 4800'
 Cmt'd w/ 1250 sx; Circ 187 sxs
 TOC @ Surface

PBTD: 4757'
 TD: 4800'

Formation Tops:

Santa Rosa Base
 Rustler 1445'
 Salado
 Yates 2751'
 Queen 3746'
 Pemrose
 Grayburg 4199'
 San Andres 4500'
 Glorieta
 Abo
 Wolfcamp