Submit 3 Copies To Appropriate District State of New Mexico Form C-103 Office May 27, 2004 Energy, Minerals and Natural Resources District I WELL API NO. 1625 N. French Dr., Hobbs, NM 88240 30-005-27940 District II OIL CONSERVATION DIVISION 1301 W. Grand Ave., Artesia, NM 88210 5. Indicate Type of Lease District III 1220 South St. Francis Dr. STATE | FEE 1000 Rio Brazos Rd., Aztec, NM 87410 Santa Fe, NM 87505 6. State Oil & Gas Lease No. District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505 VA-2146 SUNDRY NOTICES AND REPORTS ON WELLS 7. Lease Name or Unit Agreement Name (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH Chicken Little State Unit PROPOSALS.) 8. Well Number Gas Well 1. Type of Well: Oil Well Other P&A 9. OGRID Number 2. Name of Operator Yates Petroleum Corporation 025575 3. Address of Operator 10. Pool name or Wildcat 105 S. 4th Street, Artesia, NM 88210 Wildcat Oueen 4. Well Location Unit Letter 660 feet from the 660 feet from the M South line and West line Section 36 Township Range **NMPM** Chaves County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4394'GR Pit or Below-grade Tank Application 🔲 or Closure 🔲 Pit type <u>Steel</u> Depth to Groundwater <u>Distance from nearest fresh water well _</u> Distance from nearest surface water Pit Liner Thickness: Below-Grade Tank: Volume bbls; Construction Material 12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK □ PLUG AND ABANDON REMEDIAL WORK ALTERING CASING П TEMPORARILY ABANDON **CHANGE PLANS** COMMENCE DRILLING OPNS. PLUG AND ABANDON **PULL OR ALTER CASING** MULTIPLE COMPL CASING/CEMENT JOB OTHER: OTHER: 13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 10/23/05 – Began P&A procedures. 10/24/05 - Spotted 25 sx cement at 6738'-6498'. Spotted 25 sx cement at 4812'-4572'. 10/25/05 - Set CIBP at 4072' with 35' cement on top. Spotted 25 sx cement at 3665'. WOC. Tagged at 3329'. Set CIBP at 2884' with 35' cement on top. 10/26/05 - Spotted 25 sx cement at 1737'-1537'. Perforated at 476'. Set packer and squeezed with 25 sx. WOC. Tagged at 335'. Perforated at 60' and squeezed with 20 sx to surface. Leaving casing full. Cut off wellhead and anchors. Installed with 20 sx to surface. cleaned location. WELL IS PLUGGED AND ABANDONED. FINAL REPORT. 56789 Approved as to plugging of the Well Bore. Liability under bond is retained until surface restoration is completed. I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or belowgrade tank has been/will be constructed or closed according to NMOCD guidelines [], a general permit [] or an (attached) alternative OCD-approved plan []. TITLE Regulatory Compliance Supervisor DATE October 28, 2005 **SIGNATURE** E-mail address: <u>tinah@ypcnm.com</u> Telephone No. <u>505-748-1471</u> Type or print name ___ Tina Huerta PETROLEUM ENGINEER For State Use Only APPROVED BY: TITLE DATE NOV 0 2 2005

Conditions of Approval (if any):