

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO.
30-025-42457

5. Indicate Type of Lease
STATE ☒ FEE ☐

6. State Oil & Gas Lease No.
VO-8723-001

7. Lease Name or Unit Agreement Name
Mid-Vac 8 State

8. Well Number
1

9. OGRID Number
24010

10. Pool name or Wildcat
Vacuum; Abo Reef

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-104) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐

2. Name of Operator
V-F PETROLEUM INC.

3. Address of Operator
P.O. Box 1889, Midland, Texas 79702

4. Well Location
Unit Letter **P**: **990** feet from the **South** line and **990** feet from the **East** line
Section **8** Township **18-S** Range **35-E** NMPM **Lea** County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3946' GR

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETIONS ☐
DOWNHOLE COMMINGLE ☐ CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPERATIONS ☐ PLUG AND ABANDON ☐
CASING/CEMENT JOB ☒
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

07/03/15-

07/05/15 Drill 12 1/4" Intermediate Hole to 4032'.
Ran 93 Jts 40# 9 5/8" J-55 Csg.


07/06/15 Cemented w/975 sacks of Class "C" 35-65 POZ containing 5% salt + 6% gel + 2% retarder + .125 pps cellophane flakes + .4pps deformer + 3 pps Kolseal tailed w/200 sacks Class "C" containing .2 % retarder. Plug down @ 2:45 AM.
Circulated 119 sacks of cement to pit.

Spud Date:


03/31/2015

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE  TITLE Petroleum Engineer DATE 07/06/2015

Type or print name Eric Sprinkle E-mail address: eric@vfpetroleum.com PHONE: 432-683-3344
For State Use Only

APPROVED BY:  TITLE Petroleum Engineer DATE 07/23/15
Conditions of Approval (if any):

JUL 28 2015

MB

gm