 Submit 3 Copies To Appropriate District Office <u>District I</u> 	State of New Mexico Energy, Minerals and Natural F	lesources	Form C-103 May 27, 2004	
1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Ave., Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM	OIL CONSERVATION DE 1220 South St. Francis Santa Fe, NM 87505	Dr. STAT	30-025-30767 ype of Lease	
SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.) 1. Type of Well: Oil Well Gas Well Other		ACK TO A CH	7. Lease Name or Unit Agreement Name Bureaucrat AGV 8. Well Number	
Name of Operator Yates Petroleum Corporation Address of Operator 105 S. 4 th Street, Artesia, NM 88210		10. Pool nan	9. OGRID Number 025575 10. Pool name or Wildcat Wildcat San Andres	
4. Well Location Unit Letter F: 2086 feet from the North line and 2086 feet from the West line Section 14 Township 17S Range 37E NMPM Lea County 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3741' GR				
Pit type Depth to Groundwater Distance from nearest fresh water well Distance from nearest surface water Pit Liner Thickness: mil Below-Grade Tank: Volume bbls; Construction Material SSSSSSSSSSSSSSSSSSSSSSSSSSSSSSSS				
NOTICE OF IN PERFORM REMEDIAL WORK TEMPORARILY ABANDON PULL OR ALTER CASING OTHER: 13. Describe proposed or comp	PLUG AND ABANDON	SUBSEQUENT SUBSEQUENT MEDIAL WORK MMENCE DRILLING OPINS. SING/CEMENT JOB HER: Recomposite the details, and give pertinent	REPORT OF: ALTERING CASING Diletion Operations t days, including estimated date	
9-6-05 to 9-14-05 Set CIBP @ 10400' and put 35' cement on top. Perforated Bone Spring 9565-72' and 9581-91' (6 SPF) w/102 .42" holes. Acidized w/2000 gal 7-1/2% IC HCl. Set CIBP @ 9490' + cement. Perforated Abo 8644-62' and 8666-74' (2 SPF) w/52 .42" holes. Acidized w/2000 gal 15% IC HCl. Set CIBP @ 8600'. Placed 35' cement on top. Perforated San Andres 6378-88', 6446-54' and 6488-96' (2 SPF) w/52 .42" holes. Acidized 6446-96' w/2000 gal 15% NEFE and balls. Acidized 6378-88' w/1500 gal 15% NEFE and balls. Set CIBP @ 6300' and dumped cement on top. Perforated San Andres 5272-84' and 5286-91' (2 SPF) w/34 .42" holes. Acidized w/2000 gal 15% NEFE and balls.				
I hereby certify that the information above is true and complete to the best of my knowledge and belief. I further certify that any pit or below-grade tank has been/will be constructed or closed according to NMOCD guidelines , a general permit or an (attached) alternative OCD-approved plan . SIGNATURE TITLE Regulatory Compliance Technician DATE 9-28-05				
Type or print name Stormi Da For State Use Only APPROVED BY: Conditions of Approval (if any):	TITLE PE	TROLEUM ENGINEER Wolfcamp	NOV 0 3 2005 DATE	