

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised August 1, 2011

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

| |
|---|
| WELL API NO. 30-025-42149 |
| 5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/> |
| 6. State Oil & Gas Lease No. VB-1831-0002 |
| 7. Lease Name or Unit Agreement Name Cabra Loca 11 B3PA State |
| 8. Well Number 1H |
| 9. OGRID Number 14744 |
| 10. Pool name or Wildcat Ojo Chiso; Bone Spring 96553 |
| 11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3502' GL |

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Mewbourne Oil Company

3. Address of Operator
PO Box 5270, Hobbs, New Mexico

4. Well Location

Unit Letter P : 185 feet from the South line and 660 feet from the East line
Section 11 Township 22S Range 34E NMPM Lea County

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3502' GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☒

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

07/14/15..Spud 17 1/2" hole. TD hole @ 1725'. Ran 1725' of 13 3/8" 54.5# J55 ST&C csg. Cemented with 1250 sks Lite Class C w/additives. Mixed @ 13.5 /g w/ 1.72 yd. Tail w/200 sks Class C w/2% CaCl2. Mixed @ 14.8#/g w/1.33 yd. Plug down @ 2:30 PM 07/16/15. Circ 150 sks cement to the pit. WOC 18 hrs. At 1:30 PM 07/17/15, tested BOPE & csg to 1250# for 30 minutes, held OK. Drilled out with 12 1/4" bit.

Spud Date: 07/14/2015

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 07/23/15
Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905
For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engineer DATE 08/17/15
Conditions of Approval (if any):

AUG 2 2015

MB [Signature]