

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-20057
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name STATE BA
8. Well Number 6
9. OGRID Number 4323
10. Pool name or Wildcat VACCUM ABO/UPR PENN/WLFCMP
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 4,002 GL

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other ☒

2. Name of Operator
CHEVRON U.S.A. INC.

3. Address of Operator
15 SMITH ROAD MIDLAND, TEXAS 79705

4. Well Location GPS Y- LAT X-LONG.
Unit Letter D : 660 feet from the NORTH line and 860 feet from the WEST line
Section 36 Township 17-S Range 34-E NMPM County LEA

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
4,002 GL

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

E-PERMITTING <SWD INJECTION>
CONVERSION RBDMS
RETURN TO TA
CSNG ENVIRO CHG LOC
INT TO PA P&A NR P&A R

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 13 3/8" - 421' TOC SURF, 9 5/8" 36 & 40# 4,835' TOC 110', 7" - 12,109' TOC 1,600', CEMENT PLUG 9,328'-9,051', RBP @ 1,695' W/ 12FT. SAND CAP.

08 / 21 / 15 MI & RU, ND & NU BOP, TEST SAME. RIH & PULL RBP @ 1,695'.
08 / 22 / 15 RIH W/ TBG TO 9,051', CIR W/ 9.5# SALT GEL.MIX & SPOT 40 SX CL "H" CEMENT FROM 9,031' - 8,770'.
WOC & TAG @ 8,775'.
08 / 23 / 15 MIX & SPOT 40 SX CL "H" CEMENT FROM 7,900' - 7,700'. WOC & TAG @ 7,690'. MIX & SPOT 45 SX CL "H"
CEMENT FROM 7,250' - 7,050'. WOC & TAG @ 7,020'.
08 / 24 / 15 MIX & SPOT 110 SX CL "H" CEMENT FROM 6,288' - 5,616'. WOC & TAG @ 5,557', TEST 500# GOOD.
MIX & SPOT 40 SX CL "C" CEMENT FROM 4,895 - 4,660', WOC & TAG @ 4,658'.
08 / 25 / 15 MIX & SPOT 45 SX CL "C" CEMENT FROM 2,825' - 2,557', PERF @ 1,600', MIX & SQZ 40 SX CL "C" CEMENT
FROM 1,600' - 1,400', WOC & TAG @ 1,370'. PERF @ 475', EST CIR. UP 7" X 9 5/8", 13 3/8" PRESSURED UP.
MIX & CIR 165 SX CL "C CEMENT FROM 475' TO SURFACE ON BOTH STRINGS. POOH W/ TBG. NIPPLE DOWN CUT &
CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQUIRMENTS.
CLASS " H & C" CEMENT & CLOSED LOOP SYSTEM USED.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Agent for Chevron U.S.A. DATE 08 / 25 / 15

Type or print name Monty L. McCarver E-mail address: monty.mccarver@cjes.com PHONE: 713-325-6288

For State Use Only

APPROVED BY: [Signature] TITLE Dist. Supervisor DATE 8/31/2015

Conditions of Approval (if any)

SEP 01 2015