

Submit 1 Copy To Appropriate District Office
 District I - (575) 393-6161
 1625 N. French Dr., Hobbs, NM 88240
 District II - (575) 748-1283
 811 S. First St., Artesia, NM 88210
 District III - (505) 334-6178
 1000 Rio Brazos Rd., Aztec, NM 87410
 District IV - (505) 476-3460
 1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
 Energy, Minerals and Natural Resources

Form C-103
 Revised August 1, 2011

OIL CONSERVATION DIVISION
 1220 South St. Francis Dr.
 Santa Fe, NM 87505

WELL API NO. 30-025-42149	✓
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>	
6. State Oil & Gas Lease No. VB-1831-0002	
7. Lease Name or Unit Agreement Name Cabra Loca 11 B3PA State	✓
8. Well Number 1H	✓
9. OGRID Number 14744	
10. Pool name or Wildcat Ojo Chiso; Bone Spring 96553	
11. Elevation (Show whether DR, RKB, RT, GR, etc.) 3502' GL	

SUNDRY NOTICES AND REPORTS ON WELLS
 (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well Gas Well Other

2. Name of Operator
Mewbourne Oil Company ✓

3. Address of Operator
PO Box 5270, Hobbs, New Mexico

4. Well Location
 Unit Letter P : 185 feet from the South line and 660 feet from the East line
 Section 11 Township 22S Range 34E NMPM Lea County ✓

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
3502' GL

SEP 06 2015

RECEIVED

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

- PERFORM REMEDIAL WORK PLUG AND ABANDON
 TEMPORARILY ABANDON CHANGE PLANS
 PULL OR ALTER CASING MULTIPLE COMPL
 DOWNHOLE COMMINGLE

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ALTERING CASING
 COMMENCE DRILLING OPNS. P AND A
 CASING/CEMENT JOB

OTHER:

OTHER:

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

08/13/15 TD 6 1/8" hole @ 15540'. Ran 15540' of 4 1/2" 13.5# P110 LT&C csg. Top of Liner @ 10499'. Cemented with 230 sks Lite Class C (60:40:0) w/additives. Mixed @ 11.2#/g w/2.96 yd. Displaced w/174 bbls FW. Plug down @ 10:00 AM 08/15/15. Pressured up to 5300# to expand liner hanger. Displace 7" csg w/260 bbls FW. Circ 47 sks of cement off of liner top to the pit. Pulled 100k# & pushed 50k to test liner hanger. Tested liner top to 1500# for 30 mins, held OK. NU 11" 5k# x 7 1/16" 10k# tbg spool w/capping flange. Tested tbg spool pack-off to 3500#.

08/17/15 Rig released to move @ 5:00 P.M.

Spud Date: 07/14/2015

Rig Release Date: 08/17/2015

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jackie Lathan TITLE Hobbs Regulatory DATE 09/01/15

Type or print name Jackie Lathan E-mail address: jlathan@mewbourne.com PHONE: 575-393-5905

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engineer DATE 09/14/15

Conditions of Approval (if any):

SEP 15 2015

MB [Signature]