

30-025-District I  
 1625 N. French Dr., Hobbs, NM 88240  
 Phone: (575) 393-6161 Fax: (575) 393-0720  
**District II**  
 811 S. First St., Artesia, NM 88210  
 Phone: (575) 748-1283 Fax: (575) 748-9720  
**District III**  
 1000 Rio Brazos Road, Aztec, NM 87410  
 Phone: (505) 334-6178 Fax: (505) 334-6170  
**District IV**  
 1220 S. St. Francis Dr., Santa Fe, NM 87505  
 Phone: (505) 476-3460 Fax: (505) 476-3462

**State of New Mexico**  
**Energy Minerals and Natural Resources HOBBS OCD**  
**Oil Conservation Division**  
**1220 South St. Francis Dr.**  
**Santa Fe, NM 87505**

Form C-101  
 Revised July 18, 2013

SEP 17 2015  AMENDED REPORT

RECEIVED

**APPLICATION FOR PERMIT TO DRILL, RE-ENTER, DEEPEN, PLUGBACK, OR ADD A ZONE**

<sup>1</sup> Operator Name and Address CHEVRON U.S.A. INC. 15 SMITH ROAD MIDLAND, TEXAS 79705		<sup>2</sup> OGRID Number 4323	
		<sup>3</sup> API Number 30-025-35028	
<sup>4</sup> Property Code	<sup>5</sup> Property Name F.B. DAVIS		<sup>6</sup> Well No. 008

**7. Surface Location**

UL - Lot	Sec	Township	Range	Lot Idn	Feet from	N/S Line	Feet From	E/W Line	County
C	8	23S	37E		960	NORTH	2245	WEST	LEA

**8. Proposed Bottom Hole Location**

UL - Lot	Section	Township	Range	Lot Idn	Feet from	N/S Line	Feet From	E/W Line	County

**9. Pool Information**

Pool Name LANGLIE MATIX; 7 RIVERS QUEEN GRAYBURG	Pool Code 37240
---	--------------------

**Additional Well Information**

<sup>11</sup> Work Type <b>RECOMPLETE</b>	<sup>12</sup> Well Type OIL	<sup>13</sup> Cable/Rotary	<sup>14</sup> Lease Type PRIVATE	<sup>15</sup> Ground Level Elevation 3327'
<sup>16</sup> Multiple NO	<sup>17</sup> Proposed Depth 7300'	<sup>18</sup> Formation GRAYBURG	<sup>19</sup> Contractor	<sup>20</sup> Spud Date
Depth to Ground water		Distance from nearest fresh water well		Distance to nearest surface water

We will be using a closed-loop system in lieu of lined pits

**21. Proposed Casing and Cement Program**

Type	Hole Size	Casing Size	Casing Weight/ft	Setting Depth	Sacks of Cement	Estimated TOC
			NO CHANGE			

**Casing/Cement Program: Additional Comments**

--

**22. Proposed Blowout Prevention Program**

Type	Working Pressure	Test Pressure	Manufacturer

<p><sup>23</sup> I hereby certify that the information given above is true and complete to the best of my knowledge and belief.          I further certify that I have complied with 19.15.14.9 (A) NMAC <input checked="" type="checkbox"/> and/or 19.15.14.9 (B) NMAC <input checked="" type="checkbox"/> if applicable.          Signature: <i>Denise Pinkerton</i>          Printed name: DENISE PINKERTON          Title: REGULATORY SPECIALIST          E-mail Address: leakejd@chevron.com          Date: 09/15/2015      Phone: 432-687-7375</p>	<p><b>OIL CONSERVATION DIVISION</b></p> <p>Approved By: <i>[Signature]</i>          Title: <b>Petroleum Engineer</b>          Approved Date: <i>09/17/15</i>      Expiration Date: <i>09/17/17</i>          Conditions of Approval Attached</p>
--	---

ADD LANGLIE MATIX; 7 RIVERS NEW

SEP 18 2015

*[Handwritten initials]*

CHEVRON INTENDS TO PLUG BACK THE SUBJECT WELL FROM THE CURRENT BLINEBRY/PADDOCK COMPLETION INTERVAL AND RECOMPLETE IN THE GRAYBURG RESERVOIR VIA FRACTURE STIMULATION.

THE INTENDED PROCEDURE IS AS FOLLOWS:

- 1) Pull existing completion eqpt from well.
- 2) Isolate Blinebry perforations 5442-5910 w/CIBP set @ 5400' and cap w/35 cmt to 5365'. Pressure test against CIBP/cement cap to 500 psi for 10 minutes.
- 3) Isolate Paddock/Glorieta perforations 5112-5206' w/CIBP set @ 5080' and cap w/35' cmt to 5045'. Pressure test against CIBP/cement cap to 500 psi for 10 minutes.
- 4) Set Frac base CIBP @ 4050' and cap w/35' cement to 4015' (new PBTD). Pressure test against CIBP/cement cap to 500 psi for 10 minutes.
- 5) Perforate intervals 3744-3747', 3749-3755', 3775-3779', 3794-3809' & 3830-3838' @ 4 JSPF, 90 deg phasing.
- 6) Run 5 1/2" packer on 3 1/2" frac string to 3675' & set. Test 5 1/2"x3 1/2" annulus to 500 psi, install 10k frac valve & manifold. RDMOPU & MIRU frac company & associated surface eqpt for frac operations. Test eqpt & lines to 8k psi.
- 7) Frac well dn 3 1/2" frac string w/approx. 2100 gals treated water breakdown, 2500 gals 15% HCL, 9300 gals 25# gel, 75,000 gals BFrac 25 (or equiv), 6000# 100 mesh white sand, 65,000 lbs 16/30 mesh white, & 74,000 lbs resin-coated Super LC 16/30 mesh. RDMO frac eqpt.
- 8) Flow back well if necessary, otherwise MIRUPU back to well. Release treating pacer & POOH. RIH w/4 3/4" bit & 3 1/2" workstring & clean out well to PBTD.
- 9) Run completion BHA, downhole pump & rds.
- 10) RTP.

DURING THIS PROCESS WE PLAN TO USE THE CLOSED LOOP SYSTEM WITH A STEEL TANK AND HAUL TO THE REQUIRED DISPOSAL, PER THE OCD RULE 19.15.17.

PLEASE FIND ATTACHED, THE C-102 PLAT.

*J. B. Adams #8*