State of New Mexico Energy, Minerals and Natural Resources Department

OIL CONSERVATION DIVISION

FILE IN TRIPLICATE

CONDITIONS OF APPROVAL IF ANY:

Form C-103 Revised 5-27-2004

WELL API NO. 1220 South St. Francis Dr. 30-025-37428 1625 N. French Dr., Hobbs, NM 88240 Santa Fe, NM 87505 5. Indicate Type of Lease DISTRICT II STATE 1301 W. Grand Ave, Artesia, NM 88210 6. State Oil & Gas Leasé DISTRICT III 1000 Rio Brazos Rd, Aztec, NM 87410 7. Lease Name or Unit Agreement Name SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A NORTH HOBBS (G/SA) UNIT DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (Form C-101) for such proposals.) Section 31 8. Well No. 722 1. Type of Well: Oil Well X Gas Well 9. OGRID No. 2. Name of Operator 157984 Occidental Permian Ltd. 10. Pool name or Wildcat HOBBS (G/SA) 3. Address of Operator 505/397-8200 1017 W. Stanolind Rd., HOBBS, NM 88240 4. Well Location Feet From The Line Unit Letter F Feet From The NORTH 2608 EAST 1320 NMPM County Section Township 18-S Range LEA 11. Elevation (Show whether DF, RKB, RT GR, etc.) 3644' GR Pit or Below-grade Tank Application or Closure ____ Depth of Ground Water Distance from nearest fresh water well ______ Distance from nearest surface water Below-Grade Tank: Volume bbls; Construction Material Pit Liner Thickness Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data 12. NOTICE OF INTENTION TO: SUBSEQUENT REPORT OF: PERFORM REMEDIAL WORK PLUG AND ABANDON REMEDIAL WORK ALTERING CASING CHANGE PLANS COMMENCE DRILLING OPNS. PLUG & ABANDONMENT TEMPORARILY ABANDON PULL OR ALTER CASING Multiple Completion CASING TEST AND CEMENT JOB OTHER: OTHER: **New Well Completion** 13. Describe Proposed or Completed Operations (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work) SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. RUPU. Drill out DV tool @3497'. Tag PBTD @4392'. Run GR/CCL/CMTB from 4392' to surf. 2. Perforate the following intervals; 4176-93,4210-21, 4228-31, 4236-53, 4259-68, and 4284-89 using 2 spf, 120 deg sp.ph. (130 holes). Stimulate perfs 4176 to 4289 w/2600 g 15% NEFE HCL acid in 31 settings. RIH Reda ESP equipment on 126 jts 2-7/8" tbg. Intake set @4141'. Install QCI wellhead connection. RDPU. Clean Location. 10/03/2005 Rig Up Date: Rig Down Date: 10/11/2005 closed according to NMOCD guidelines or an (attached) alternative OCD-approved. a general permit **SIGNATURE** TITLE Workover Completion Specialist DATE 10/18/2005 TYPE OR PRINT NAME robert_gilbert@oxy.com TELEPHONE NO. Robert Gilbert E-mail address: For State Use Only PETROLEUM ENGINEER APPROVED BY TITLE DATE