

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENTNew Mexico Oil Conservation Division, District I
1625 N. French Drive
Hobbs, NM 88240FORM APPROVED
OMB No. 1004-0137
Expires: March 31, 2007

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.

SUBMIT IN TRIPLICATE- Other instructions on reverse side.

1. Type of Well
☐ Oil Well ☐ Gas Well ☒ Other2. Name of Operator
Breck Operating Corp.3a. Address
P.O. Box 911, Breckenridge, TX 764243b. Phone No. (include area code)
254-559-3355

4. Location of Well (Footage, Sec., T., R., M., or Survey Description)

1980' FSL & 660' FEL, Sec 29, T22S, R36E, I

5. Lease Serial No.
LC 030133B

6. If Indian, Allottee or Tribe Name

7. If Unit or CA/Agreement, Name and/or No.
NM71034X8. Well Name and No.
South Eunice Unit #439. API Well No.
30-025-0919410. Field and Pool, or Exploratory Area
Eunice 7 Rivers Queen, So.11. County or Parish, State
Lea, NM

12. CHECK APPROPRIATE BOX(ES) TO INDICATE NATURE OF NOTICE, REPORT, OR OTHER DATA

TYPE OF SUBMISSION	TYPE OF ACTION			
<input type="checkbox"/> Notice of Intent	<input type="checkbox"/> Acidize	<input type="checkbox"/> Deepen	<input type="checkbox"/> Production (Start/Resume)	<input type="checkbox"/> Water Shut-Off
<input checked="" type="checkbox"/> Subsequent Report	<input type="checkbox"/> Alter Casing	<input type="checkbox"/> Fracture Treat	<input type="checkbox"/> Reclamation	<input type="checkbox"/> Well Integrity
<input type="checkbox"/> Final Abandonment Notice	<input type="checkbox"/> Casing Repair	<input type="checkbox"/> New Construction	<input type="checkbox"/> Recomplete	<input checked="" type="checkbox"/> Other <u>Repair Csg Leak</u>
	<input type="checkbox"/> Change Plans	<input type="checkbox"/> Plug and Abandon	<input type="checkbox"/> Temporarily Abandon	
	<input type="checkbox"/> Convert to Injection	<input type="checkbox"/> Plug Back	<input type="checkbox"/> Water Disposal	

13. Describe Proposed or Completed Operation (clearly state all pertinent details, including estimated starting date of any proposed work and approximate duration thereof. If the proposal is to deepen directionally or recompleate horizontally, give subsurface locations and measured and true vertical depths of all pertinent markers and zones. Attach the Bond under which the work will be performed or provide the Bond No. on file with BLM/BIA. Required subsequent reports shall be filed within 30 days following completion of the involved operations. If the operation results in a multiple completion or recompleation in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)

10-13-05 MIRU. ND WH. NU BOP. Release pkr. POH w/tbg & pkr. PU & RIH with 5-1/2 BP & tbg. SDON.

10-14-05 Open well up. TIH to 1600'. Set BP. Set pkr @ 1548'. RU pump truck. Test BP to 500#. Release pkr. Spot 1 sx sand. POH to 345'. Set pkr. RU pump truck. Pump via tbg & establish injection rate. Release pump truck. POH. LD tools. PU & RIH with cement retainer & tbg. SDFWE.

10-17-05 RU cement company. Pump 2 bbls fresh water thru retainer. Set retainer @ 345'. Establish injection rate @ 1/2 bbl/min @ 400#. Mix & pump 50 sxs Class C with 4/10% C-16A, 3/10% C-41P. Mix @ 14.8#/gal., 25 sxs Class C with 3/10% C-41P @ 14.8#/gal. Displace, left 2 bbls cement in tbg. Hesitate squeeze last 2 bbls. Squeeze pressure 500#. Sting out of retainer. Trap 500# pressure. POH w/tbg & LD tools. SDON.

10-18-05 Finish PU DC's. RU Reverse Unit. Tag @ 314'. Drill cement stringers to 339'. Drill hard cement 339-345'. Drill on retainer 345-346'. Circulate & SD.

10-19-05 Drill cement retainer 346-348'. Drill hard cement to 474'. Drill cement stringers to 531'. Circulate. Pressure csg to 500#. Pressure dropped to 200# in 1 minute. Repeat 4 times. POH & SD.

10-20-05 Finish LD tools. RIH w/retrieving tool & tbg. Wash sand off BP @ 1600'. Retrieve BP & POH. LD tools. TIH w/tbg open ended. ND BOP. NU WH. RD.

Work to repair casing leak was unsuccessful. Breck will submit a proposed P&A procedure as soon as we receive WI owner approval.

14. I hereby certify that the foregoing is true and correct
Name (Printed/Typed)

Donald R. Craig


Title District Engineer

Signature



Date November 1, 2005

ACCEPTED FOR RETURN TO THIS SPACE FOR FEDERAL OR STATE OFFICE USE

Approved by  DAVID R. GLASS

Title

Date

Conditions of approval, if any, are attached. Approval of this notice does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

Office

Title 18 U.S.C. Section 1001 and Title 18 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Instructions on page 2)

GNW