

1000 Rio Brazos Rd., Aztec, NM 87410

11.

REMEDIAL WORK	☐	ALTERING CASING	☐
COMMENCE DRILLING OPERATION	☐	PLUG AND ABANDONMENT	☐
CASING TEST AND CEMENT JOB	☐		
OTHER:			

THIS WELL IS ON THE INACTIVE WELL LIST AND THE TA SHOULD REMOVE IT FROM THAT LIST.

DeSoto/Nichols 12-93 ver 1.0

MEXICO "J" # 17

KOB = 14'

SE 1/4 of SE 1/4 Sec 32, T24S, R38E

LEA CO., NEW MEXICO

8 5/8" 24" x 32" J-55 CASING @ 3150'
2000 SX CMT. - CIRC

2 SQUEEZE PERFS 3025', 450 SX CMT. CIRC 55 SX

3567'
QUEEN5953'
TUBB6294'
DRINKARD

5 1/2" CASING Top Down:

22 JTS, 696', 17" N-80 @ 705' (5' stub)

25 JTS, 808', 17" J-55 @ 1513'

136 JTS, 4238', 15.5" J-55 @ 5751'

62 JTS, 2025', 17" J-55 @ 7776'

26 JTS, 824', 17" N-80 @ 8600'

PBD: 8315'

CIBP @ 8350
(35' CMT ON TOP)7431
DEVONIAN
7646'
SILURIAN
8407'
FUSSELMAN

FUSSELMAN Perfs 8413' to 8550' (129 HOLES)

5 1/2" 15.5" x 17" J-55 CASING @ 8600'
910 SX CMT. - TOC @ 4298 Bone Log.

TD @ 8600'

PBD @ 8597'

JMR

3-29-92