



Submit To Appropriate District Office State Lease - 6 copies Fee Lease - 5 copies District I 1625 N. French Dr., Hobbs, NM 88240 District II 1301 W. Grand Avenue, Artesia, NM 88210 District III 1000 Rio Brazos Rd., Aztec, NM 87410 District IV 1220 S. St. Francis Dr., Santa Fe, NM 87505	State of New Mexico Energy, Minerals and Natural Resources Oil Conservation Division 1220 South St. Francis Dr. Santa Fe, NM 87505	Form C-105 Revised June 10, 2003 WELL API NO. 30-025-37049 5. Indicate Type of Lease STATE ☐ FEE ☒ State Oil & Gas Lease No.
--	---	---

WELL COMPLETION OR RECOMPLETION REPORT AND LOG													
1a. Type of Well: OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____ b. Type of Completion: NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF. WELL OVER _____ BACK RESVR. ☐ OTHER _____			7. Lease Name or Unit Agreement Name Duncan 19										
2. Name of Operator Chesapeake Operating Inc.			8. Well No. 3										
3. Address of Operator P. O. Box 11050 Midland, TX 79702-8050			9. Pool name or Wildcat D-K;Abo 15200										
4. Well Location Unit Letter G : 1650 Feet From The N Line and 1650 Feet From The E Line Section 19 Township 20S Range 39E NMPM Lea County													
10. Date Spudded 09/28/2005	11. Date T.D. Reached 10/13/2005	12. Date Compl. (Ready to Prod.) 11/03/2005	13. Elevations (DF& RKB, RT, GR, etc.) 3535 Gr	14. Elev. Casinghead									
15. Total Depth 7700	16. Plug Back T.D. 7655	17. If Multiple Compl. How Many Zones? _____	18. Intervals Drilled By 0 - 7700	Rotary Tools	Cable Tools								
19. Producing Interval(s), of this completion - Top, Bottom, Name 7452 - 7506				20. Was Directional Survey Made yes									
21. Type Electric and Other Logs Run DLL/MG; SD/DSN/SGR				22. Was Well Cored No									
23. CASING RECORD (Report all strings set in well)													
CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED								
8 5/8"	24#	1620	12 1/4	765 sx Hall-Light									
5 1/2"	17#	7700	7 7/8	2000 sx Poz									
24. LINER RECORD													
SIZE	TOP	BOTTOM	SACKS CEMENT	SCREEN									
25. TUBING RECORD													
SIZE	DEPTH SET	PACKER SET											
2 7/8"	7371												
26. Perforation record (interval, size, and number) 7452 - 7506 4 spf (136 holes)			27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC. <table border="1" style="width:100%; border-collapse: collapse;"> <tr> <th>DEPTH INTERVAL</th> <th>AMOUNT AND KIND MATERIAL USED</th> </tr> <tr> <td>7452 - 7506</td> <td>3,000gals 15% NeFe HCL + 200BS</td> </tr> <tr> <td> </td> <td>10,000gals 20% Ultragel HCL</td> </tr> <tr> <td> </td> <td> </td> </tr> </table>			DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED	7452 - 7506	3,000gals 15% NeFe HCL + 200BS		10,000gals 20% Ultragel HCL		
DEPTH INTERVAL	AMOUNT AND KIND MATERIAL USED												
7452 - 7506	3,000gals 15% NeFe HCL + 200BS												
	10,000gals 20% Ultragel HCL												
28. PRODUCTION													
Date First Production 10/27/2005		Production Method (Flowing, gas lift, pumping - Size and type pump) 2 1/2" x 1 1/2" x 24' RHBC pump		Well Status (Prod. or Shut-in) producing									
Date of Test 11/11/2005	Hours Tested 24	Choke Size	Prod'n For Test Period	Oil - Bbl 62	Gas - MCF 136								
		Water - Bbl. 12	Gas - Oil Ratio 2193										
Flow Tubing Press.	Casing Pressure	Calculated 24-Hour Rate	Oil - Bbl. 62	Gas - MCF 136	Water - Bbl. 12								
					Oil Gravity - API - (Corr.)								
29. Disposition of Gas (Sold, used for fuel, vented, etc.) Sold					Test Witnessed By								
30. List Attachments Logs, C-104, Inclination Report; C-102													
31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief													
Signature 		Printed Name Brenda Coffman		Title Regulatory Analyst									
E-mail Address bcoffman@chkenergy.com		Date 11/23/2005 											

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy	T. Canyon	T. Ojo Alamo	T. Penn "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2899	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 3149*	T. Devonian	T. Menefee	T. Madison
T. Queen 3722	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg	T. Montoya	T. Mancos	T. McCracken
T. San Andres 4319	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta 5632	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry 6082	T. Gr. Wash	T. Morrison	T.
T. Tubb 6567	T. Delaware Sand	T. Todilto	T.
T. Drinkard 6887	T. Bone Springs	T. Entrada	T.
T. Abo 7152	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from.....to..... No. 3, from.....to.....
 No. 2, from.....to..... No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
0	1606	1606	Redbeds				
1606	3149	1543	Anhydrite & Salt				
3149	4319	1170	Sand, Salt, Anhydrite, Shale & Dolo				
4319	5632	1313	Dolomite				
5632	6082	450	Dolomite & Sand				
6082	6567	485	Dolomite				
6567	6887	320	Dolomite & Sand				
6887	7700	813	Dolomite, Anhydrite & Limestone				