

Submit To Appropriate District Office
State Lease - 6 copies
Fee Lease - 5 copies
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Avenue, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Oil Conservation Division
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-105
Revised June 10, 2003

WELL API NO.
30-025-37162

5. Indicate Type of Lease
STATE ☐ FEE ☒

State Oil & Gas Lease No.

WELL COMPLETION OR RECOMPLETION REPORT AND LOG

1a. Type of Well:
OIL WELL ☒ GAS WELL ☐ DRY ☐ OTHER _____
b. Type of Completion:
NEW ☒ WORK ☐ DEEPEN ☐ PLUG ☐ DIFF.
WELL OVER BACK RESVR. ☐ OTHER

7. Lease Name or Unit Agreement Name

W. H. Turner

2. Name of Operator

Range Operating New Mexico, Inc.

3. Address of Operator

777 Main St., Ste. 800, Fort Worth, TX 76101

4. Well Location

Unit Letter L : 2310 Feet From The south Line and 990 Feet From The west Line
Section 29 Township 24S Range 37E NMPM Lea County

10. Date Spudded 11-03-05 11. Date T.D. Reached 11-12-05 12. Date Compl. (Ready to Prod.) 12-03-05 13. Elevations (DF&RKB, RT, GR, etc.) 3480 GR 14. Elev. Casinghead 3490

15. Total Depth 4430 16. Plug Back T.D. 4270 17. If Multiple Compl. How Many Zones? No 18. Intervals Drilled By Rotary Tools Cable Tools 0 - 4430

19. Producing Interval(s), of this completion - Top, Bottom, Name 3870 - 3980', 4020 - 4158; Eunice San Andres 20. Was Directional Survey Made No

21. Type Electric and Other Logs Run Dual Laterolog; Compensated Neutron 22. Was Well Cored No

23. CASING RECORD (Report all strings set in well)

CASING SIZE	WEIGHT LB./FT.	DEPTH SET	HOLE SIZE	CEMENTING RECORD	AMOUNT PULLED
8.625	24	1088	12.25	200 sx POZ/C	0
				180 sx C	
5.5	15.5	4429	7 7/8	400 sx 35:65 POZ/C	0
				250 sx 50:50 POZ/C	

24. LINER RECORD				25. TUBING RECORD		
SIZE	TOP	BOTTOM	SACKS CEMENT	SIZE	DEPTH SET	PACKER SET
				2 3/8	4184	
				SN @ 4183	TAC @ 3783	

26. Perforation record (interval, size, and number)
4020 - 4062 - 42 shots; 4092 - 4158 - 66 shots
3870 - 3916 - 46 shots; 3932 - 3938 - 12 shots; 3968 - 3980 - 24 shots
Total 190 shots

27. ACID, SHOT, FRACTURE, CEMENT, SQUEEZE, ETC.
DEPTH INTERVAL AMOUNT AND KIND MATERIAL USED
4020 - 4158 Acidize w/5000 gals 15% NEFE, 150 ball sealers
3870 - 3980 Acidize w/4000 gals 15% NEFE, 150 ball sealers

28. PRODUCTION

Date First Production 12/03/05 Production Method (*Flowing, gas lift, pumping - Size and type pump*) Pmpg; 2 1/2" x 1 3/4" x 20' RHBC BHD pmp Well Status (*Prod. or Shut-in*) Producing
Date of Test 12-05-05 Hours Tested 24 Choke Size -- Prod'n For Test Period Oil - Bbl 49 Gas - MCF 439 Water - Bbl. 459 Gas - Oil Ratio 8959
Flow Tubing Press. 250 Casing Pressure 330 Calculated 24-Hour Rate Oil - Bbl. Gas - MCF Water - Bbl. Oil Gravity - API - (*Corr.*)

29. Disposition of Gas (*Sold, used for fuel, vented, etc.*) Sold Test Witnessed By Chris Garcia

30. List Attachments

C-104, Inclination survey, Dual Laterolog, Compensated Neutron

31. I hereby certify that the information shown on both sides of this form as true and complete to the best of my knowledge and belief

Signature Paula Hale
E-mail Address phale@rangeresources.com

Printed Name Paula Hale Title Sr. Reg. Sp.

Date 12/07/05

INSTRUCTIONS

This form is to be filed with the appropriate District Office of the Division not later than 20 days after the completion of any newly-drilled or deepened well. It shall be accompanied by one copy of all electrical and radio-activity logs run on the well and a summary of all special tests conducted, including drill stem tests. All depths reported shall be measured depths. In the case of directionally drilled wells, true vertical depths shall also be reported. For multiple completions, items 25 through 29 shall be reported for each zone. The form is to be filed in quintuplicate except on state land, where six copies are required. See Rule 1105.

INDICATE FORMATION TOPS IN CONFORMANCE WITH GEOGRAPHICAL SECTION OF STATE

Southeastern New Mexico		Northwestern New Mexico	
T. Anhy 1215	T. Canyon	T. Ojo Alamo	T. Penn. "B"
T. Salt	T. Strawn	T. Kirtland-Fruitland	T. Penn. "C"
B. Salt	T. Atoka	T. Pictured Cliffs	T. Penn. "D"
T. Yates 2644	T. Miss	T. Cliff House	T. Leadville
T. 7 Rivers 2844	T. Devonian	T. Menefee	T. Madison
T. Queen 3304	T. Silurian	T. Point Lookout	T. Elbert
T. Grayburg 3631	T. Montoya	T. Mancos	T. McCracken
T. San Andres 3848	T. Simpson	T. Gallup	T. Ignacio Otzte
T. Glorieta	T. McKee	Base Greenhorn	T. Granite
T. Paddock	T. Ellenburger	T. Dakota	T.
T. Blinebry	T. Gr. Wash	T. Morrison	T.
T. Tubb	T. Delaware Sand	T. Todilto	T.
T. Drinkard	T. Bone Springs	T. Entrada	T.
T. Abo	T.	T. Wingate	T.
T. Wolfcamp	T.	T. Chinle	T.
T. Penn	T.	T. Permian	T.
T. Cisco (Bough C)	T.	T. Penn "A"	T.

OIL OR GAS SANDS OR ZONES

No. 1, from...3870.....to...4158.....
No. 2, from.....to.....
No. 3, from.....to.....
No. 4, from.....to.....

IMPORTANT WATER SANDS

Include data on rate of water inflow and elevation to which water rose in hole.

No. 1, from.....to.....feet.....
 No. 2, from.....to.....feet.....
 No. 3, from.....to.....feet.....

LITHOLOGY RECORD (Attach additional sheet if necessary)

From	To	Thickness In Feet	Lithology	From	To	Thickness In Feet	Lithology
0	1215	1215	Alluvium & Red Beds				
1215	2644	1429	Anhydrite & Salt				
2644	2844	200	Siltstone, Dolomite, & Shale				
2844	3463	619	Anhydritic Dolomite				
3463	3848	385	Siltstone, Siltstone, & Dolomite				
3848	4430	582	Dolomite				