	New Mexico Oil Conservation Divisio 1625 N. French Drive	m, pistrict I
	Hobbs, NM 83240	
		FORM APPROVED
	UNITED STATES MENT OF THE INTERIOR	Budget Bureau No. 1004-0135
· · · · · · · · · · · · · · · · · · ·	OF LAND MANAGEMENT	
		5. Lease Designation and Serial No.
SUNDRY NOTIC	ES AND REPORTS ON WELLS	NM-13279
Do not use this form for proposals to drill or to deepen or reentry to a different reservoir. Use "APPLICATION FOR PERMIT" for such proposals		6. If Indian, Allottee or Tribe Name
		N/A
SUE	BMIT IN TRIPLICATE	7. If Unit or CA, Agreement Designation
1. Type of Well Oil Gas		N/A 8. Well Name and No.
Well Well Other		Bandit 15 Federal Com #2
2. Name of Operator SAMSON RESOURCES		9. API Well No.
3. Address and Telephone No.		30-025-37231
TWO WEST SECOND STREET	T, TULSA, OK 74103-3103 (918) 583-1791	10. Field and Pool, or Exploratory Area
Location of Well (Footage, Sec., T., R	R., M., or Survey Description)	·
Surface: 1,980' FSL & 1,980	N' FEL Sec 15-208-335	11. County or Parish, State
	· . LL, UGU #U-ZUU-JJL	Lea, NM
	NATE BOX(s) TO INDICATE NATURE OF NOTIC	
		· · · · · · · · · · · · · · · · · · ·
TYPE OF SUBMISSION		OF ACTION X Change of Plans
	Recompletion	New Construction
x Subsequent Report	Plugging Back Casing Repair	Non-Routine Fracturing Water Shut-Off
Final Abandonment Notice	Altering Casing	Conversion to Injection
<u> </u>	Other	Dispose Water
	Intermediate Casing	(Note: Report results of multiple completion on Well Completion or Recompletion Report and Log form.)
	ocations and measured and true vertical depths for all markers and zone	g estimated date of starting any proposed work. If well is es pertinent to this work.)*
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500'
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Inte	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500'
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two	es pertinent to this work.)* Premium Plus Cement through t from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Inte	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500'
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Inte	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two	es pertinent to this work.)* Premium Plus Cement through t from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Inte	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Inte	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two	es pertinent to this work.)* Premium Plus Cement through t from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Inte	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks APPROVED DEC 1 4 2005
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Inte	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks APPROVED DEC 1 4 2005 GARY GOURLEY
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Inte	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks APPROVED DEC 1 4 2005
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Inte Premium Plus (stage 2).	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two erfill C & 260 sacks premium plus (stage 1) and	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks APPROVED DEC 1 4 2005 GARY GOURLEY
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Into Premium Plus (stage 2).	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two erfill C & 260 sacks premium plus (stage 1) and	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks APPROVED DEC 14 2005 GARY GOURLEY PETROLEUM ENGINEER
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Into Premium Plus (stage 2).	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two erfill C & 260 sacks premium plus (stage 1) and true and correct odd Wiley	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks APPROVED DEC 1 4 2005 GARY GOURLEY
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Into Premium Plus (stage 2).	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two erfill C & 260 sacks premium plus (stage 1) and true and correct odd Wiley Title	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks APPROVED DEC 1 4 2005 GARY GOURLEY PETROLEUM ENGINEER
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Into Premium Plus (stage 2).	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two erfill C & 260 sacks premium plus (stage 1) and true and correct odd Wiley	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks APPROVED DEC 14 2005 GARY GOURLEY PETROLEUM ENGINEER
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Into Premium Plus (stage 2).	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two erfill C & 260 sacks premium plus (stage 1) and true and correct odd Wiley Tite Tite	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks APPROVED DEC 1 4 2005 GARY GOURLEY PETROLEUM ENGINEER Date
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Into Premium Plus (stage 2).	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two erfill C & 260 sacks premium plus (stage 1) and true and correct odd Wiley Title Drilling Engineer ice use)	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks APPROVED DEC 1 4 2005 GARY GOURLEY PETROLEUM ENGINEER Date
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Into Premium Plus (stage 2).	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two erfill C & 260 sacks premium plus (stage 1) and true and correct odd Wiley Title Drilling Engineer ice use)	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks APPROVED DEC 1 4 2005 GARY GOURLEY PETROLEUM ENGINEER Date
Abandon hole section from EZSV set at 2,750'. Set cer (10.625" hole). Run and ce TVD). Pump 190 sacks Into Premium Plus (stage 2).	n 2,750 to 5,200'. Squeeze 550 SXS Halliburton ment plug to from 2,750 to 2,300' and sidetrack ement to surface 32# HCK-55 8.625" casing (two erfill C & 260 sacks premium plus (stage 1) and true and correct odd Wiley Title Drilling Engineer ice use) Title	Premium Plus Cement through from 2,300' TVD to 5,200' TVD o stage cement job-DVT @ 3,500' d 300 sacks Interfill C & 50 sacks APPROVED DEC 1 4 2005 GARY GOURLEY PETROLEUM ENGINEER Date

i T