Form 3160-5 (September 2001)

UNITED STATES DEPARTMENT OF THE INTERIOR BUREAU OF LAND MANAGEMENT

FORM APPROVED
OMB No. 1004-0135
Expires: January 31 2004

5. Lease Serial No.

		Y NOTICES AND REPOR				NM 12852		
Do not use this form for proposals to drill or to re-enter an abandoned well. Use Form 3160-3 (APD) for such proposals.					6. If Indian, Allo	ottee or Tribe Name		
	ATT IN TR	PLICATE a Other Instru	ម្យាល់ខ្លួ	everse sid	ė.	7. If Unit or CA	Agreement, Name and	/or No.
I. Type of Well ☐ Oil Well ☑ Gas Well ☐ Other						8, Well Name and No.		
2. Name of Operator						Federal 2	7 Com #3	
H.L. Brown Operating L.L.C. OGRID #213179						9. API Well No		
Sa. Address 3b. Phon			3b. Phone No	o. (include area code)		30 - 041 - 20895		
 			432 - 68	3 - 3726 10. Field and Pool, or Exploratory Area Bluitt Wolfcamp, Gas			ř	
4. Location of Well (Footage, Sec., T, R, M., or Survey Description) 1200' FNL & 1000' FWL - surface 2579' FNL & 1959' FV				- bottom hol	e	11. County or Pa		
Unit D, Sec 27, T-7-S, R-37-E Unit F, Sec 27						Roosevelt	County, NM	
12. CI	HECK API	PROPRIATE BOX(ES) TO	INDICATE	NATURE (OF NOTICE, R	EPORT, OR O	THER DATA	
TYPE OF SUBMISSION				TYPE OF ACTION				
			Д Веереп		Production (Start	/Resume) 🖊 🗂	Water Shut-Off	<u> </u>
Notice of Intent		☐ Alter Casing	Fracture Tr	eat 🔲	Reclamation	/# 0	Well Integrity	S
Subsequent Repo	rt	Casing Repair	New Const	ruction	Recomplete		Other Zing.	31
		Change Plans	Plug and A	bandon	Temporarily Ab	andon	A Plus	<u> 71) </u>
☐ Final Abandonment Notice		Convert to Injection	Plug Back		Water Disposal	- 14 .	Ochos Col	<u> </u>
3. Describe Proposed or Completed Operation								
Objective: Run slotted liner in the lateral and acid frac Wolfcamp. Prior rate: 135 MCFPD, 0 BO, 0 BW.								
09-04-02:	MIDLLV	v ria. Dologood nockey e	صدرام ما الحام	II. NID walle	and and NULL	BOD.		
09-05-02:		ey rig. Released packer and killed well. ND wellhead and NU BOP.						
09-06-02:		with 2-3/8" tubing. PU bit and PH-6 workstring. TIH to 9422' MD and tag bottom – no fill.						
09-07-02:		and PU 57 jts 3-1/2", 10.4#, N-80 HDL pre-drilled liner and TIH with liner and packer.					Londos	
03-07-02.		tom and pulled up to 9420'. Set TIW HP-6 liner-hanger packer and liner at 7704' MD. Loader and tested to 1500 psi – OK. Liner was pre-drilled from 8316' to 9389'.						
09-08-02:		vith tubing and PH-6 work string. ND BOP and NU frac valve. RU BJ services.						
09-09-02:		olfcamp down the casing and 3-1/2" liner with 77,000 gals 15% HCl, 874 Bbls slick water, 4550#						
		rock salt and 70 tons CO_2 . RD BJ and opened well to the tanks on a choke.						
09-10-02:		ck load water, spent acid and CO₂ to the frac tanks.						
09-11-02:		h wireline-set Arrowset 1X 10K packer and T-2 (1.81" ID) on/off tool and set at 7649'.						
09-12-02:	TIH with 2-3/8", J55/N80 production tubing and latched onto the packer. Tested casing to 1000 psi – OK.							
Pulled profile nipple and swabbed back load. Well kicked off flowing.								
09-13-02:	24 hrs: made 465 MCFPD, 5 BO and 89 Bbls load water. FTP = 100 psi.							
10-01-02: 24 hrs. made 325 MCFPD, 2 BO and 16 BW.								
14. 1 hereby certify the Name (PrintedITy)		ng is true and correct						
Robert McNaughton			Title Operati	ons Manager/ Pe	troleum Enginee	T		
Signature				Date 12	-29-05	-		
	, seet	A MINISTRACE F	QR FEDERA	L OR STAT	E OFFICE USE			
Approved by (Signalize SGD.) DAVID R. CLASS			Name (Printed	/Typed)	Ti	tle		
Conditions of approve certify that the applic which would entitle the	al, if any, are ant holds leg applicant to	attached Amprovance this notice all of equitable tritle to those right conduct operations thereon.	e does not warn				Date	
		itle 43 U.S.C. Section J212, make	it a crime for a	ny person knov within its juriso	wingly and willfully liction.	y to make to any de	epartment or agency of	the United

Well Bore Schematic

Lease: FEDERAL 27 Com Well: 3	Field: BLUITT WOLFCAMP (GAS)
SURFACE: Location: 1200 feet FNL& 1000 feet FWL. BHL: 2579 FEET FAXL = 1959 A FWL.	Section 27 Township 75 Range 375 Seems 27 Township 75 Range 375
Block Survey	ROOSEVELT County, //M State
	Spud Date: <u>9/03/01</u> Completion Date: <u>10/14/01</u>
GL 4057 /t.	Surface Casing
рг жв <u>4076</u> #	13% 00, 48 #/tt, grade H-40 Casing Set at 550 Cmt with 550 sks, Circ 135 sks Hole Size: 17/2
	Intermediate Casing 8% OD, 32 #/ft, grade 3-55
	Casing Set at 3900 fc Cmt with 1350 sks, Circ 76 sks TOC SURE by CIRC Hole Size: //
770C	
2-3/8", J55/N80tbg	A.
	'nipple '649'
	704' MD
Kick Off Power - 8150	13/16 000 1/-
11	7D 94.19' MD 7995' NO
	Production Casing
3-1/2", 10.4#, N-80 HDL liner pre-drilled from 8316' - 9389' PBTO: 9419'MD 7995'TVD	