## DEPARTMENT OF THE INTERIOR-HOBBS UNITEDSTATES

BUREAU OF LAND MANAGEMENT

SUNDRY NOTICES AND REPORTS ON WELLS

Do not use this form for proposals to drill or to re-enter an

FORMAPPROVED OM B No. 1004-0137 Expires: March 31, 2007

	L	e	a	S	е	2	er	1	aı	r	10.	
		_			_	_	_		_	_	_	

						4 ^	82
N	ш	л	NI	n	/	או	×,

6. If Indian, Allottee or Tribe Name

abandoned we	ll. Use Form 3160 - 3 (APD) for si	ich proposals.						
SUBMIT IN TRI	7. If Unit or CA/Agreement, Name and/or No.							
1. Type of Well  X Oil Well	8. Well Name and No.							
2. Name of Operator	Wynell Federal 5							
Chesapeake Operating Ir	9. API Well No. 30-025-37065							
3a. Address P. O. Box 11050 Midland	10. Field and Pool, or Exploratory Area							
4. Location of Well (Footage, Sec	Tonto;Seven Rivers 59470							
1800' FNL & 2010' FEL, \$	11. County or Parish, State Lea New Mexico							
12. CHECK AF	PROPRIATE BOX(ES)TO INDICATE	NATURE OF NOTICE, R	EPORT, OI	R OTHER DATA				
TYPE OF SUBMISSION	TYPE OF ACTION							
Notice of Intent  Subsequent Report	Acidize Deepen AlterCasing FractureTo Casing Repair New Cons		art/Resume)	Water Shut-Off Well Integrity OtherSpud/Casing				
	Change Plans Plug and A		andon					
Final Abandonment Notice	Convert to Injection PlugBack	Water Disposal						
following completion of the involved operations. If the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing has been completed. Final Abandonment Notices shall be filed only after all requirements, including reclamation, have been completed, and the operator has determined that the site is ready for final inspection.)  12-12-05 Spud 12 1/4" surface hole @ 11:00 p.m.  12-15-05 Ran 34 jts. 8 5/8" 24# J-55 STC csg set @1515'. Cmt'd w/265 sx  35:65:6 Cl. C 1.98 yield, tail in w/100 sx Cl. C 2.27 yield. WOC 24 hrs. Tested csg  to 1200 psi - ok  12-20-05 In 7 7/8" hole, ran 92 jts. 5 1/2" 15.5# J55 LTC csg. set @ 3918'. Cmt'd w/850 sx 35/65 Poz + additives, 2.04 yield, tail in w/225 sx + additives 1.35 yield, bump plug. RD cmt crew.Release Capstar Drilling Rig #20 @ 11:00 p.m. on  12/19/05.  Mucd Temperature survey on surface caseing.  By Calculation and the operation results in a multiple completion or recompletion in a new interval, a Form 3160-4 shall be filed once testing in the survey of the completed. The perature of the operator has determined that the site is ready for final inspection.)								
		3 ) - N	3					
14. I hereby certify that the fores	going is true and correct	*. · · · ·		/				
Name (Printed/Typed)  Brenda Coffman		Title Regulatory Ana	ılyst					
Signature S)	da Coffman	Date 01/06/2006	*******					
ACCEPTI	THIS SPACE FOR FEDERAL	OR STATE OFFICE	USE					
Approved by _	DI DAVID R. CALAD	Title		Date				
which would entitle the applicant	<del></del>	ease Office						
Title 18 U.S.C. Section 1001 and Fit States any false, fictitious or fraud	F S C Section 1212, make it a crime for an interpretations as to any representations as to any representations.	y person knowingly and willfully natter within its jurisdiction.	to make to ar	ny department or agency of the United				