

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
811 South First, Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
2040 South Pacheco, Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
2040 South Pacheco
Santa Fe, NM 87505

Form C-103
Revised March 25, 1999

WELL API NO. 30-025-28162
39-0

5. Indicate Type of Lease
STATE ☐ FEE ☐

6. State Oil & Gas Lease No.

7. Lease Name or Unit Agreement Name:

QUALITY BRINE

Watson

8. Well No.

9. Pool name or Wildcat

SUNDRY NOTICES AND REPORTS ON WELLS

(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well:

Oil Well ☐ Gas Well ☒ Other BRINE WELL

2. Name of Operator

GANDY CORPORATION

3. Address of Operator

P. O. BOX 827, TATUM, NM 88267

4. Well Location

Unit Letter M : 593 feet from the SOUTH line and 639 feet from the WEST line

Section 20 Township 12S Range 36E NMM 11273 County LEA

10. Elevation (Show whether DR, RKB, RT, GR, etc.)

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐

TEMPORARILY ABANDON ☐ CHANGE PLANS ☐

PULL OR ALTER CASING ☒ MULTIPLE COMPLETION ☐

OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐

COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐

CASING TEST AND CEMENT JOB ☐

OTHER: ☐

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

9-8-05 Run packer and set at 2180'

Hole in casing at surface, weld on new bell nipple and pressure up on casing--hole near surface (external corrosion)

9-12-05 Run new 4½ flush joint-11.6#, set at 2165', cement casing with 70 sacks of cement with .5 of 1% friction reducer and 1% calcium chloride Circulate 35 sacks to surface. Shut in for 24 hours.

9-14-05 Run 2 3/8" tubing and drill to approximately 2800' and return to brine.

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Larry Gandy TITLE SECRETARY/TREASURER DATE 9-15-05

Type or print name LARRY GANDY

Telephone No. 505-398-4960

(This space for State use)

APPROVED BY Larry W. Wink TITLE

Conditions of approval, if any:

OC FIELD REPRESENTATIVE II/STAFF MANAGER

RECEIVED

OCT 11 2005

FEB 16 2006

Oil Conservation Division
1220 S. St. Francis
Santa Fe, NM 87505