Submit 3 Copies To Appropriate District	State of Ne	w Mexico		Form C-103
Office District I	Energy, Minerals and	l Natural Resources	TYPE LABINO	May 27, 2004
1625 N. French Dr., Hobbs, NM 88240			WELL API NO.	
District II	OIL CONSERVA	TION DIVISION	30-025-20613	CI
District III 1220 South St. Francis Dr.		5. Indicate Type STATE	FEE 🖾	
1000 Rio Brazos Rd., Aztec, NM 87410	Santa Fe, N		6. State Oil & C	
<u>District IV</u> 1220 S. St. Francis Dr., Santa Fe, NM	Santa i C, i	111 07505	6. State Off & C	Jas Lease 140.
87505				
SUNDRY NOTIC	ES AND REPORTS ON V	VELLS	7. Lease Name	or Unit Agreement Name
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH		Vnicht		
PROPOSALS.)		Knight 8. Well Number	r 13	
	as Well 🔲 Other Injec	tion		
2. Name of Operator		9. OGRID Num	nber	
Whiting Oil & Gas Corporation			025078 10. Pool name or Wildcat	
3. Address of Operator 400 W. Illinois, Suite 1300, Midland, Texas 79701			Langlie Mattix Seven Rivers Queen	
4. Well Location		TN A		
	5 feet from the Eas	st line and 5	Sfeet from the	South line
Section 21	Township 24-S		-	
	11. Elevation (Show wheth			
			\\Ze'z	63.11.4
Pit or Below-grade Tank Application or			121225	0200
Pit typeSTEELDepth to Groundwater_	Distance from nearest (fresh water wellover 1,	000'_ Distance from neares	st surface water_ over 1,000'
Pit Liner Thickness: STEEL mil	Below-Grade Tank: Volu	ımebbls;	Construction Material	STEEL
12. Check A	opropriate Box to India	cate Nature of No	ice, Report or Othe	er Data
	ENTION TO	1	NUDOCOUCNE D	EDODT OF
NOTICE OF INT			SUBSEQUENT R	
PERFORM REMEDIAL WORK		REMEDIAL		ALTERING CASING RANDA
	CHANGE PLANS [DRILLING OPNS.	P AND A
TEMPORARILY ABANDON	141 U TIDI E 0014DI		MENT IOD	
PULL OR ALTER CASING	MULTIPLE COMPL [CASING/CE	MENT JOB	
PULL OR ALTER CASING OTHER:		OTHER:		
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple	eted operations. (Clearly st	OTHER:	s, and give pertinent de	ates, including estimated date
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed work	eted operations. (Clearly st	OTHER:	s, and give pertinent de	ates, including estimated date gram of proposed completion
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple	eted operations. (Clearly st	OTHER:	s, and give pertinent de	ates, including estimated date gram of proposed completion
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed work	eted operations. (Clearly st k). SEE RULE 1103. For	OTHER:	s, and give pertinent de	ates, including estimated date gram of proposed completion
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and	eted operations. (Clearly st k). SEE RULE 1103. For plugging equipment.	OTHER: ate all pertinent detai Multiple Completion	s, and give pertinent dass: Attach wellbore diag	gram of proposed completion
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed work or recompletion.	eted operations. (Clearly st k). SEE RULE 1103. For plugging equipment.	OTHER: ate all pertinent detai Multiple Completion	s, and give pertinent dass: Attach wellbore diag	gram of proposed completion
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud.	eted operations. (Clearly st k). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BC	OTHER: ate all pertinent detai Multiple Completion OP. POOH w/ tbg & p	ls, and give pertinent dass: Attach wellbore diag	gram of proposed completion & set @ 3,312'. Circulated
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312	eted operations. (Clearly st k). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BO -2,941'. POOH w/ tbg. F	OTHER: ate all pertinent detai Multiple Completion OP. POOH w/ tbg & p	s, and give pertinent dass: Attach wellbore diagrammacker. RIH w/ CIBP & 6644'. RIH w/ packer,	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @
PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy	eted operations. (Clearly st k). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BC -2,941'. POOH w/ tbg. H Hill, ok'd balanced plug.	OTHER: ate all pertinent detai Multiple Completion OP. POOH w/ tbg & poor perforated casing @ 2 RIH w/ tubing to 2,70	s, and give pertinent dass: Attach wellbore diagracker. RIH w/ CIBP & 6,644'. RIH w/ packer, 1' and pumped 25 sx C	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'.
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312	eted operations. (Clearly st k). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BC -2,941'. POOH w/ tbg. I Hill, ok'd balanced plug. I forated casing @ 1,305'. Se	OTHER: ate all pertinent detai Multiple Completion P. POOH w/ tbg & p Perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established	s, and give pertinent dass: Attach wellbore diagracker. RIH w/ CIBP & 6,644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40:	gram of proposed completion set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'.
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410'. Performance work of the complex of t	eted operations. (Clearly st k). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BO - 2,941'. POOH w/ tbg. If Hill, ok'd balanced plug. If forated casing @ 1,305'. So rated casing @ 844'. RIH	OTHER: ate all pertinent detai Multiple Completion OP. POOH w/ tbg & p Perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, established	s, and give pertinent dass: Attach wellbore diagracker. RIH w/ CIBP & 6644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40 st rate, and squeezed 45	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN.
PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410'. Perf	eted operations. (Clearly st k). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BC - 2,941'. POOH w/ tbg. If Hill, ok'd balanced plug. If forated casing @ 1,305'. So rated casing @ 844'. RIH cmt @ 620', POOH w/ wi	OTHER: ate all pertinent detai Multiple Completion OP. POOH w/ tbg & p Perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, established	s, and give pertinent dass: Attach wellbore diagracker. RIH w/ CIBP & 6644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40 st rate, and squeezed 45	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN.
PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410'. Perfor WOC & tagged cmt @ 1,100'. Perfor 02/08/06 RIH w/ wireline and tagged	eted operations. (Clearly st k). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BC - 2,941'. POOH w/ tbg. If Hill, ok'd balanced plug. If forated casing @ 1,305'. So rated casing @ 844'. RIH cmt @ 620', POOH w/ with 0' to surface. RDMO.	OTHER: ate all pertinent detai Multiple Completion OP. POOH w/ tbg & p Perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, established ireline. RIH w/ tbg to cellar.	s, and give pertinent days: Attach wellbore diagonal acker. RIH w/ CIBP & 6644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40 at a squeezed 45 a 390', pumped 25 sx C	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN. ccmt 400 to 30'. POOH w/
PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410'. Perform WOC & tagged cmt @ 1,100'. Perform 02/08/06 RIH w/ wireline and tagged tbg, ND BOP, pumped 10 sx C cmt 30	eted operations. (Clearly st k). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BC - 2,941'. POOH w/ tbg. If Hill, ok'd balanced plug. If forated casing @ 1,305'. So rated casing @ 844'. RIH cmt @ 620', POOH w/ with 0' to surface. RDMO.	OTHER: ate all pertinent detai Multiple Completion P. POOH w/ tbg & p Perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, established ireline. RIH w/ tbg to cellar.	s, and give pertinent days: Attach wellbore diagracker. RIH w/ CIBP & 6,644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40 strate, and squeezed 45 a 390', pumped 25 sx Crate as to plugging of the	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN. cmt 400 to 30'. POOH w/
PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410'. Perform WOC & tagged cmt @ 1,100'. Perform 02/08/06 RIH w/ wireline and tagged tbg, ND BOP, pumped 10 sx C cmt 30	eted operations. (Clearly st k). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BC - 2,941'. POOH w/ tbg. If Hill, ok'd balanced plug. If forated casing @ 1,305'. So rated casing @ 844'. RIH cmt @ 620', POOH w/ with 0' to surface. RDMO.	OTHER: ate all pertinent detai Multiple Completion OP. POOH w/ tbg & pool of the perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, established ireline. RIH w/ tbg to cellar. Approved Liability 1	s, and give pertinent desired as: Attach wellbore diagracker. RIH w/ CIBP & 6644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40 strate, and squeezed 45 390', pumped 25 sx Crass to plugging of the ander bond is retained.	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN. c cmt 400 to 30'. POOH w/
PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410'. Perform WOC & tagged cmt @ 1,100'. Perform 02/08/06 RIH w/ wireline and tagged tbg, ND BOP, pumped 10 sx C cmt 30	eted operations. (Clearly st k). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BC - 2,941'. POOH w/ tbg. If Hill, ok'd balanced plug. If forated casing @ 1,305'. So rated casing @ 844'. RIH cmt @ 620', POOH w/ with 0' to surface. RDMO.	OTHER: ate all pertinent detai Multiple Completion OP. POOH w/ tbg & pool of the perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, established ireline. RIH w/ tbg to cellar. Approved Liability 1	s, and give pertinent days: Attach wellbore diagonal acker. RIH w/ CIBP & 6644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40 at a squeezed 45 a 390', pumped 25 sx C	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN. c cmt 400 to 30'. POOH w/
PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410'. Performation 2/08/06 RIH w/ wireline and tagged tbg, ND BOP, pumped 10 sx C cmt 30 Cut off wellhead & install dryhole materials.	pted operations. (Clearly st k). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BC - 2,941'. POOH w/ tbg. It Hill, ok'd balanced plug. It orated casing @ 1,305'. So rated casing @ 844'. RIH cmt @ 620', POOH w/ with 0' to surface. RDMO. arker, cut anchors, backfill	OTHER: ate all pertinent detai Multiple Completion P. POOH w/ tbg & poor perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, established w/ packer, established ireline. RIH w/ tbg to cellar. Approved Liability to surface resurface resurfa	s, and give pertinent des: Attach wellbore diagracker. RIH w/ CIBP & 644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40 strate, and squeezed 45 a 390', pumped 25 sx Crate as to plugging of the ander bond is retained storation is complete wiedge and belief. I fur	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN. c cmt 400 to 30'. POOH w/ e Well Bore. d until ed.
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410°. Perform WOC & tagged cmt @ 1,100°. Perform 02/08/06 RIH w/ wireline and tagged tbg, ND BOP, pumped 10 sx C cmt 30 Cut off wellhead & install dryhole mass	pted operations. (Clearly st k). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BC - 2,941'. POOH w/ tbg. It Hill, ok'd balanced plug. It orated casing @ 1,305'. So rated casing @ 844'. RIH cmt @ 620', POOH w/ with 0' to surface. RDMO. arker, cut anchors, backfill	OTHER: ate all pertinent detai Multiple Completion P. POOH w/ tbg & poor perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, established w/ packer, established ireline. RIH w/ tbg to cellar. Approved Liability to surface resurface resurfa	s, and give pertinent des: Attach wellbore diagracker. RIH w/ CIBP & 644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40 strate, and squeezed 45 a 390', pumped 25 sx Crate as to plugging of the ander bond is retained storation is complete wiedge and belief. I fur	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN. c cmt 400 to 30'. POOH w/ e Well Bore. d until ed.
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410'. Perform WOC & tagged cmt @ 1,100'. Perform 02/08/06 RIH w/ wireline and tagged tbg, ND BOP, pumped 10 sx C cmt 30 Cut off wellhead & install dryhole magnade tank has been/will be constructed or complete to the proposed to the	eted operations. (Clearly start) is the control of	OTHER: ate all pertinent detai Multiple Completion OP. POOH w/ tbg & poor perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, established w/ packer, established ireline. RIH w/ tbg to cellar. Approved Liability to surface received to the best of my know delines \(\times \), a general per	is, and give pertinent destacts: Attach wellbore diagracker. RIH w/ CIBP & 6644'. RIH w/ packer, 1' and pumped 25 sx C rate, and squeezed 40 strate, and squeezed 45 390', pumped 25 sx C as to plugging of the ander bond is retained storation is complete vieldge and belief. I furnit \(\square\$ or an (attached) alternit \(\square\$ or a	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN. c cmt 400 to 30'. POOH w/ e Well Bore. d until ed. ther certify that any pit or belowernative OCD-approved plan
PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410'. Performation 2/08/06 RIH w/ wireline and tagged tbg, ND BOP, pumped 10 sx C cmt 30 Cut off wellhead & install dryhole materials.	eted operations. (Clearly start) is the control of	OTHER: ate all pertinent detai Multiple Completion OP. POOH w/ tbg & poor perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, established w/ packer, established ireline. RIH w/ tbg to cellar. Approved Liability to surface received to the best of my know delines \(\times \), a general per	s, and give pertinent des: Attach wellbore diagracker. RIH w/ CIBP & 644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40 strate, and squeezed 45 a 390', pumped 25 sx Crate as to plugging of the ander bond is retained storation is complete wiedge and belief. I fur	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN. c cmt 400 to 30'. POOH w/ e Well Bore. d until ed. ther certify that any pit or belowernative OCD-approved plan
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410'. Perform WOC & tagged cmt @ 1,100'. Perform 02/08/06 RIH w/ wireline and tagged tbg, ND BOP, pumped 10 sx C cmt 30 Cut off wellhead & install dryhole materials. I hereby certify that the information a grade tank has been/will be constructed or co	eted operations. (Clearly stak). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BO - 2,941'. POOH w/ tbg. Fill, ok'd balanced plug. It forated casing @ 1,305'. Strated casing @ 844'. RIH cmt @ 620', POOH w/ with the cmt @ 620', POOH w/ with the cmt according to NMOCD guides.	OTHER: ate all pertinent detai Multiple Completion P. POOH w/ tbg & p Perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, established ireline. RIH w/ tbg to cellar. Approved Liability u surface re to the best of my know delines \(\sigma, \text{ a general per} \) TLE	is, and give pertinent disc. Attach wellbore diagracker. RIH w/ CIBP & 6,644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40 strate, and squeezed 45 a 390', pumped 25 sx Crate as to plugging of the moder bond is retained storation is complete wiedge and belief. I furnit or an (attached) alteriple N Services, Inc.	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN. c cmt 400 to 30'. POOH w/ e Well Bore. d until ed. ther certify that any pit or belowernative OCD-approved plan
PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410'. Performance Performa	plugging equipment. Hill. ND wellhead, NU BC — 2,941'. POOH w/ tbg. If Hill, ok'd balanced plug. If orated casing @ 1,305'. So rated casing @ 844'. RIH I cmt @ 620', POOH w/ with O' to surface. RDMO. In which is true and complete the losest according to NMOCD guide Every according	OTHER: ate all pertinent detai Multiple Completion P. POOH w/ tbg & p Perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, established ireline. RIH w/ tbg to cellar. Approved Liability u surface re to the best of my know delines \(\sigma, \text{ a general per} \) TLE	is, and give pertinent disc. Attach wellbore diagracker. RIH w/ CIBP & 6,644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40 strate, and squeezed 45 a 390', pumped 25 sx Crate as to plugging of the moder bond is retained storation is complete wiedge and belief. I furnit or an (attached) alteriple N Services, Inc.	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN. c cmt 400 to 30'. POOH w/ e Well Bore. d until ed. ther certify that any pit or belowernative OCD-approved plan DATE 02/25/06
PULL OR ALTER CASING OTHER: 13. Describe proposed or complet of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410'. Performance Performa	eted operations. (Clearly stak). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BO - 2,941'. POOH w/ tbg. If Hill, ok'd balanced plug. If orated casing @ 1,305'. So rated casing @ 844'. RIH own of the surface. RDMO. In the control of the surface of the surface of the surface of the surface. It is the surface of the su	OTHER: ate all pertinent detai Multiple Completion OP. POOH w/ tbg & poor perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, est	is, and give pertinent destacker. RIH w/ CIBP & 6,644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40 strate, and squeezed 45 and squeezed 45 and squeezed 25 sx Crate, and squeezed 45 as to plugging of the ander bond is retained storation is complete vieldge and belief. I furnit or an (attached) alterine or an (attached) alterine or an (attached) attached the complete vieldge and belief. I furnit or an (attached) attached the complete vieldge and belief. I furnit or an (attached) attached the complete vieldge and belief. I furnit or an (attached) attached the complete vieldge and belief. I furnit or an (attached) attached the complete vieldge and belief. I furnit or an (attached) attached the complete vieldge and belief.	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN. c cmt 400 to 30'. POOH w/ E Well Bore. d until ed. Ther certify that any pit or belowernative OCD-approved plan DATE 02/25/06 Telephone No. 432-687-1994
PULL OR ALTER CASING OTHER: 13. Describe proposed or comple of starting any proposed work or recompletion. 02/03/06 MIRU Triple N rig #26 and 02/06/06 Notified NMOCD, Buddy Hole w/ mud. 02/07/06 Pumped 25 sx C cmt 3,312 1,800 psi. Notified NMOCD, Buddy WOC and tagged cmt @ 2,410'. Perform WOC & tagged cmt @ 1,100'. Perform 02/08/06 RIH w/ wireline and tagged tbg, ND BOP, pumped 10 sx C cmt 30 Cut off wellhead & install dryhole materials. I hereby certify that the information a grade tank has been/will be constructed or co	eted operations. (Clearly stak). SEE RULE 1103. For plugging equipment. Hill. ND wellhead, NU BO - 2,941'. POOH w/ tbg. If Hill, ok'd balanced plug. If orated casing @ 1,305'. So rated casing @ 844'. RIH own of the surface. RDMO. In the control of the surface of the surface of the surface of the surface. It is the surface of the su	OTHER: ate all pertinent detai Multiple Completion P. POOH w/ tbg & p Perforated casing @ 2 RIH w/ tubing to 2,70 et packer, established w/ packer, established ireline. RIH w/ tbg to cellar. Approved Liability u surface re to the best of my know delines \(\sigma, \text{ a general per} \) TLE	is, and give pertinent destacker. RIH w/ CIBP & 6,644'. RIH w/ packer, 1' and pumped 25 sx Crate, and squeezed 40 strate, and squeezed 45 and squeezed 45 and squeezed 25 sx Crate, and squeezed 45 as to plugging of the ander bond is retained storation is complete vieldge and belief. I furnit or an (attached) alterine or an (attached) alterine or an (attached) attached the complete vieldge and belief. I furnit or an (attached) attached the complete vieldge and belief. I furnit or an (attached) attached the complete vieldge and belief. I furnit or an (attached) attached the complete vieldge and belief. I furnit or an (attached) attached the complete vieldge and belief. I furnit or an (attached) attached the complete vieldge and belief.	gram of proposed completion & set @ 3,312'. Circulated unable to establish rate @ C cmt w/ 3% CaCl ₂ @ 2,701'. sx C cmt w/ CaCl ₂ @ 1,305'. sx C cmt @ 844'. SDFN. c cmt 400 to 30'. POOH w/ e Well Bore. d until ed. ther certify that any pit or belowernative OCD-approved plan DATE 02/25/06