

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-06024
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>		5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input type="checkbox"/> X
2. Name of Operator CHEVRON U.S.A. INC.		6. State Oil & Gas Lease No.
3. Address of Operator 15 SMITH ROAD MIDLAND, TEXAS 79705		7. Lease Name or Unit Agreement Name USA BERTHA J. BARBER
4. Well Location GPS Y- LAT X-LONG. Unit Letter E : 1650 feet from the NORTH line and 330 feet from the WEST line Section 8 Township 20-S Range 37-E NMPM County LEA		8. Well Number 10
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 4323
		10. Pool name or Wildcat MONUMENT PADDOCK

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

E-PERMITTING <SWD INJECTION>
CONVERSION ☐ RBDMS ☐
RETURN TO ☐ TA ☐
CSNG ☐ ENVIRO ☐ CHG LOC ☐
INT TO PA ☐ P&A NR ☒ P&A R ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion. 13 3/8" - 999' TOC SURF, 8 5/8" 32# -2,899' TOC 1,325', 7" 23# - 3,603' TOC @ 1,325', 5" 15# -5,689' TOC 3,590', PERFS 5,106'-5,665', 5" CIBP @ 5,047'.

10 / 20 / 15 MI & RU, ND & NU BOP, TEST SAME.RIH W/ TBG TO 5,029'.

10 / 22 / 15 CIR W/ 9.5# SALT GEL.MIX & SPOT 40 SX CL "C" CMT FROM 5,020' - 4,531'. WOC & TAG 4,492', MIX & SPOT 55 SX CL "C" CEMENT FROM 4,087' -3,402'. WOC & TAG 3,426'

10 / 23 / 15 PERF @ 3,150' UNABLE TO SQZ, M. WHITAKER W/ NMOC OK TO SPOT, MIX & SPOT 35 SX CL "C" CEMENT FROM 3,207' -2,771', WOC TAG @ 2,763', PERF @ 2,685' UNABLE TO SQZ, MIX & SPOT 50 SX CL "C" CEMENT FROM 2,735' -2,112', WOC TAG @ 2,137'.

10 / 24 / 15 PERF @ 1,050', ABLE TO CIR 7"X8 5/8", 8 5/8"X13 3/8" UNABLE TO CIR 5"X7" M. WHITAKER OK TO SET PLUG MIX & CIR 200 SX ON BOTH CASINGS AND INSIDE 5" FROM 1,050' -750', WOC TAG @ 787', PERF @ 300' ABLE TO CIR 7"X8 5/8" & 8 5/8"X13 3/8", BUT NOT 5"X7".

10 / 25 / 15 MIX & CIR 220 SX CL "C" CEMENT FROM 300' TO SURFACE ON ALL THREE STRINGS.

NIPPLE DOWN CUT & CAP WELL TO MEET WITH RULE 19.15.7.14 NMAC REQUIREMENTS.

CLASS "C" CEMENT & CLOSED LOOP SYSTEM USED.

Spud Date:

Rig Release Date

APPROVED FOR PLUGGING OF WELL BORE ONLY.
LIABILITY UNDER BOND IS RETAINED PENDING RECEIPT OF
C-103(SPECIFICALLY FOR SUBSEQUENT REPORT OF WELL
PLUGGING) WHICH MAY BE FOUND AT OCD WEB PAGE
UNDER FORMS. www.emnrd.state.nm.us/oecd

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE [Signature] TITLE Agent for Chevron U.S.A. DATE 10 / 26 / 15

Type or print name Monty L. McCarver E-mail address: monty.mccarver@cjes.com PHONE: 713-325-6288

For State Use Only

APPROVED BY: [Signature] TITLE Dist. Supervisor DATE 10/27/2015

Conditions of Approval (if any):

OCT 28 2015