

Submit 3 Copies To Appropriate District Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
June 19, 2008

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-01338
5. Indicate Type of Lease STATE <input type="checkbox"/> FEE <input checked="" type="checkbox"/>
6. State Oil & Gas Lease No.
7. Lease Name or Unit Agreement Name Fee MA B
8. Well Number 2
9. OGRID Number 013837
10. Pool Name or Wildcat Corbin;Abo
11. Elevation (Show whether DR, RKB, RT, GR etc.) 4009' GR

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR, USE "APPLICATION FOR PERMIT" (FORM C-10) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☒ Gas Well ☐ Other

2. Name of Operator
Mack Energy Corporation

3. Address of Operator
P.O. Box 960 Artesia, NM 88210

4. Well Location
Unit Letter B 800 feet from the North line and 2145 feet from the East line
Section 31 Township 17S Range 33E NMPM County Lea

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐

OTHER: Plugback & recomplete ☒

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐

OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

Mack Energy Corporation proposes to Plugback this well as follows.

1. Set CIBP at 8335' w/ 35' cmt cap on top.
2. Circulate hole w/9.5# brine & 25#/bbl gel @ 8300'
3. Set 25sx 14.8ppg 1.32 yield plug @ 6138'-6238', Covering top of Glorietta. WOC 4 hours.
4. Perforate Grayburg-San Andres from 4290-4445.
5. Acidize and evaluate for frac.

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Jerry W. Sherrell TITLE Production Clerk DATE 10/26/15

Type or print name Jerry W. Sherrell E-mail address: jerrys@mec.com PHONE: (575)748-1288

For State Use Only

APPROVED BY: [Signature] TITLE Petroleum Engineer DATE 11/04/15

Conditions of Approval (if any):

NOV 05 2015

Mack Energy Corporation

Fee MA B #2 30-025-01338

800 FNL & 2145 FEL Sec. 31 T17S R33E

Before

13 3/8 csg @ 297'
cmt w/225sx, circ.

8 5/8 csg @ 2799'
cmt w/950sx, circ.

Perfs from 8435-8692'

5 1/2 csg @ 8930'
cmt w/1195sx, TOC @ 1600'

TD @ 8935'

After

13 3/8 csg @ 297'
cmt w/225sx, circ.

8 5/8 csg @ 2799'
cmt w/950sx, circ.

Perforate from 4290-4445'

25sx plug from 6238-6138'

CIBP @ 8335' w/35' cmt cap

Perfs from 8435-8692'

5 1/2 csg @ 8930'
cmt w/1195sx, TOC @ 1600'

TD @ 8935'