

Submit 1 Copy To Appropriate District Office
District I - (575) 393-6161
1625 N. French Dr., Hobbs, NM 88240
District II - (575) 748-1283
811 S. First St., Artesia, NM 88210
District III - (505) 334-6178
1000 Rio Brazos Rd., Aztec, NM 87410
District IV - (505) 476-3460
1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

Form C-103
Revised July 18, 2013

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

WELL API NO. 30-025-24971
5. Indicate Type of Lease STATE ☒ FEE ☐
6. State Oil & Gas Lease No. L-101
7. Lease Name or Unit Agreement Name Mang B Com.
8. Well Number 1
9. OGRID Number 16696
10. Pool name or Wildcat Flying M Atoka, S. (Gas)

SUNDRY NOTICES AND REPORTS ON WELLS
(DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)

1. Type of Well: Oil Well ☐ Gas Well ☒ Other ☐ **HOBBS OCD**

2. Name of Operator
OXY USA Inc. **NOV 16 2015**

3. Address of Operator
P.O. Box 50250 Midland, TX 79710 **RECEIVED**

4. Well Location
Unit Letter C : 660 feet from the north line and 2130 feet from the west line
Section 36 Township 9S Range 32E NMPM County Lea

11. Elevation (Show whether DR, RKB, RT, GR, etc.)
4268'

12. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

E-PERMITTING <SWD _____ INJECTION>
CONVERSION _____ RBDMS _____
RETURN TO _____ TA _____
CSNG _____ ENVIRO _____ CHG LOC _____
INT TO PA _____ P&A NR PM P&A R _____

DON ☐
L ☐

SUBSEQUENT REPORT OF:
REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☒
CASING/CEMENT JOB ☐

OTHER: ☐ OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15. NMAC. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

See Attached

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE David Stewart TITLE Sr. Regulatory Advisor DATE 11/10/15

Type or print name David Stewart E-mail address: david_stewart@oxy.com PHONE: 432-685-5717

For State Use Only

APPROVED BY: Mark Brown TITLE Dist. Supervisor DATE 11/30/2015

Conditions of Approval (if any):

DEC 02 2015

- 10/19/2015 RUPU, dig out wellhead and valves
- 10/20/2015 Replace valves, unload & tally tbg
- 10/21/2015 Pump 10# brine to kill well, ND christmas tree on WH, ND BOP. RIH w/ CCL, tag TOF @ 10519', CCL shows pkr @ 10219' w/ tailpipe below to 10509'. Mark Whitake-NMOCD approved cutting tbg above pkr and leaving pkr in hole and setting CIBP @ 10200'. RIH & perf csg @ 10146', RIH w/ jet cutter to 10200' and cut tbg.
- 10/22/2015 POOH & LD 2-3/8" tbg, RIH w/ gauge ring & tag @ 10220', POOH. RIH & set CIBP @ 10220', POOH.
- 10/23/2015 RIH w/ tbg & tag CIBP @ 10173', M&P 10# MLF, attempt to test casing, unsuccessful. M&P 30sx CL H cmt, PUH, WOC.
- 10/26/2015 RIH w/ tbg & tag cmt @ 9906', PUH to 9393', M&P 30sx CL H cmt, POOH, WOC. RIH & set pkr @ 7800'.
- 10/27/2015 Test below pkr to 500#, held OK. RIH & tag cmt @ 8958', PUH & perf @ 8225', unable to EIR, pressure up to 1100#, no rate. Mark Whitaker-NMOCD approved spotting plug. RIH to 8279', SI for rig repair.
- 10/28/2015 M&P 25sx CL H cmt @ 8280', POOH, WOC. RIH & tag cmt @ 8069', PUH & set pkr @ 6809', RIH & perf @ 7220', unable to EIR, pressure up to 15--#, no rate. Mark Whitaker-NMOCD approved spotting plug. RIH to 7270', M&P 40sx CL H cmt, PUH & set pkr @ 5211', sqz .5bbl, pressure increased to 1250#, SI, WOC.
- 10/29/2015 RIH & tag cmt @ 6573', PUH & perf @ 5600', EIR @ 2.5BPM @ 500#, M&P 40sx CL C cmt, PUH, WOC. RIH & tag cmt @ 5388', POOH. RIH w/ CBL to 5388' and log to surface.
- 10/30/2015 RIH w/ csg jet cutter to 4750' and cut csg. Remove B section of wellhead install spear and start to POOH, unable to get collars thru WH, RIH, re-land cag, reinstall B section.
- 11/2/2015 ND B section, BOP, NU adapter spool & BOP, POOH & LD csg.
- 11/3/2015 RIH w/ tbg to 4800', circ hole w/ 10 # MLF, M&P 45sx CL C cmt @ 4800', PUH, WOC. RIH & tag cmt @ 4620', PUH.
- 11/4/2015 RIH to 3516', M&P 40sx CL C cmt, PUH, WOC. RIH & tag cmt @ 3381', POOH. ND 7-1/16 BOP, NU 11 BOP.
- 11/5/2015 RIH & perf @ 2250', RIH & set pkr @ 1118', unable to EIR, pressure to 1500#, no rate, Mark Whitaker-NMOCD approved spotting plug. POOH, w/ pkr.
- 11/6/2015 RIH to 2301', M&P 50sx CL C cmt, PUH, WOC. RIH & tag cmt @ 2102', POOH. RIH & perf @ 1650', RIH & set pkr @ 1342', attempt to EIR, pump 10bbl, pressured up to 1500#, no rate. Mark Whitaker-NMOCD approved spotting plug and sqz 3.5bbl. RIH tp 1701', M&P 60sx CL C cmt, PUH, set pkr @ 31', sqz 3.5bbl into perms, ISIP-650#, WOC.
- 11/9/2015 RIH & perf @ 446', RIH & tag cmt @ 1455', PUH & set pkr @ 31', EIR @ 2BPM @ 375#, circ to surface, M&P 265sx CL C cmt, circ to surf, visually confirmed. ND BOP, top off csg, RDP.