

15-646.

OCD Hobbs
HOBBS OCD

DEC 21 2015

RECEIVED

Form 3160-3
(March 2012)

FORM APPROVED
OMB No. 1004-0137
Expires October 31, 2014

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT

APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		7. If Unit or CA Agreement, Name and No.	
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		8. Lease Name and Well No. <i>(315791)</i> El Mar 21 A1DM Fed Com #4H	
2. Name of Operator Mewbourne Oil Company <i>(14744)</i>		9. API Well No. <i>30-025-42987</i>	
3a. Address PO Box 5270 Hobbs, NM 88241	3b. Phone No. (include area code) 575-393-5905	10. Field and Pool, or Exploratory <i>(97900)</i> Red Hills Upper Bone Spring Shale	
4. Location of Well (Report location clearly and in accordance with any State requirements.)* At surface 175' FNL & 450' FWL, Sec. 21 T26S R33E At proposed prod. zone 330' FSL & 330' FWL, Sec. 21 T26S R28E		11. Sec., T. R. M. or Blk. and Survey or Area Sec 21 T26S R33E	
14. Distance in miles and direction from nearest town or post office* 23 miles west of Jal, NM		12. County or Parish Lea	
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. unit line, if any) 175'		16. No. of acres in lease NMNM02965A - 2,174.12 acres	17. Spacing Unit dedicated to this well 160 acres
18. Distance from proposed location* to nearest well, drilling, completed, applied for, on this lease, ft. 50' - El Mar 21 A3DM #1H		20. BLM/BIA Bond No. on file NM-1693 nationwide, NMB-000919	
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3275' - GL		22. Approximate date work will start* 07/13/2015	23. Estimated duration 60 days

UNORTHODOX
LOCATION

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No.1, must be attached to this form:

- | | |
|--|---|
| 1. Well plat certified by a registered surveyor. | 4. Bond to cover the operations unless covered by an existing bond on file (see Item 20 above). |
| 2. A Drilling Plan. | 5. Operator certification |
| 3. A Surface Use Plan (if the location is on National Forest System Lands, the SUPO must be filed with the appropriate Forest Service Office). | 6. Such other site specific information and/or plans as may be required by the BLM. |

25. Signature <i>Bradley Bishop</i>	Name (Printed/Typed) Bradley Bishop	Date 05/11/2015
Title		

Approved by (Signature) <i>JM</i> /S/ JEANETTE MARTINEZ	Name (Printed/Typed)	Date DEC 14 2015
Title FIELD MANAGER	Office CARLSBAD FIELD OFFICE	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.
Conditions of approval, if any, are attached.

APPROVAL FOR TWO YEARS

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

*(Instructions on page 2)

Carlsbad Controlled Water Basin

Ka
12/21/15

Approval Subject to General Requirements & Special Stipulations Attached

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

DEC 21 2015

Mewbourne Oil Company, El Mar 21 A1DM Fed Com #4H
 Sec 21, T26S, R33E
 SL: 175' FNL & 450' FWL
 BHL: 330' FSL & 330' FWL

HOBBS OCD

DEC 21 2015

1. Geologic Formations

RECEIVED

TVD of target	9355'	Pilot hole depth	NA
MD at TD:	13840'	Deepest expected fresh water:	125'

Basin

Formation	Depth (TVD) from KB	Water/Mineral Bearing/ Target Zone?	Hazards*
Quaternary Fill	Surface		
Rustler	800	Water	
Top of Salt	1170	Salt	
Castile/Base Salt	4850		
Lamar	4930	Oil	
Bell Canyon	4935	Oil	
Cherry Canyon			
Manzanita Marker			
Brushy Canyon			
Bone Spring	9050	Target Zone	
1 st Bone Spring Sand			
2 nd Bone Spring Sand			
3 rd Bone Spring Sand			
Abo			
Wolfcamp			
Devonian			
Fusselman			
Ellenburger			
Granite Wash			

*H2S, water flows, loss of circulation, abnormal pressures, etc.

Mewbourne Oil Company, El Mar 21 A1DM Fed Com #4H
 Sec 21, T26S, R33E
 SL: 175' FNL & 450' FWL
 BHL: 330' FSL & 330' FWL

2. Casing Program

See COA

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
	From	To							
17.5"	0'	825' 920'	13.375"	48	H40	STC	1.72	4.03	8.13
12.25"	0'	3453'	9.625"	36	J55	LTC	1.13	1.96	2.49
12.25"	3453'	4393'	9.625"	40	J55	LTC	1.13	1.73	8.98
12.25"	4393'	4875'	9.625"	40	N80	LTC	1.22	2.27	38.24
8.75"	0'	8738'	7"	26	HCP110	LTC	1.72	2.19	2.77
8.75"	8738'	9632'	7"	26	HCP110	BTC	1.61	2.06	35.71
6.125"	8738'	13840'	4.5"	13.5	P110	LTC	2.20	2.55	4.89
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet

All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
 Must have table for contingency casing

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Is casing API approved? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	Y
Will the pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y
Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	N
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	Y
If yes, are there two strings cemented to surface?	Y
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

Mewbourne Oil Company, El Mar 21 A1DM Fed Com #4H
 Sec 21, T26S, R33E
 SL: 175' FNL & 450' FWL
 BHL: 330' FSL & 330' FWL

3. Cementing Program

Casing	# Sks	Wt. lb/gal	Yld ft ³ /sack	H ₂ O gal/sk	500# Comp. Strength (hours)	Slurry Description
Surf.	415	12.5	2.12	11	10	Lead: Class C + 4.0% Bentonite + 0.6% CD-32 + 5% Sodium Chloride + 0.25lb/sk Cello-Flake
	200	14.8	1.34	6.3	8	Class C + 0.005pps Static Free + 1% CaCl ₂ + 0.25 pps CelloFlake + 0.005 gps FP-6L
Inter.	775	12.5	2.12	11	10	Lead: Class C (35:65:4) + 5% Sodium Chloride + 5#/sk LCM + 0.25lb/sk Cello-Flake
	200	14.8	1.34	6.3	8	Tail: Class C + 0.25 lb/sk Cello Flake + 0.005 lb/sk Static Free
Prod.	240	12.5	2.12	11	9	Lead: 60:40:0 Class C + 15.00 lb/sk BA-90 + 4.00% MPS-5 + 3.00% SMS + 5.00% A-10 + 1.00% BA-10A + 0.80% ASA-301 + 2.90% R-21 + 8.00 lb/sk LCM-1 + 0.005 lb/sk Static Free
	400	15.6	1.18	5.2	10	Tail: Class H + 0.65% FL-52 + 0.10% R-3 + 0.005 lb/sk Static Free
Liner	205	11.2	2.97	17	16	Class C (60:40:0) + 4% MPA5 + 1.2% BA10A + 10#/sk BA90 + 5%A10 + 0.65%ASA301 + 1.5% SMS + 1.2%R21

See COA

See COA

A copy of cement test will be available on location at time of cement job providing pump times, compressive strengths, etc.

Casing String	TOC	% Excess
Surface	0'	100%
Intermediate	0'	25%
Production	4675'	25%
Liner	8738'	25%

Mewbourne Oil Company, El Mar 21 A1DM Fed Com #4H
 Sec 21, T26S, R33E
 SL: 175' FNL & 450' FWL
 BHL: 330' FSL & 330' FWL

4. Pressure Control Equipment

Variance: None

BOP installed and tested before drilling which hole?	Size?	System Rated WP	Type	✓	Tested to:
See 0074 12-1/4"	13-5/8"	2M 3M	Annular	X	T250# must test to 2000 psi
			Blind Ram		
			Pipe Ram		
			Double Ram		
			Other*		
8-3/4"	11"	3M	Annular	X	1500#
			Blind Ram	X	3000#
			Pipe Ram	X	
			Double Ram		
			Other*		
6-1/8"	11"	3M	Annular	X	1500#
			Blind Ram	X	3000#
			Pipe Ram	X	
			Double Ram		
			Other*		

*Specify if additional ram is utilized.

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

X	Formation integrity test will be performed per Onshore Order #2.
---	--

Mewbourne Oil Company, El Mar 21 A1DM Fed Com #4H
 Sec 21, T26S, R33E
 SL: 175' FNL & 450' FWL
 BHL: 330' FSL & 330' FWL

	On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
	Variance: None
N	<p>A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested.</p> <ul style="list-style-type: none"> • Provide description here <p>See attached schematic.</p>

5. Mud Program

See COP

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0'	825' 920'	FW Gel	8.6-8.8	28-34	N/C
825'	4875'	Saturated Brine	10.0	28-34	N/C
4875'	8738'	Cut Brine	8.6-9.5	28-34	N/C
8738'	13840'	FW w/Polymer	8.6-9.5	30-40	<20cc

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	Visual Monitoring
---	-------------------

6. Logging and Testing Procedures

Logging, Coring and Testing.	
X	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No Logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain
	Coring? If yes, explain

Additional logs planned	Interval
X	Gamma Ray
	Density
	CBL
	Mud log
	PEX

Mewbourne Oil Company, El Mar 21 A1DM Fed Com #4H
 Sec 21, T26S, R33E
 SL: 175' FNL & 450' FWL
 BHL: 330' FSL & 330' FWL

7. Drilling Conditions

Condition	Specify what type and where?
BH Pressure at deepest TVD	4022 psi
Abnormal Temperature	No

Mitigation measure for abnormal conditions. Describe. Lost circulation material/sweeps/mud scavengers in surface hole.

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.

See COA

	H2S is present
X	H2S Plan attached

8. Other facets of operation

Is this a walking operation? If yes, describe. *No*

Will be pre-setting casing? If yes, describe. *No*

Attachments

Directional Plan

Other, describe