

FORM APPROVED
OMB No. 1004-0137
Expires October 31, 2014

SECRETARY'S BOTASHD
HOBBBS
JAN 25 2016
RECEIVED

UNITED STATES
DEPARTMENT OF THE INTERIOR
BUREAU OF LAND MANAGEMENT
APPLICATION FOR PERMIT TO DRILL OR REENTER

1a. Type of Work: <input checked="" type="checkbox"/> DRILL <input type="checkbox"/> REENTER		5. Lease Serial No. NMNM85937	
1b. Type of Well: <input checked="" type="checkbox"/> Oil Well <input type="checkbox"/> Gas Well <input type="checkbox"/> Other <input checked="" type="checkbox"/> Single Zone <input type="checkbox"/> Multiple Zone		6. If Indian, Allottee or Tribe Name Airbonita 12 Federal #11H	
2. Name of Operator COG Operating LLC. (229137)		7. If Unit or CA Agreement, Name and No.	
3a. Address 2208 West Main Street Artesia, NM 88210		8. Lease Name and Well No. (38682)	
3b. Phone No. (include area code) 575-748-6940		9. API Well No. 30-025-43031	
4. Location of Well (Report location clearly and in accordance with any State requirements. *) At surface 190' FSL & 1980' FWL Unit Letter N (SESW) SHL At proposed prod. Zone 330' FNL & 1980' FWL Unit Letter C (NENW) BHL		10. Field and Pool, or Exploratory (51683) Red Tank; Bone Spring	
14. Distance in miles and direction from nearest town or post office* About 25 miles from Malaga		11. Sec., T.R.M. or Blk and Survey or Area Sec. 12 - T22S - R32E	
15. Distance from proposed* location to nearest property or lease line, ft. (Also to nearest drig. Unit line, if any) 190		12. County or Parish Lea County	
16. No. of acres in lease 800		13. State NM	
17. Spacing Unit dedicated to this well 160		18. Distance from location* to nearest well, drilling, completed, applied for, on this lease, ft. SHL: 30' (Proposed Airbonita #7H) BHL: 1585'	
19. Proposed Depth TVD: 9886' MD: 14437'		20. BLM/BIA Bond No. on file NMB000740 & NMB000215	
21. Elevations (Show whether DF, KDB, RT, GL, etc.) 3657.9' GL		22. Approximate date work will start* 9/1/2015	
		23. Estimated duration 30 days	

UNORTHODOX LOCATION

24. Attachments

The following, completed in accordance with the requirements of Onshore Oil and Gas Order No. 1, shall be attached to this form:

- Well plat certified by a registered surveyor.
- A Drilling Plan
- A Surface Use Plan (if the location is on National Forest System Lands, the SUPO shall be filed with the appropriate Forest Service Office).
- Bond to cover the operations unless covered by an existing bond on file (see Item 20 above).
- Operator certification
- Such other site specific information and/or plans as may be required by the authorized officer.

25. Signature <i>Mayte Reyes</i>	Name (Printed/Typed) Mayte Reyes	Date 5-6-15
-------------------------------------	-------------------------------------	----------------

Title Regulatory Analyst		Title FIELD MANAGER	
Approved by (Signature) /s/George MacDonell		Name (Printed/Typed)	
		Date JAN 19 2016	
		Office BLM-CARLSBAD FIELD OFFICE	

Application approval does not warrant or certify that the applicant holds legal or equitable title to those rights in the subject lease which would entitle the applicant to conduct operations thereon.

APPROVAL FOR TWO YEARS

Conditions of approval, if any, are attached.

Title 18 U.S.C. Section 1001 and Title 43 U.S.C. Section 1212, make it a crime for any person knowingly and willfully to make to any department or agency of the United States any false, fictitious or fraudulent statements or representations as to any matter within its jurisdiction.

(Continued on page 2)

SEE ATTACHED FOR
CONDITIONS OF APPROVAL

Kz
01/26/16

APPROVAL SUBJECT TO INSTRUCTIONS ON PAGE 2
GENERAL REQUIREMENTS AND
SPECIAL STIPULATIONS
ATTACHED

JAN 27 2016

Witness Surface & Intermediate Casing

Carlsbad Controlled Water Basin

HOBBS OCD
JAN 25 2016
RECEIVED

1. Geologic Formations

TVD of target	9886'	Pilot hole depth	N/A
MD at TD:	14437'	Deepest expected fresh water:	580

Basin

Formation	Depth (TVD) from KB	Water/Mineral Bearing/Target Zone?	Hazards*
Quaternary Fill	Surface	Water	
Rustler	868'	Water	
Top of Salt	952'	Salt	
Lamar	4708'		
Delaware Group	4807'	Oil/Gas	
Bone Spring	8579'	Oil/Gas	
First Bone Spring	9811'	Target Zone	
Second Bone Spring	10360'	Will Not Penetrate	

*H2S, water flows, loss of circulation, abnormal pressures, etc.

2. Casing Program

See COP

Hole Size	Casing Interval		Csg. Size	Weight (lbs)	Grade	Conn.	SF Collapse	SF Burst	SF Tension
	From	To							
17.5"	0	920 910	13.375"	54.5	J55	STC	2.62	1.23	10.25
12.25"	0	4300	9.625"	40	J55	BTC	1.28	0.85*	3.32
12.25"	4350	4750	9.625"	40	L80	BTC	1.39	1.24	50.89
8.75"	0	14437	5.5"	17	P110	LTC	1.62	2.30	1.81D
BLM Minimum Safety Factor							1.125	1	1.6 Dry 1.8 Wet

- All casing strings will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.h
- BLM standard formulas used on all safety factor calculations
- Assumed 9 ppg MW equivalent pore pressure
- *Explanation for SF's below BLM's minimum standards:
 - 9-5/8" Burst SF @ 0.85 – used BLM's frac gradient scenario to qualify
 - $3950 \text{ psi} / 4750' = 0.83 > 0.7$

	Y or N
Is casing new? If used, attach certification as required in Onshore Order #1	Y
Does casing meet API specifications? If no, attach casing specification sheet.	Y
Is premium or uncommon casing planned? If yes attach casing specification sheet.	N
Does the above casing design meet or exceed BLM's minimum standards? If not provide justification (loading assumptions, casing design criteria).	N
Will the intermediate pipe be kept at a minimum 1/3 fluid filled to avoid approaching the collapse pressure rating of the casing?	Y

COG Operating LLC, Airbonita 12 Federal 11H

Is well located within Capitan Reef?	N
If yes, does production casing cement tie back a minimum of 50' above the Reef?	
Is well within the designated 4 string boundary.	
Is well located in SOPA but not in R-111-P?	Y
If yes, are the first 2 strings cemented to surface and 3 rd string cement tied back 500' into previous casing?	Y
Is well located in R-111-P and SOPA?	N
If yes, are the first three strings cemented to surface?	
Is 2 nd string set 100' to 600' below the base of salt?	
Is well located in high Cave/Karst?	N
If yes, are there two strings cemented to surface?	
(For 2 string wells) If yes, is there a contingency casing if lost circulation occurs?	
Is well located in critical Cave/Karst?	N
If yes, are there three strings cemented to surface?	

3. Cementing Program

Casing	# Skis	Wt. lb/gal	Yld ft ³ /sack	H ₂ O gal/sk	500# Comp. Strength (hours)	Slurry Description
Surf.	425	13.5	1.75	9.15	5.5	Lead: Class C + 4.0% Gel + 2.0% CaCl ₂
	240	14.8	1.35	6.57	7	Tail: Class C + 2.0% CaCl ₂
Inter.	1080	13.5	1.73	9.15	5.5	Lead: Class C + 4.0% Gel
	350	14.8	1.34	6.47	5.5	Tail: Class C
Prod.	965	10.4	3.48	21.16	90	Lead: Tuned Lite + 2 lb/sk Kol-Seal + 0.125 lb/sk. Pol-E-Flake + 0.5 lb/sk HALAD-9 + 0.25 lb/sk D-Air 5000
	1200	14.4	1.25	5.69	19	Tail: Class H + 0.5% HALAD-9 + 0.05% SA-1015 + 1% NaCL + 2% Gel

Casing String	TOC	% Excess
Surface	0'	66%
Intermediate	0'	66%
Production	0'	48%

COG Operating LLC, Airbonita 12 Federal 11H

4. Pressure Control Equipment

N	A variance is requested for the use of a diverter on the surface casing. See attached for schematic.
---	--

BOP installed and tested before drilling which hole?	Size?	Min. Required WP	Type	✓	Tested to:
12-1/4"	13-5/8"	2M	Annular	X	WP
			Blind Ram		WP
			Pipe Ram		
			Double Ram		
			Other*		
8-3/4"	13-5/8"	3M	Annular	X	50% WP
			Blind Ram	X	WP
			Pipe Ram	X	
			Double Ram		
			Other*		

See COG

BOP/BOPE will be tested by an independent service company to 250 psi low and the high pressure indicated above per Onshore Order 2 requirements. The System may be upgraded to a higher pressure but still tested to the working pressure listed in the table above. If the system is upgraded all the components installed will be functional and tested.

Pipe rams will be operationally checked each 24 hour period. Blind rams will be operationally checked on each trip out of the hole. These checks will be noted on the daily tour sheets. Other accessories to the BOP equipment will include a Kelly cock and floor safety valve (inside BOP) and choke lines and choke manifold. See attached schematics.

N	Formation integrity test will be performed per Onshore Order #2. On Exploratory wells or on that portion of any well approved for a 5M BOPE system or greater, a pressure integrity test of each casing shoe shall be performed. Will be tested in accordance with Onshore Oil and Gas Order #2 III.B.1.i.
Y	A variance is requested for the use of a flexible choke line from the BOP to Choke Manifold. See attached for specs and hydrostatic test chart.
N	Are anchors required by manufacturer?
N	A multibowl wellhead is being used. The BOP will be tested per Onshore Order #2 after installation on the surface casing which will cover testing requirements for a maximum of 30 days. If any seal subject to test pressure is broken the system must be tested. See attached schematic.

See COG

COG Operating LLC, Airbonita 12 Federal 11H

5. Mud Program

Depth		Type	Weight (ppg)	Viscosity	Water Loss
From	To				
0	Surf. shoe	FW Gel	8.4-9.4	32-34	N/C
Surf csg	Int shoe	Saturated Brine	10.0-10.2	28-30	N/C
Int shoe	TD	Cut Brine	8.8-9.2	28-30	N/C

Sufficient mud materials to maintain mud properties and meet minimum lost circulation and weight increase requirements will be kept on location at all times.

What will be used to monitor the loss or gain of fluid?	PVT/Pason/Visual Monitoring
---	-----------------------------

6. Logging and Testing Procedures

Logging, Coring and Testing	
X	Will run GR/CNL from TD to surface (horizontal well – vertical portion of hole). Stated logs run will be in the Completion Report and submitted to the BLM.
	No Logs are planned based on well control or offset log information.
	Drill stem test? If yes, explain
	Coring? If yes, explain

Additional logs planned	Interval
Resistivity	
Density	
CBL	
X Mud log	Production
PEX	

7. Drilling Conditions

Condition	Specify what type and where?
BH Pressure at deepest TVD	4,627 psi @ 9886' TVD
Abnormal Temperature	No

Mitigation measure for abnormal conditions. Describe: No abnormal drilling conditions are expected to occur.

Hydrogen Sulfide (H2S) monitors will be installed prior to drilling out the surface shoe. If H2S is detected in concentrations greater than 100 ppm, the operator will comply with the provisions of Onshore Oil and Gas Order #6. If Hydrogen Sulfide is encountered, measured values and formations will be provided to the BLM.

N	H2S is present
Y	H2S Plan attached

See COP

8. Other facets of operation

Is this a walking operation? Yes *No. If multiple wells are being drilled Submit Sundry.*
Will be pre-setting casing? No

Attachments

- Directional Plan
- BOP & Choke Schematics
- C102 and supporting maps
- Rig plat
- H2S schematic
- H2S contingency plan
- Interim reclamation plat
- Variance for Flex Hose