

Submit 1 Copy To Appropriate District
Office
District I
1625 N. French Dr., Hobbs, NM 88240
District II
1301 W. Grand Ave., Artesia, NM 88210
District III
1000 Rio Brazos Rd., Aztec, NM 87410
District IV
1220 S. St. Francis Dr., Santa Fe, NM
87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103
Revised July 18, 2013

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)		WELL API NO. 30-025-31304 ✓
1. Type of Well: Oil Well ☒ Gas Well ☐ Other ☐		5. Indicate Type of Lease STATE ☒ FEE ☐
2. Name of Operator XTO Energy, Inc. ✓		6. State Oil & Gas Lease No.
3. Address of Operator 500 W. Illinois St Ste 100 Midland, TX 79701		7. Lease Name or Unit Agreement Name: Arrowhead Grayburg Unit ✓
4. Well Location Unit Letter N : 660 feet from the South line and 1905 feet from the West line Section 2 Township 22S Range 36E NMPM County Lea ✓		8. Well Number 174 ✓
11. Elevation (Show whether DR, RKB, RT, GR, etc.)		9. OGRID Number 005380
		10. Pool name or Wildcat Arrowhead; Grayburg

12. Check Appropriate Box to Indicate Nature of Notice, Report, or Other Data

NOTICE OF INTENTION TO:

PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☒ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPL ☐
DOWNHOLE COMMINGLE ☐
CLOSED-LOOP SYSTEM ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ P AND A ☐
CASING/CEMENT JOB ☐
OTHER: ☐

13. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 19.15.7.14 NMAC.. For Multiple Completions: Attach wellbore diagram of proposed completion or recompletion.

XTO Energy, Inc respectfully requests to TA the referenced well with the following procedure:

1. Set CIBP @ 3700'.
2. Cap w/35' cmt via wireline or 25sxs thru tbq. WOC. Tag.
3. Run a good MIT.

A closed-loop system will be used to perform this procedure.

Condition of Approval: notify
OCD Hobbs office 24 hours
prior of running MIT Test & Chart

Spud Date:

Rig Release Date:

I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Stephanie Rabadue TITLE Regulatory Analyst DATE 02/05/2016

Type or print name Stephanie Rabadue E-mail address: stephanie_rabadue@xtoenergy.com PHONE 432-620-6714

For State Use Only

APPROVED BY Malcolm Brown TITLE Dist Supervisor DATE 2/10/2016

Conditions of Approval (if any):

FEB 11 2016

CY

Arrowhead Grayburg Unit #174

API: 30-025-31304

Current WBD

ELEV: GL: 3652'
KB TO GL: 11'
DF TO GL: 10'

TUBING (07/31/12):
114 JTS 2 7/8" 8RD J-55, 1 TAC, 13 JTS 2
7/8" 6.5# J-55, 2-3/4" BN PMP, PERF SUB,
BP/MA @ 3995'.
TAC @ 3545'. EOT @ 4025'.

RODS (12/06/12):
1-1/2" SM, 7/8" PONY, 144 RDS 7/8"
N-97 (98), 12 K-BARS, 1-1/2" ON/OFF
TOOL (NEW).
ON/OFF TOOL @ 3949'.

5-1/2" OD K-55 15.5# CSG SET
@ 4090'. CMT W/750 SX.
CIRC 10SX TO SURF.

8-5/8" OD 23# M-50 SURF PIPE
SET @ 1417' W/900 SX CMT.
CIRC 76 SX TO SURF.

T/PNRS

3724-29'
3730-40'
3752-57'
3458-68'
3776-82'
3783-90'
3796-3806'

T/AGU

3814-22'

Z1

3838-40'
3846-48'
3862-64'

Z2

3872-74'
3885-87'
3895-97'
3897-3900'
3904-06'
3909-12'
3912-14'
3919-21'
3921-24'
3927-29'
3929-34'
3944-46'

Z3

3950-52'
3970-72'

Z4

3988-90'
4000-04'
4014-18'

Z5

4044-48'
4052-55'

PBTD: 4072'
TD: 4090'

Arrowhead Grayburg Unit #174

API: 30-025-31304

Proposed WBD

ELEV: GL: 3652'
KB TO GL: 11'
DF TO GL: 10'

35' CMT
CIBP @ 3700' w/ - or -
25 SX5
TUBING (07/31/12):
114 JTS 2 7/8" 8RD J-55, 1 TAC, 13 JTS 2
7/8" 6.5# J-55, 2-3/4" BN PMP, PERF SUB,
BP/MA @ 3995'.
TAC @ 3545'. EOT @ 4025'.

RODS (12/06/12):
1-1/2" SM, 7/8" PONY, 144 RDS 7/8"
N-97 (98), 12 K-BARS, 1-1/2" ON/OFF
TOOL (NEW).
ON/OFF TOOL @ 3949'.

5-1/2" OD K-55 15.5# CSG SET
@ 4090'. CMT W/750 SX.
CIRC 10SX TO SURF.

8-5/8" OD 23# M-50 SURF PIPE
SET @ 1417' W/900 SX CMT.
CIRC 76 SX TO SURF.

T/PNRS
3724-29'
3730-40'
3752-57'
3458-68'
3776-82'
3783-90'
3796-3806'
T/AGU
3814-22'
Z1
3838-40'
3846-48'
3862-64'
Z2
3872-74'
3885-87'
3895-97'
3897-3900'
3904-06'
3909-12'
3912-14'
3919-21'
3921-24'
3927-29'
3929-34'
3944-46'
Z3
3950-52'
3970-72'
Z4
3988-90'
4000-04'
4014-18'
Z5
4044-48'
4052-55'

PBTD: 4072'
TD: 4090'