

Submit 3 Copies To Appropriate District
Office

District I

1625 N. French Dr., Hobbs, NM 88240

District II

1301 W. Grand Avenue, Artesia, NM 87210

District III

1000 Rio Brazos Rd., Aztec, NM 87410

District IV

1220 S. St. Francis Dr., Santa Fe, NM 87505

State of New Mexico
Energy, Minerals and Natural Resources

OIL CONSERVATION DIVISION
1220 South St. Francis Dr.
Santa Fe, NM 87505

Form C-103

Revised March 25, 1999

WELL API NO. 30-041-20899
5. Indicate Type of Lease STATE <input checked="" type="checkbox"/> FEE <input type="checkbox"/>
6. State Oil & Gas Lease No. LH-2338
7. Lease Name or Unit Agreement Name: FOX B STATE
8. Well No. 3
9. Pool name or Wildcat ALLISON PENN

SUNDRY NOTICES AND REPORTS ON WELLS (DO NOT USE THIS FORM FOR PROPOSALS TO DRILL OR TO DEEPEN OR PLUG BACK TO A DIFFERENT RESERVOIR. USE "APPLICATION FOR PERMIT" (FORM C-101) FOR SUCH PROPOSALS.)	
1. Type of Well: Oil Well <input checked="" type="checkbox"/> Gas Well <input type="checkbox"/> Other <input type="checkbox"/>	
2. Name of Operator LAYTON ENTERPRISES, INC.	
3. Address of Operator 3103 79th St. LUBBOCK, TEXAS 79423	
4. Well Location Unit Letter I : 1980 feet from the SOUTH line and 510 feet from the EAST line Section 36 Township 8S Range 36E NMPM County ROOSEVELT	
10. Elevation (Show whether DR, RKB, RT, GR, etc.) 4044GL	

11. Check Appropriate Box to Indicate Nature of Notice, Report or Other Data

NOTICE OF INTENTION TO:


- PERFORM REMEDIAL WORK ☐ PLUG AND ABANDON ☐
TEMPORARILY ABANDON ☐ CHANGE PLANS ☐
PULL OR ALTER CASING ☐ MULTIPLE COMPLETION ☐
OTHER: ☐

SUBSEQUENT REPORT OF:

- REMEDIAL WORK ☐ ALTERING CASING ☐
COMMENCE DRILLING OPNS. ☐ PLUG AND ABANDONMENT ☐
CASING TEST AND CEMENT JOB ☐
OTHER: ☒ PLUG BACK

12. Describe proposed or completed operations. (Clearly state all pertinent details, and give pertinent dates, including estimated date of starting any proposed work). SEE RULE 1103. For Multiple Completions: Attach wellbore diagram of proposed completion or recompilation.

Set C.I. Bridge Plug @9570 w/5 sks. cement on top.
Spotted 15 sks cement 7850 - 7700.
Spotted 15 sks cement 6200 - 6150.
9# mud laden fluid between plugs.
Prep. to perforate & treat selected San Andres zones.



I hereby certify that the information above is true and complete to the best of my knowledge and belief.

SIGNATURE Donald R. Layton President DATE 7-9-03

Type or print name DONALD R. LAYTON

806/745-4638
Telephone No.

(This space for State use)

APPROVED BY Harry W. Wink TITLE OC FIELD REPRESENTATIVE II/STAFF MANAGER DATE JUL 22 2003
Conditions of approval, if any: